



+/- 1/16" tolerances on dimensions unless specified
Specifications and procedures subject to change without notice.



SPECIFICATIONS

- Dissipative Low Charging Vinyl Badge Holder
 - Material Thickness: 0.012" (0.3 mm) front & 0.024" (0.6 mm) back
 - Material Tolerance (thickness): $\pm 10\%$
 - Material Color: matte front & back
- Highly visible yellow header with ESD protective symbol
- Includes a 1/8" (3 mm) x 9/16" (14 mm) punch through slot, setback 3/8" (10 mm) from top
- 4" (101 mm) x 3-3/8" (86 mm) (Outer Dimension)
- Opening setback 3/4" (19 mm) from top with zipper closure
- Embossing with: Menda and Made In America along the bottom of the badge holder
- Dissipative vinyl 1×10^4 to $< 1 \times 10^{11}$ ohms, per ANSI/ESD STM11.11. Meets ANSI/ESD S20.20 and ANSI/ESD S541
- Genuine Made In America - accept no substitutes
- We can do customs just let us know your insert size

"It should be understood that any object, item, material or person could be a source of static electricity in the work environment. Removal of unnecessary nonconductors, replacing nonconductive materials with dissipative or conductive materials and grounding all conductors are the principle methods of controlling static electricity in the workplace, regardless of the activity." [ESD Handbook ESD TR20.20-2008 section 2.4 Sources of Static Electricity]

⚠ WARNING: This product can expose you to chemicals including DINP, which is known to the State of California to cause cancer. For more information go to <http://www.p65warnings.ca.gov/>

ESD DISSIPATIVE BADGE HOLDER, HORIZONTAL

MENDA

3651 WALNUT AVENUE, CHINO, CA 91710
PHONE: (909) 627-2453
WEBSITE: MENDATools.com

**DRAWING
NUMBER**
35017

DATE
October
2024