




Made in Italy



Blue

### Electrical Properties:

Property	Test Method	Value
Rtt Resistance (Blue top layer):	ANSI/ESD S4.1	1 x 10 <sup>6</sup> to < 1 x 10 <sup>9</sup> ohms
Rtt Resistance (Black bottom layer):	ANSI/ESD S4.1	< 1 x 10 <sup>5</sup> ohms

### Specifications:

**Construction:** Dual-layer Rubber  
**Thickness:** 0.080" (2mm)  
**Texture:\*** Smooth  
**Colors:\*** Blue

\*Color and texture may vary between lots and mils

**No Detectable Levels of Silicone or DOP:** Approved\* for used in Class 100 cleanrooms. [Request a sample](#) to test to your requirements.

**Grounding:** This material must be properly grounded for optimum electrical performance. See Tech Bulletin [TB-2000](#) for mat grounding instructions.

**Cleaning:** For optimum electrical performance, surface must be cleaned regularly using an ESD mat cleaner. We suggest using our [Reztore Surface & Mat Cleaner](#). Do not use cleaners with silicone. Silicone buildup will create an insulative film on the surface.

**Compatible with Workstation Continuous Monitors**

#### Disclaimer:

All statements, technical data, and recommendations contained herein are based upon tests we believe to be reliable. However, the accuracy or completeness thereof is not guaranteed. The proper and correct applications of products and data is the responsibility of the user. Statements or recommendations not contained herein shall have no force or effect unless embodied in a written agreement signed by authorized officers of Desco Industries, Inc.

#### RoHS 2, REACH, and Conflict Minerals Statement

None of the RoHS 2 restricted materials, or REACH substances of very high concern as of 2015/06/15, or Conflict Minerals are intentionally added in manufacturing this product. Ref: European Union Directive 2011/65/EU and Regulation (EC) No. 1907/2006/CE. See Desco [Limited Warranty](#) at Desco.com.

#### Limited Lifetime Warranty:

Desco warrants for one year that Statfree® matting products will be free of defects in materials and workmanship and will guarantee dissipative/conductive mat properties for the life of the mat. Damage to matting caused by misuse of any kind, including using inappropriate cleaners is not covered by [Desco Limited Warranty](#).

#### Mat Kit Item Numbers

Item	Item†	Size**
<a href="#">66302</a>	<a href="#">66311</a>	24" x 36"
<a href="#">66303</a>	<a href="#">66312</a>	24" x 48"
<a href="#">66304</a>	<a href="#">66313</a>	30" x 60"
<a href="#">66305</a>	<a href="#">66314</a>	30" x 72"

† Cleaned and Packaged in a Class 1000 Controlled Environment. Click [HERE](#) to learn more.

\* Although cleanroom requirements vary, Statfree® UC material will most likely meet the requirements for a class 100 or higher clean

#### Mat Top Kit Includes

- 1 Mat, size as specified
- 1 [14234](#) Grounding Kit
- 1 Sample (4oz) of [Reztore Mat Cleaner](#)

#### Tray Liner Item Number

Item	Item†	Size**
<a href="#">66301</a>	<a href="#">66310</a>	16" x 24"

Tray liner has 1" radius corners and does not include grounding hardware

#### Roll Material Item Number

Item	Size**
<a href="#">66300</a>	30" x 40'

Roll material does not include grounding hardware

#### \*\*Tolerances:

Width ± .0250"  
Length ± .0250" every 1 linear foot of running material.  
Thickness ±10%

Matting materials have a tendency to shrink slightly when first unrolled. In applications where length is critical, allow the material to relax for at least 4 hours before cutting to size. Using care, always trim with a sharp knife or razor blade.

Specifications and procedures subject to change without notice.

## STATFREE UC™ DISSIPATIVE DUAL LAYER ULTRA CLEAN RUBBER



DESCO WEST: 3651 WALNUT AVE., CHINO, CA 91710 WEB SITE: [Desco.com](#)  
PHONE (909) 627-8178

DESCO EAST: ONE COLGATE WAY, CANTON, MA 02021-1407  
PHONE (781) 821-8370

STATFREE UC™  
DRAWING PM-121

DATE:  
November  
2015