

4CH Programmable DC Power Supply

MPS-4 Series



- 4 in 1, easy to install and takes up small space
- Output voltage and current: 30V/5A; 30V/10A or 60V/3A; 60V/5A (30V/3A can be customized)
- Each channel is independently adjustable and isolated from each other
- Four channels simultaneously display voltage and current
- Voltage compensation function to ensure accuracy
- 1mV/0.1mA high resolution
- Linear power supply, low ripple
- Panel operation, it is convenient to be used independently

Standard RS-232 SENSE

Model	MPS-3054	MPS-30104	MPS-6034	MPS-6054
Rated output voltage	0~30V*4CH	0~30V*4CH	0~60V*4CH	0~60V*4CH
Rated output current	0~5A*4CH	0~10A*4CH	0~3A*4CH	0~5A*4CH
Transformation method	Linear power supply			
Load regulation rate	Voltage	$\leq 0.02\% + 5\text{mV}$		
	Current	$\leq 0.02\% + 5\text{mA}$		
Line regulation	Voltage	$\leq 0.02\% + 5\text{mV}$		
	Current	$\leq 0.02\% + 5\text{mA}$		
Set value resolution	Voltage	1mV		
	Current	0.1mA		
Setting accuracy (25°C±5°C)	Voltage	$\leq 0.05\% + 5\text{digits}$		
	Current	$\leq 0.05\% + 2\text{mA}$		
Readback resolution	Voltage	1mV		
	Current	0.1mA		
Readback accuracy	Voltage	$\leq 0.05\% + 5\text{digits}$		
	Current	$\leq 0.05\% + 2\text{mA}$		
Ripple and noise	Voltage	$\leq 2\text{mV(rms)}$	$\leq 5\text{mV(rms)}$	$\leq 2\text{mV(rms)}$
	Current	$\leq 5\text{mA(rms)}$	$\leq 5\text{mA(rms)}$	$\leq 5\text{mA(rms)}$
Temperature Coefficient	Operating environment	0 ~ 40 °C $\leq 80\%$ RH		
	Storage environment	-15 ~ 70 °C $\leq 80\%$ RH		
Interface	Standard	RS232		
size (W*H*D)	mm	480*142*370		
weight	kg	23	28	23
				28