XACS399

Harmony XAC, Single isolating block for power circuit, horizontal fixing centres 40mm, screw clamp terminal, 3 NC



Main

Range of Product	Harmony XAC
Product or Component Type	Isolating block
Component name	XACS
Electrical circuit type	Power circuit
Contact block application	Emergency stop push-button
Contact block type	Single
Product Compatibility	XACB
Contacts type and composition	3 NC
Mounting of block	Front mounting
Contact operation	Snap action

Complementary

Connections - terminals	Screw clamp terminals, 1 x 2.5 mm ² with or without cable end Screw clamp terminals, 2 x 1.5 mm ² with or without cable end	
Horizontal fixing centres	1.57 in (40 mm)	
Mechanical durability	1000000 cycles	
Contact code designation	A300 AC-15, Ue = 240 V, Ie = 3 A IEC 60947-5-1 appendix A Q300 DC-13, Ue = 250 V, Ie = 0.27 A IEC 60947-5-1 appendix A	
[Ui] rated insulation voltage	400 V 3)IEC 60947-1	
[Uimp] rated impulse withstand voltage	6 kV IEC 60947-1	
Rated operational power in W	3000 W AC-23B 400 V	
Net Weight	0.22 lb(US) (0.1 kg)	

Environment

Limitorinent		
Standards	EN 60947-3	
	IEC 60947-3	
	CSA C22.2 No 14	
Ambient air temperature for operation	-13158 °F (-2570 °C)	
Ambient Air Temperature for Storage	-40158 °F (-4070 °C)	
Vibration resistance	15 gn 10500 Hz)IEC 60068-2-6	
Shock resistance	100 gn IEC 60068-2-27	
Electrical shock protection class	Class II IEC 61140	
-		

Ordering and shipping details

22473 - PUSHBUTTON, PENDANTS	
CS2	
3389110647457	
1	
0.18 lb(US) (0.08 kg)	
No	
CZ	

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	1.73 in (4.4 cm)
Package 1 width	3.78 in (9.6 cm)
Package 1 Length	3.23 in (8.2 cm)
Unit Type of Package 2	S02
Number of Units in Package 2	50
Package 2 Weight	10.71 lb(US) (4.856 kg)
Package 2 Height	5.91 in (15 cm)
Package 2 width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, ar Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go t www.P65Warnings.ca.gov	
REACh Regulation	[™] REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EV RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	₽¥Yes	
China RoHS Regulation	☑ China RoHS Declaration	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.	

Contractual warranty

Warranty	18 months	