

Features:

- Saves time & Human efforts
- Less programming errors
- LED indication: download/upload
- Easily portable
- · easy to use

Specifications

Communication protocol Modbus

Rated supply voltage 1.8VDC to 5.5VDC

Uploading time 1sec
Downloading time 1sec

Dimensions 30mm(H) X 24mm(W)

X 13mm(D)


connection Plug In type

LED indication

| IDM condition | LED R | LED G |
|----------------------|-------|-------|
| No parameter loaded | Blink | OFF |
| Parameter loaded | ON | OFF |
| Upload in progress | Blink | ON |
| Download in progress | ON | ON |
| Error | Blink | Blink |

Independent Downloader module (IDM)





| IDINI Level | | |
|-------------|-------------------------------|--|
| Display | Parameter Description | |
| 19 | Independent Downloader Module | |
| UP | Upload from product to IDM | |
| 9. | Download from IDM to product | |
| 90 | Operation Successful | |
| ٤٢ | Operation unsuccessful | |

| IDM Can be used | | | |
|-----------------|----------|--|--|
| TC544C | TC244CX | | |
| TC513CX | TC344CX | | |
| TC203CX | PID500-U | | |
| TC303CX | CH403B | | |

Ordering Information

| Product Code | Discription |
|--------------|-------------------------------|
| IDM | Independent Downloader Module |

www.selec.com 1