

Advantech Panel PCs

Diverse offerings for a wide range of applications

- / Introduction
- / Benefits and Features
- / Selection Guide



ADVANTECH

Enabling an Intelligent Planet

www.advantech.com

Advantech's PPC Product Family

Reliable, Cost-Effective, and High-Performance Industrial Panel PCs

Advantech's PPC (panel PC) product family offers highly scalable, economical solutions in a range of performance classes that support various display sizes to satisfy diverse equipment manufacturing and process automation applications. The PPC product portfolio includes an all-in-one series (PPC-3000) and a configurable series (PPC-6000C). The all-in-one series features an optimized design, compact form factor, and industrial-grade specifications, such as rich I/O, flexible expansion slots, and a wide operating temperature range. Regarding the configurable series, these products are designed to be equipped with any mini-ITX motherboard according to price and functionality.



Features



IP65-rated true-flat panel

In addition to IP65 certification for dust and water resistance, Advantech's panel PCs are equipped with a true flat P-CAP/resistive touchscreen, giving the system an elegant and stylish appearance.



Rich industrial-grade I/O

To ensure excellent connectivity for integrating devices and peripherals, Advantech's PPC systems are equipped with multiple industrial-grade I/O, including isolated RS-422/485, GPIO, RS-232, USB 3.0, DisplayPort, and Line Out ports.



intel Core i

PPC-3001S

- 6th gen Intel® Core™ i processor
- PCAP touch screen control
- All-metal body

PPC-3181SW

21.5"

18.5"

PPC-3211SW

15.6"

PPC-3000S

- Intel® Celeron® N4200/N2930/ N2807 processor
- PCAP/resistive touch screen control
- All-metal body

intel A

PPC-31

PPC-3001

- 6/7th gen Intel® Core™ i processor
- PCAP/resistive touch screen control
- PCIe x4/PCI expansion

PPC-3151W

15.6"

21.5"

PPC-3151

15"

PPC-3211W

PPC-3000

- Intel® Atom™ E3845/E3940 processor
- Wide operating temperature (-20 ~ 60 °C/-4 ~ 140 °F)
- Resistive touch screen control
- PCIe x1/PCI expansion

PPC-3170

PPC-6000C

PPC-6171C

17"

19"

PPC-6191C

15"

PPC-6151C

Expansion slots

PPC series systems feature expansion slots that support a range of optional riser cards, such as PCI, PCIe x1, and PCIe x4, to enable flexible expansion according to the platform specifications.



Wide operating temperature range

All PPC-3000 series systems equipped with an Intel® Atom™ processor support a wide operating temperature range of -20 ~ 60 °C, making them suitable for operation in harsh environments.



Wide input power range

With support for a wide input power range of 12 ~ 24 V_{DC}, Advantech PPC systems can be operated in various industrial environments without necessitating an additional power converter or generating increased energy costs.

Atom



All-metal body

PPC-3000S series products are designed with an all-metal body to ensure an elegant and streamlined appearance.

Accessories

PPC-IPS-AE



PPC-STAND-A1E



PPC-ARM-A03



A swivel arm equipped with a C-clamp to enable installation on any surface. The swivel arm supports 360-degree rotation.



PPC-174T-WL-MTE

A compact wall-mount kit that supports 360-degree rotation and vertical/horizontal viewing angle adjustment.



PPC-WLAN-C1E

An optional WiFi + BT4.2 Combo Module with dual antennae (2T2R) and 802.11 a/b/g/n/ac support.

	PPC-3001S			PPC-3000S										
Model	PPC-3151SW/3181SW/3211SW			PPC-3060S		PPC-3100S/3120S/3150S/3210SW				PPC-3150SW/3180SW				
CPU	6th Gen Intel® Core™ i5-6300U			Intel® Celeron® N2807 (1.58 GHz)		Intel® Celeron® N2930 (1.86 GHz)				Intel® Pentium® N4200 (1.1G up to 2.5GHz)				
Memory	1 x SODIMM DDR4 1866/2133 MHz (up to 16 GB)			1 x SODIMM DDR3L 1333 (up to 4 GB)		1 x SODIMM DDR3L, 1333 MHz (up to 8 GB)				1 x SODIMM, DDR3L 1600/1866 (up to 8GB)				
Display Size	15.6"	18.5"	21.5"	6.5"		10.4"	12.1"	15"	21.5"	15.6"	18.5"			
Max. Resolution	1920 x 1080	1366 x 768	1920 x 1080	640 x 480		800 x 600	1024 x 768	1024 x 768	1920 x 1080	1366 x 768	1366 x 768			
Luminance (cd/m²)	450	450	300	700		400	500	400	300	400	450			
Backlight MTBF	50,000	50,000	50,000	50,000		30,000	30,000	50,000	50,000	50,000	50,000			
Touchscreen	Multi-touch projected capacitive			5-wire analog resistive				PCT	Multi-touch projected capacitive					
Network (LAN)	2 x GbE (Intel® I211-AT, I219LM)			2 x GbE (Intel® I211)				2 x GbE (Intel® I211)						
I/O	1 x RS-232, 1x RS-232/422/485 (by BIOS), 2 x USB 3.0, 2 x USB 2.0, 1 x HDMI, 1 x TPM2.0 (optional module),			1 x RS-232, 1x RS-232/422/485 (by BIOS), 2 x USB 2.0, 1 x USB 3.0,				1 x RS-232, 1x RS-232/422/485 (by BIOS), 2 x USB 3.0, 2 x USB 2.0, 1 x Line-out, 1 x HDMI,						
Storage	1 x 2.5" SATA bay, 1 x mSATA bay			1 x 2.5" SATA bay (optional), 1 x mSATA bay				1 x 2.5" SATA bay (optional), 1 x mSATA bay						
Expansion Slots	N/A			N/A				N/A						
Additional Expansion	1 x Full-size Mini PCIe			1 x Full-size Mini PCIe				1 x Full-size Mini PCIe						
Input Power	12 ~ 24 V _{DC}			12 ~ 24 V _{DC}				12 ~ 24 V _{DC}						
Operating Temperature	0 ~ 50 °C with SSD			0 ~ 50 °C with SSD				0 ~ 50 °C with SSD						
Operating System	Windows 7/10 (64bit), Linux			Windows 7/10 (64bit), Linux, Android 6.0				Windows 10 (64bit), Linux, Android 8.0						

	PPC-3001			PPC-3000				PPC-6000C				
Model	PPC-3151	PPC-3151W/3211W	PPC-3100/3120-RE9A	PPC-3150/3170/3190		PPC-6121	PPC-6151C	PPC-6171C	PPC-6191C			
CPU	6th Gen Intel® Core™ i5-6300U	7th Gen Intel® Core™ i5-7300U	Intel® Atom™ E3940 (1.6 GHz)	Intel® Atom™ E3845 (1.91 GHz)		8th Gen Intel® Core™ i/ Celeron® processor	Supports processors with up to 65 W TDP depending on the Mini-ITX motherboard					
Memory	1 x SODIMM DDR4, 1866/2133 MHz (up to 16 GB)			1 x SODIMM DDR3L 1600/1866 MHz (up to 8 GB)	1 x SODIMM DDR3L 1333 MHz (up to 8 GB)		2 x 260-pin SO-DIMM DDR4, 2666 MHz (up to 32 GB, 16 GB per SODIMM)	Dependent on the Mini-ITX motherboard specifications				
Display Size	15"	15.6"	21.5"	10.4"	12.1"	15"	17"	19"	12.1"	15"	17"	19"
Max. Resolution	1024 x 768	1920 x 1080	1920 x 1080	800 x 600	1024 x 768	1024 x 768	1280 x 1024	1280 x 1024	1024 x 768	1024 x 768	1280 x 1024	1280 x 1024
Luminance (cd/m²)	400	450	300	400	600	400	350	350	600	400	350	350
Backlight MTBF	50,000	50,000	50,000	30,000	50,000	50,000	50,000	50,000	50,000	50,000	50,000	50,000
Touchscreen	Multi-touch projected capacitive			5-wire analog resistive		5-wire analog resistive		5-wire analog resistive	5-wire analog resistive			
Network (LAN)	2 x GbE (Intel® I211-AT, I219LM)			2 x GbE (Intel® I210)		2 x GbE (Intel® I210)		2 x GbE (Intel® I211-AT, I219LM)	Dependent on the Mini-ITX motherboard specifications			
I/O	1 x isolated RS-422/485, 4 x RS-232 (2 x by optional module), 1 x GPIO (8 channels, TTL level), 4 x USB 3.0, 1 x VGA, 1 x DP1.2, 1 x Line-Out, 1 x Mic-In, 1 x TPM2.0 (optional module)			4 x RS-232, 1 x isolated RS-422/485 (by BIOS), 4 x USB 3.0, 1 x Line-out, 1 x Mic-in, 1 x VGA, 1 x HDMI, 1 x GPIO (8 channels, TTL),	1 x isolated RS-422/485, 4 x RS-232 (2 x by optional module), 1 x GPIO (8 channels, TTL level), 1 x USB 3.0, 3 x USB 2.0, 1 x VGA, 1 x DP1.1a, 1 x Line-Out, 1 x Mic-In		4 x RS-232, 1 x isolated RS422/485, 4 x USB3.1, 1 x VGA, 1 x HDMI 1.4 , 1 x Mic in, 1 x Line out, 1 x GPIO (8channels, TTL)	4 x Reserved ports 2 x WLAN antenna ports				
Storage	1 x 2.5" SATA bay, 1 x M.2 bay (22 x 42 mm)	2 x 2.5" SATA bay, 1 x M.2 bay (22 x 42 mm)	1 x 2.5" SATA bay, 1 x mSATA bay	1 x 2.5" SATA bay, 1 x mSATA bay		1 x 2.5" SATA bay, 1 x mSATA bay	1 x 2.5" SATA bay, 1 x mSATA bay		1 x 2.5" SATA bay, 2 x 2.5" SATA bay (optional)			
Expansion Slots	1 x PCIe x4 or PCI			N/A	(optional) 1 x PCIe x1 or 1 PCI	1 x PCI or 1 x PCIe x1		(optional) 1 x PCIe x4 or 1 x PCI	2 x PCI or 1 x PCIe x 4 (in the accessory box)			
Additional Expansion	1 x Full-size Mini PCIe, (optional) 1 x Cfast,			1 x Full-size Mini PCIe	1 x Full-size Mini PCIe, (optional) 1 x Cfast,		1 x M.2 2230 (E Key)	Dependent on the Mini-ITX motherboard specifications				
Input Power	9 ~ 32 V _{DC}	9 ~ 32 V _{DC}	12 ~ 32 V _{DC}	9 ~ 32 V _{DC}	9 ~ 32 V _{DC}		12 ~ 30 V _{DC}	100 ~ 240 V _{AC} @ 50/60 Hz				
Operating Temperature	0 ~ 50 °C with SSD			-20 ~ 60 °C with SSD	-20 ~ 60 °C with SSD		0 ~ 50 °C with SSD	0 ~ 50 °C with 35W CPU 0 ~ 45 °C with 65W CPU				
Operating System	Windows 7/10 (64bit), Linux	Windows 10 (64bit), Linux	Windows 10 (64bit), Linux, Android 8.0	Windows 10 (64bit), WEC7, Linux, Android 6.0	Windows 10 (64bit), Linux		Windows 10 (64bit), Linux	Dependent on the Mini-ITX motherboard specifications				

Regional Service & Customization Centers

China | Kunshan
86-512-5777-5666

Taiwan | Taipei
886-2-2792-7818

Netherlands | Eindhoven
31-40-267-7000

Poland | Warsaw
00800-2426-8080

USA | Milpitas, CA
1-408-519-3898

Worldwide Offices

Greater China

China

Toll Free	800-810-0345
Beijing	86-10-6298-4346
Shanghai	86-21-3632-1616
Shenzhen	86-755-8212-4222
Chengdu	86-28-8545-0198
Hong Kong	852-2720-5118

Taiwan

Toll Free	0800-777-111
Taipei & IoT Campus	886-2-2792-7818
Taichung	886-4-2372-5058

Middle East and Africa

Israel 072-2410527

Asia

Japan

Toll Free	0800-500-1055
Tokyo	81-3-6802-1021
Osaka	81-6-6267-1887
Nagoya	81-0800-500-1055

Korea

Toll Free	080-363-9494/5
Seoul	82-2-3660-9255

Singapore

Singapore 65-6442-1000

Malaysia

Kuala Lumpur 60-3-7725-4188
Penang 60-4-537-9188

Thailand

Bangkok 66-02-2488306-9

Vietnam

Hanoi 84-24-3399-1155

Indonesia

Jakarta 62-21-751-1939

Australia

Toll Free	1300-308-531
Melbourne	61-3-9797-0100

India

Bangalore 91-80-6814-4600
Pune 91-94-2260-2349

Europe

Netherlands

Eindhoven	31-40-267-7000
Breda	31-76-523-3100

Germany

Toll Free	00800-2426-8080/81
Munich	49-89-12599-0
Düsseldorf	49-2103-97-855-0

France

Paris 33-1-4119-4666

Italy

Milan 39-02-9544-961

UK

Newcastle 44-0-191-262-4844
London 44-0-870-493-1433

Spain

Madrid 34-91-668-86-76

Sweden

Stockholm 46-0-864-60-500

Poland

Warsaw 48-22-31-51-100

Russia

Moscow 8-800-555-01-50
St. Petersburg 8-800-555-81-20

Czech Republic

Ústí nad Orlicí 420-465-524-421

Ireland

Galway 353-91-792444

Americas

North America

Toll Free	1-888-576-9668
Cincinnati	1-513-742-8895
Milpitas	1-408-519-3898
Irvine	1-949-420-2500
Ottawa	1-815-433-5100

Brazil

Toll Free	0800-770-5355
São Paulo	55-11-5592-5367

Mexico

Toll Free	1-800-467-2415
Mexico City	52-55-6275-2727

www.advantech.com

Please verify specifications before quoting. This guide is intended for reference purposes only.

All product specifications are subject to change without notice.

No part of this publication may be reproduced in any form or by any means, electronic, photocopying, recording or otherwise, without prior written permission of the publisher.

All brand and product names are trademarks or registered trademarks of their respective companies.

© Advantech Co., Ltd. 2019

Buy Now



8600000493

ADVANTECH

Enabling an Intelligent Planet