



# VSE180-2P32437

V180

CYLINDRICAL PHOTOELECTRIC SENSORS

**SICK**  
Sensor Intelligence.



Illustration may differ



### Ordering information

| Type           | Part no. |
|----------------|----------|
| VSE180-2P32437 | 6044035  |

Other models and accessories → [www.sick.com/V180](http://www.sick.com/V180)

### Detailed technical data

#### Features

|                                        |                                                 |
|----------------------------------------|-------------------------------------------------|
| <b>Functional principle</b>            | Through-beam photoelectric sensor               |
| <b>Dimensions (W x H x D)</b>          | 18 mm x 18 mm x 69.8 mm                         |
| <b>Housing design (light emission)</b> | Cylindrical                                     |
| <b>Housing length</b>                  | 69.8 mm                                         |
| <b>Thread diameter (housing)</b>       | M18 x 1                                         |
| <b>Optical axis</b>                    | Axial                                           |
| <b>Sensing range max.</b>              | 0 m ... 28 m                                    |
| <b>Sensing range</b>                   | 0 m ... 20 m                                    |
| <b>Focus</b>                           | Approx. 5°                                      |
| <b>Type of light</b>                   | Visible red light                               |
| <b>Light source</b>                    | LED <sup>1)</sup>                               |
| <b>Light spot size (distance)</b>      | Ø 1,100 mm (20 m)                               |
| <b>Angle of dispersion</b>             | Approx. 5°                                      |
| <b>Wave length</b>                     | 645 nm                                          |
| <b>Adjustment</b>                      | Potentiometer, 270° (Sensitivity) <sup>2)</sup> |

<sup>1)</sup> Average service life: 100,000 h at T<sub>U</sub> = +25 °C.

<sup>2)</sup> Receiver.

#### Mechanics/electronics

|                                     |                                   |
|-------------------------------------|-----------------------------------|
| <b>Supply voltage U<sub>B</sub></b> | 10 V DC ... 30 V DC <sup>1)</sup> |
| <b>Ripple</b>                       | ± 10 % <sup>2)</sup>              |

<sup>1)</sup> Limit values when operated in short-circuit protected network: max. 8 A.

<sup>2)</sup> May not fall below or exceed U<sub>V</sub> tolerances.

<sup>3)</sup> Without load.

<sup>4)</sup> Signal transit time with resistive load.

<sup>5)</sup> With light/dark ratio 1:1.

<sup>6)</sup> A = V<sub>S</sub> connections reverse-polarity protected.

<sup>7)</sup> B = inputs and output reverse-polarity protected.

<sup>8)</sup> D = outputs overcurrent and short-circuit protected.

|                                             |                                                       |
|---------------------------------------------|-------------------------------------------------------|
| <b>Power consumption, sender</b>            | 20 mA <sup>3)</sup>                                   |
| <b>Power consumption, receiver</b>          | 15 mA <sup>3)</sup>                                   |
| <b>Switching output</b>                     | PNP                                                   |
| <b>Switching mode</b>                       | Dark switching                                        |
| <b>Signal voltage PNP HIGH/LOW</b>          | Approx. $V_S - 1.8 \text{ V} / 0 \text{ V}$           |
| <b>Output current <math>I_{\max}</math></b> | $\leq 100 \text{ mA}$                                 |
| <b>Response time</b>                        | $\leq 0.5 \text{ ms}$ <sup>4)</sup>                   |
| <b>Switching frequency</b>                  | 1,000 Hz <sup>5)</sup>                                |
| <b>Connection type</b>                      | Connector M12, 3-pin                                  |
| <b>Circuit protection</b>                   | A <sup>6)</sup><br>B <sup>7)</sup><br>D <sup>8)</sup> |
| <b>Protection class</b>                     | III                                                   |
| <b>Weight</b>                               | 36 g                                                  |
| <b>Housing material</b>                     | Plastic, PBT/PC                                       |
| <b>Optics material</b>                      | Plastic, PMMA                                         |
| <b>Enclosure rating</b>                     | IP67                                                  |
| <b>Items supplied</b>                       | Fastening nuts (4 x)                                  |
| <b>Ambient operating temperature</b>        | -25 °C ... +55 °C                                     |
| <b>Ambient temperature, storage</b>         | -40 °C ... +70 °C                                     |

<sup>1)</sup> Limit values when operated in short-circuit protected network: max. 8 A.

<sup>2)</sup> May not fall below or exceed  $U_Y$  tolerances.

<sup>3)</sup> Without load.

<sup>4)</sup> Signal transit time with resistive load.

<sup>5)</sup> With light/dark ratio 1:1.

<sup>6)</sup> A =  $V_S$  connections reverse-polarity protected.

<sup>7)</sup> B = inputs and output reverse-polarity protected.

<sup>8)</sup> D = outputs overcurrent and short-circuit protected.

## Safety-related parameters


|                         |             |
|-------------------------|-------------|
| <b>MTTF<sub>D</sub></b> | 2,274 years |
| <b>DC<sub>avg</sub></b> | 0 %         |

## Classifications

|                     |          |
|---------------------|----------|
| <b>ECLASS 5.0</b>   | 27270901 |
| <b>ECLASS 5.1.4</b> | 27270901 |
| <b>ECLASS 6.0</b>   | 27270901 |
| <b>ECLASS 6.2</b>   | 27270901 |
| <b>ECLASS 7.0</b>   | 27270901 |
| <b>ECLASS 8.0</b>   | 27270901 |
| <b>ECLASS 8.1</b>   | 27270901 |
| <b>ECLASS 9.0</b>   | 27270901 |
| <b>ECLASS 10.0</b>  | 27270901 |
| <b>ECLASS 11.0</b>  | 27270901 |

|                       |          |
|-----------------------|----------|
| <b>ECLASS 12.0</b>    | 27270901 |
| <b>ETIM 5.0</b>       | EC002716 |
| <b>ETIM 6.0</b>       | EC002716 |
| <b>ETIM 7.0</b>       | EC002716 |
| <b>ETIM 8.0</b>       | EC002716 |
| <b>UNSPSC 16.0901</b> | 39121528 |

Adjustments




- ③ Sensitivity control 270°
- ④ LED indicator orange: switching output active
- ⑤ LED indicator green

Connection type



Connection diagram


Cd-057



- ① Sender
- ② Receiver


## Characteristic curve

VSE180-2, 28 m, axial




## Light spot size

VSE180-2, 28 m, axial




## Sensing range diagram

VSE180-2, 28 m, axial



**Dimensional drawing** (Dimensions in mm (inch))

VSE180-2, plastic, axial



- ① M12 male device connector, 4-pin
- ② Connection cable 2 m
- ③ Sensitivity control 270°
- ④ LED indicator orange
- ⑤ LED indicator green: strength indicator
- ⑥ Fastening nuts (2 x); A/F 22, PC

## SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

**For us, that is “Sensor Intelligence.”**

## WORLDWIDE PRESENCE:

Contacts and other locations –[www.sick.com](http://www.sick.com)