XLG3-1470F812 XLG

MEASURING AUTOMATION LIGHT GRIDS



SICK

20202

XLG3-1470F812 | XLG

MEASURING AUTOMATION LIGHT GRIDS



Ordering information

Туре	Part no.
XLG3-1470F812	1047926

Illustration may differ

Other models and accessories -> www.sick.com/XLG



Detailed technical data

Features	
Minimum detectable object (MDO)	Parallel beam, 35 mm ¹⁾
Beam separation	30 mm
Number of beams	50
Detection height	1,470 mm
Configuration	Parameterization interface (measuring)
¹⁾ MDO min. detectable object.	
Mechanics/electronics	
Light source	Infrared light
Wave length	880 nm
Supply voltage V _s	DC 18 V 30 V ¹⁾
Power consumption sender	240 mA ²⁾
Power consumption receiver	250 mA ²⁾
Ripple	< 5 V _{pp}
Output current I _{max.}	\leq 100 mA ³⁾
Output load, capacitive	100 nF
Output load, Inductive	1 H
Initialization time	1s
Switching output	3 x PNP
Inputs	1 x PNP
Dimensions (W x H x D)	34 mm x 1,564 mm x 29 mm
Connection type	Male connector M12, 8-pin
Housing material	Aluminum
Indication	7-segment display, 7-segment display
Synchronization	Cable
Enclosure rating	IP65 4)

¹⁾ Without load.

²⁾ Without load with 24 V.

³⁾ Typical value.

⁴⁾ Operating in outdoor condition only with a external protection housing.

XLG3-1470F812 | XLG

MEASURING AUTOMATION LIGHT GRIDS

Circuit protection	U _V connections, reverse polarity protected Output Q short-circuit protected Interference pulse suppression
Protection class	III
Weight	3.881 kg
Front screen	PMMA

¹⁾ Without load.

 $^{\rm 2)}$ Without load with 24 V.

³⁾ Typical value.

 $^{\rm 4)}$ Operating in outdoor condition only with a external protection housing.

Performance

Maximum range	7 m ¹⁾
Minimum range	Parallel beam: ≥ 0 mm
Operating range	5 m
Response time	Parallel beam, 8.5 ms ²⁾

 $^{\mbox{\sc 1})}$ No reserve for environmental issue and deterioration of the diode.

²⁾ With resistive load.

Ambient data

Shock resistance	10 g / IEC 68-2-29 / 16 ms
Vibration resistance	5 g, 10 Hz 55 Hz (IEC 68-2-6)
EMC	EN 60947-5-2
Ambient light immunity	Direct: 150,000 lx ¹⁾ Indirect: 200,000 lx ²⁾
Ambient operating temperature	-25 °C +55 °C
Ambient temperature, storage	-40 °C +70 °C

¹⁾ Sunlight.

 $^{2)}$ 200,000 lux up to a sensing range of 5 m and at a sensing range of 12 m 25,000 lux directly.

Classifications

ECLASS 5.0	27270910
ECLASS 5.1.4	27270910
ECLASS 6.0	27270910
ECLASS 6.2	27270910
ECLASS 7.0	27270910
ECLASS 8.0	27270910
ECLASS 8.1	27270910
ECLASS 9.0	27270910
ECLASS 10.0	27270910
ECLASS 11.0	27270910
ECLASS 12.0	27270910
ETIM 5.0	EC002549
ETIM 6.0	EC002549
ETIM 7.0	EC002549

XLG3-1470F812 | XLG

MEASURING AUTOMATION LIGHT GRIDS

ETIM 8.0	EC002549
UNSPSC 16.0901	39121528

Dimensional drawing (Dimensions in mm (inch))



	A Distance: XLG e	B dge – first beam
Beam separation XLG1 10 mm	49 (1.93)	160 (6.30)
Beam separation XLG2 20 mm	49 (1.93) ¹⁾ 59 (2.32) ²⁾	170 (6.69)
Beam separation XLG3 30 mm	69 (2.72)	180 (7.09)
Beam separation XLG5 50 mm	89 (3.50)	200 (7.87)

¹⁾ With even number of beams.

²⁾ With odd number of beams.

- Detection height (see optical performance)
 Beam spacing (30, 50 mm)
- ③ Status indicator: green, yellow, red LEDs
- ④ Indicator panel, 7-segment display
- ⑤ Terminals: M16 cable entry/connector M12, 12-pin
- 6 Configuration connector M8, 4-pin

Connection type and diagram

Connection type and diagram







Adjustments

Setting options, receiver



- ② Device error
- ③ No object in the light path
- ④ Contamination control
- ⑤ Blocked Beams Hold (BBH)
- ⑥ Activated teach-in procedure
- ⑦ ParamMode is active
- ⑧ Standby
- (9) Error: E1 = sync. error; E2 = less receiver signal; E9 = defect

XLG3-1470F812 | XLG MEASURING AUTOMATION LIGHT GRIDS

Recommended accessories

Other models and accessories -> www.sick.com/XLG

	Brief description	Туре	Part no.
Mounting brackets and plates			
**	Side mounting with T-nuts, 4 pieces, mounting hardware included	BEF-NUT-MLG	2023696
	Metal mounting bracket, compact, steel, zinc coated, Set, consisting of 4 pieces, without mounting hardware	BEF-WK-XLG	2029100
Terminal and	alignment brackets		
	4 pieces, Mounting kit 1, rotatable, swivel mount, plastic	BEF-2SMKEAKU4	2019649
Others			
	 Connection type head A: Female connector, M8, 4-pin, straight Connection type head B: Female connector, D-Sub, 9-pin, straight Signal type: Sensor/actuator cable Cable: 2 m Description: Sensor/actuator cable, unshielded Note: Rectangular plug-in system, parameterization cable 	YF8U14- 020VA3FDSA9	2023695
Se.	 Connection type head A: Female connector, M12, 8-pin, A-coded Connection type head B: Female connector, M12, 8-pin, A-coded Connection type head C: Male connector, M12, 8-pin, A-coded Note: Male connector M12, 8-pin, straight, to 1 x female connector M12, 8-pin, straight and 1 x female connector M12, 8-pin, straight 	SBO-02F12-SM	6029306
k. k.	 Connection type head A: Female connector, M12, 8-pin, straight, A-coded Connection type head B: Male connector, M12, 8-pin, straight, A-coded Signal type: Sensor/actuator cable Cable: 2 m, 8-wire, PUR, halogen-free Description: Sensor/actuator cable, shielded Application: Zones with oils and lubricants, Drag chain operation 	YF2A28- 020UA6M2A28	2096105
×.	 Connection type head A: Female connector, M12, 8-pin, straight, A-coded Connection type head B: Flying leads Signal type: Sensor/actuator cable Cable: 2 m, 8-wire, PVC Description: Sensor/actuator cable, shielded Application: Zones with chemicals 	YF2A28- 020VA6XLEAX	2096243
k. k.	 Connection type head A: Female connector, M12, 8-pin, straight, A-coded Connection type head B: Male connector, M12, 8-pin, straight, A-coded Signal type: Sensor/actuator cable Cable: 5 m, 8-wire, PUR, halogen-free Description: Sensor/actuator cable, shielded Application: Zones with oils and lubricants, Drag chain operation 	YF2A28- 050UA6M2A28	2096106
×.	 Connection type head A: Female connector, M12, 8-pin, straight, A-coded Connection type head B: Flying leads Signal type: Sensor/actuator cable Cable: 5 m, 8-wire, PVC Description: Sensor/actuator cable, shielded Application: Zones with chemicals 	YF2A28- 050VA6XLEAX	2096244
	 Connection type head A: Female connector, M12, 8-pin, straight, A-coded Connection type head B: Male connector, M12, 8-pin, straight, A-coded Signal type: Sensor/actuator cable Cable: 10 m, 8-wire, PUR, halogen-free Description: Sensor/actuator cable, shielded Application: Zones with oils and lubricants, Drag chain operation 	YF2A28- 100UA6M2A28	2096109

XLG3-1470F812 | XLG MEASURING AUTOMATION LIGHT GRIDS

	Brief description	Туре	Part no.
×.	 Connection type head A: Female connector, M12, 8-pin, straight, A-coded Connection type head B: Flying leads Signal type: Sensor/actuator cable Cable: 10 m, 8-wire, PVC Description: Sensor/actuator cable, shielded Application: Zones with chemicals 	YF2A28- 100VA6XLEAX	2096245
	 Connection type head A: Female connector, M12, 8-pin, angled, A-coded Connection type head B: Flying leads Signal type: Sensor/actuator cable Cable: 2 m, 8-wire, PVC Description: Sensor/actuator cable, shielded Application: Zones with chemicals 	YG2A28- 020VA6XLEAX	2096218
	 Connection type head A: Female connector, M12, 8-pin, angled, A-coded Connection type head B: Flying leads Signal type: Sensor/actuator cable Cable: 5 m, 8-wire, PVC Description: Sensor/actuator cable, shielded Application: Zones with chemicals 	YG2A28- 050VA6XLEAX	2096219

SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

WORLDWIDE PRESENCE:

Contacts and other locations -www.sick.com



Online data sheet

