

Integrated ultrasonic level gauge, 5 m range,
4-20 mA, G2A, direct lead, 3 m cable

LLUSCS01-5201 Liquid Level Sensors



Features

- Integrated LCD display
- High reliability
- Rugged industrial grade housing
- G2A process connection
- 4-20 mA output

Applications

- Petroleum Industry
- Water and sewage treatment
- Chemical Production
- Food and beverage
- Non-contact level monitoring

Description

The LLUSCS01-5201 Integrated Ultrasonic level gauge is a non-contact, highly reliable level measuring instrument. It is easy to install and maintain, and provides continuous level measurement without touching the medium. It is well suited for monitoring fluids of varying viscosity as well as granular solid materials, such as bulk dry goods.

General Specifications

Application:	Level Sensing
Sensor Type:	Integrated Ultrasonic
Electrical Connection:	Direct Lead
Process Connection:	G2A
Connection Type:	3 meter 2 wire cable
Output Signal:	4-20 mA
Resolution:	3mm or 0.1% (whichever is larger)

Description	Minimum	Typical	Maximum	Unit
Sensing Distance			5,000	mm
Resolution Ratio			5	mm
Accuracy		0.5		% Full Scale

Electrical Specifications

Description	Minimum	Typical	Maximum	Unit
DC Power Supply Voltage		24		VDC
Power Supply Current		30		mA
Power Supply Voltage			±5	%
Pressure Resistance			3	bar

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications:
[Integrated ultrasonic level gauge, 5 m range, 4-20 mA, G2A, direct lead, 3 m cable LLUSCS01-5201](#)

Integrated ultrasonic level gauge, 5 m range,
4-20 mA, G2A, direct lead, 3 m cable

LLUSCS01-5201 Liquid Level Sensors



Power Consumption	≤0.75	W
-------------------	-------	---

Material Specifications

Description	Material
Cable Material	PVC
Housing Material	Polycarbonate

Notes: Resistant to weak acids and alkali; Display: IP65

Environmental Specifications

Temperature (Operating)	-20 deg C to 60 deg C
Temperature (Probe Resistance)	-20 deg C to 80 deg C
Ingress Protection	IP68

The Infinite Electronics portfolio includes coaxial cable assemblies, connectors, adapters and custom products, as well as our wireless product line which includes antennas, RF amplifiers, lightning and surge protectors, and NEMA rated enclosures.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. L-com reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. L-com does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and L-com does not assume any liability arising out of the use of any part or documentation.

LLUSCS01-5201 CAD Drawing

Integrated ultrasonic level gauge, 5 m range, 4-20 mA, G2A, direct lead, 3 m cable

