

Integrated ultrasonic level gauge, 10 m range, 4-20 mA, G2A, direct lead, 3 m cable

# LLUSCS01-5202 Liquid Level Sensors



#### **Features**

- · Integrated LCD display
- High reliability
- · Rugged industrial grade housing

## **Applications**

- · Petroleum Industry
- · Water and sewage treatment
- · Chemical Production

- · G2A process connection
- 4-20 mA output
- · Food and beverage
- · Non-contact level monitoring

### **Description**

The LLUSCS01-5202 Integrated Ultrasonic level guage is a non-contact, highly reliable level measuring instrument. It is easy to install and maintain, and provides continuous level measurement without touching the medium. It is well suited for monitoring fluids of varying viscosity as well as granular solid materials, such as bulk dry goods.

## **General Specifications**

Application: Level Sensing

Sensor Type: Integrated Ultrasonic

Electrical Connection: Direct Lead

Process Connection: G2A

Connection Type: 3 meter 2 wire cable

Output Signal: 4-20 mA

Resolution: 3mm or 0.1% (whichever is larger)

Description	Minimum	Typical	Maximum	Unit
Sensing Distance			10,000	mm
Resolution Ratio			5	mm
Accuracy		0.5		% Full Scale

#### **Electrical Specifications**

1

Description	Minimum	Typical	Maximum	Unit	
DC Power Supply Voltage		24		VDC	
Power Supply Current		30		mA	
Power Supply Voltage			±5	%	
Pressure Resistance			3	bar	

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Integrated ultrasonic level gauge, 10 m range, 4-20 mA, G2A, direct lead, 3 m cable LLUSCS01-5202



Integrated ultrasonic level gauge, 10 m range, 4-20 mA, G2A, direct lead, 3 m cable

# LLUSCS01-5202 Liquid Level Sensors



Power Consumption ≤0.75 W

# **Material Specifications**

Description	Material	
Cable Material	PVC	
Housing Material	Polycarbonate	

Notes: Resistant to weak acids and alkali; Display: IP65

#### **Environmental Specifications**

Temperature (Operating) -20 deg C to 60 deg C
Temperature (Probe Resistance) -20 deg C to 80 deg C

Ingress Protection IP68

The Infinite Electronics portfolio includes coaxial cable assemblies, connectors, adapters and custom products, as well as our wireless product line which includes antennas, RF amplifiers, lightning and surge protectors, and NEMA rated enclosures.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. L-com reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. L-com does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and L-com does not assume any liability arising out of the use of any part or documentation.

# LLUSCS01-5202 CAD Drawing

Integrated ultrasonic level gauge, 10 m range, 4-20 mA, G2A, direct lead, 3 m cable

