Specifications



Photo is representative





Eaton E59-M18A109A01-A1

Eaton iProx Sensor, E59, Straight, 18 mm, Shielded, 360° viewable LED, Dual key micro, 2-wire, 200 mA at 20-132 V, 3 pin, <1% sensing range, 2-wire AC, NO, 20-132V

| General specifications | |
|-------------------------|---|
| PRODUCT NAME | Eaton E59 iProx programmable inductive proximity sensor |
| CATALOG NUMBER | E59-M18A109A01-A1 |
| UPC | 782116183371 |
| PRODUCT LENGTH/DEPTH | 2.73 in |
| PRODUCT HEIGHT | 0.71 in |
| PRODUCT WIDTH | 0.71 in |
| PRODUCT WEIGHT | 0.7 lb |
| WARRANTY | 1 year |
| COMPLIANCES | CE Marked |
| CERTIFICATIONS | UL Listed CSA Certified |



| Product specifications | |
|--------------------------------|---|
| ТҮРЕ | E59 |
| CONTACT RATING | 200 mA at 20-132 V |
| ACTUATOR FUNCTION | Shielded |
| ACCURACY | < 1% sensing range |
| ENCLOSURE MATERIAL | 303 stainless steel |
| CONNECTION | Dual key micro |
| CONTACT CONFIGURATION | 2-wire AC, NO |
| SERIES | E59 |
| NUMBER OF WIRES | 2 |
| ENVIRONMENTAL RATING | NEMA 4, NEMA 4X, NEMA 6, NEMA 6P, NEMA 12, NEMA 13, IP67, IP69K |
| TEMPERATURE RATING | -40 to 158 °F |
| NUMBER OF PINS | 3 |
| OPERATING TEMPERATURE - MAX | 158 °F |
| OPERATING TEMPERATURE - MIN | -40 °F |
| MAXIMUM AC CURRENT | 200 mA |
| INPUT VOLTAGE | 20-132 V |
| SIZE | 18 |
| LED INDICATOR | 360 ° viewable LED |

| Resources | |
|-------------------------------|--|
| MULTIMEDIA | We make what matters |
| SPECIFICATIONS AND DATASHEETS | Eaton Specification Sheet - E59-M18A109A01-A1 |
| | |

| PROJECT NAME: | |
|-----------------|--|
| PROJECT NUMBER: | |
| PREPARED BY: | |
| DATE: | |



Eaton Corporation plc

Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Eaton is a registered trademark.

Follow us on social media to get the latest product and support information.

All other trademarks are property of their respective owners.

Reserved.

