



Industrial Power Strip, 6-Outlet, 6 ft. (1.8 m) Cord, Beige

MODEL NUMBER: 6SPDX



Highlights

- 6 outlets
- 6-ft. (1.83 m) cord
- 12.5-in. length
- · Lighted master switch
- · All-metal housing

Package Includes

- 6SPDX Power Strip
- · Warranty information
- Instruction manual

Description

The 6SPDX Power Strip offers a convenient method of power distribution in workbench, wall-mount or floor-mount applications. Includes six NEMA 5-15R outlets with 1.5-inch center-to-center spacing, six-foot (1.8-meter) AC line cord and keyhole mounting tabs for installation in a wide variety of applications. Corded, multi-outlet strip reduces cabling clutter and enables the connection of multiple electrical devices to a single AC wall socket. Unfiltered electrical pass-through makes the 6SPDX ideal for distributing alternate waveform UPS or generator power. Features rugged metal housing, lighted power switch with integrated 15A resettable circuit breaker and attractive beige color scheme.

Features

- Multi-outlet power strip offers convenient power distribution in workbench, wallmount or floor mount applications
- Includes 6 NEMA 5-15R output receptacles with 1.520-in. center-to-center spacing
- Lighted combination power switch with integrated circuit breaker
- Keyhole mounting tabs for installation in a wide variety of applications
- UL1363 (USA), cUL (Canada)
- 15A power handling capacity
- 6-ft. (1.83 m) AC line cord

Specifications

OVERVIEW		
UPC Code	037332108234	
INPUT		
Nominal Input Voltage(s) Supported	120V AC	
Recommended Electrical Service	15A 120V	





Voltage Compatibility (VAC)	120	
Input Plug Type	NEMA 5-15P	
Input Cord Length (ft.)	6	
Right-Angle Plug	No	
Input Cord Length (m)	1.83	
Integrated Cord Clip	No	
OUTPUT		
Frequency Compatibility	50 / 60 Hz	
Output (Watts)	1800	
Output Receptacles	(6) 5-15R	
Circuit Breaker (amps)	15	
Transformer Accommodation	(2) Yes	
Outlet Orientation	Single row of 6	
Right-Angle Outlets	No	
Outlet Spacing	1.520 in.	
USER INTERFACE, ALERTS & CONTROLS		
Switches	Lighted combination switch / circuit breaker	
PHYSICAL		
Color	Beige	
Material of Construction	Metal	
Power Cord Color	Beige	
Housing Color	Beige	
Mounting Holes or Slots	Yes	
Slot or Hole Mount Measurement (Center to Center)	203.20mm	
Outlets Measurement (Center to Center)	3.05 in.	
Receptacle Color	Beige	
Shipping Dimensions (hwd / in.)	2.25 x 6.00 x 14.25	
Shipping Dimensions (hwd / cm)	5.72 x 15.24 x 36.20	
Shipping Weight (lbs.)	2.41	
Shipping Weight (kg)	1.09	
Unit Dimensions (hwd / in.)	1.500 x 12.500 x 2.500	
Unit Dimensions (hwd / cm)		
Offic Difficusions (fiwa / cm)	31.75 x 6.35 x 3.8	
Outlet Spacing	31.75 x 6.35 x 3.8 1.520 in.	





FEATURES & SPECIFICATIONS		
Antimicrobial	No	
Built-In Circuit Breaker	Yes	
STANDARDS & COMPLIANCE		
Product Certifications	cUL Listed; UL 1363; UL Listed	
Product Compliance	RoHS	
WARRANTY & SUPPORT		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

1000 Eaton Boulevard Cleveland, OH 44122 United States https://tripplite.eaton.com © 2025 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.