



Powering Business Worldwide

Eaton Internal Replacement Battery Cartridge (RBC) for Select 3kVA Line-Interactive & Online UPS Systems

MODEL NUMBER: 744-A3122



UPS backup battery cartridge replaces the expired or aging internal battery in your Eaton 3kVA Line-Interactive or Online UPS system.

Features

UPS Replacement Battery Cartridge for Select Eaton 9PX and SmartOnline UPS Systems

This UPS backup battery replacement is compatible with Eaton's 5PX3000RTG2, 5PX3000RTNG2, 5PX3000HRTG2, 5PX3000HRTNG2, 9PX3000RT, 9PX3000RTN, 9PX3000GRT, 9PX3000GLRT, Tripp Lite series SMART3000RM2U, SMART3000RM2UN, SMART3000RML2U, SU3000RTXLCD2UTAA, SUINT3000LCD2U, SU3000RTXLCD2U, and SU3000RTXLCD2UN UPS systems. Eaton UPS batteries have an expected lifespan of three to five years, so you should take proactive steps to avoid a dead battery and ensure continuous uptime.

Comes Pre-Wired for Quick, Easy Installation

The sealed lead acid (SLA) 744-A3122 internal battery cartridge is hot-swappable, allowing you to install it without powering down any connected equipment. Built to function in a wide range of operating temperatures, the 744-A3122 has been carefully screened and certified to restore your UPS system's runtime performance to its original specifications. It is leakproof, requires no maintenance and comes pre-wired for quick and easy installation in your Line-Interactive and Online UPS systems.

Specifications

OVERVIEW	
UPC Code	743172089786
INPUT	
Input Phase	Single-Phase
BATTERY	
Battery Type	Valve Regulated Lead Acid (VRLA)

Highlights

- Replacement battery backup for select Eaton 3kVA 5PX G2, Eaton series SmartPro 3kVA; 9PX and Eaton series SmartOnline UPS systems
- Carefully screened and certified to restore UPS runtime to original specs
- Leakproof internal battery cartridge requires no regular maintenance
- Ships ready for immediate UPS installation to prevent downtime

System Requirements

Compatible only with Eaton's 5PX3000RTG2, 5PX3000RTNG2, 5PX3000HRTG2, 5PX3000HRTNG2, 9PX3000RT, 9PX3000RTN, 9PX3000GRT, 9PX3000GLRT, SMART3000RM2U (2023 redesign), SMART3000RM2U (2023 redesign), SMART3000RML2U (2023 redesign), SU3000RTXLCD2UTAA, SU3000RTXLCD2U (2023 redesign), SU3000RTXLCD2UN (2023 redesign), and SUINT3000LCD2U (2024 redesign) UPS systems

Package Includes

744-A3122 Internal Replacement Battery Cartridge



Powering Business Worldwide

Battery Replacement Description	Hot-swappable, user replaceable batteries. Re-use existing wiring harness.
Hot Swap Battery	Yes
PHYSICAL	
Unit Dimensions (hwd / in.)	2.640 x 8.270 x 18.310
Unit Weight (lbs.)	34.8
Unit Weight (kg)	15.79
ENVIRONMENTAL	
Operating Temperature Range	32° to 104°F (0° to 40°C)
APPLICATIONS	
Used With	5PX3000RTG2, 5PX3000RTNG2, 5PX3000HRTG2, 5PX3000HRTNG2, 9PX3000RT, 9PX3000RTN, 9PX3000GRT, 9PX3000GLRT, SMART3000RM2U (2023 redesign), SMART3000RM2U (2023 redesign), SMART3000RMXL2U (2023 redesign), SU3000RTLCD2UTAA, SU3000RTLCD2U (2023 redesign), SU3000RTLCD2UN (2023 redesign), SUINT3000LCD2U (2024 redesign)
STANDARDS & COMPLIANCE	
Product Certifications	UL Listed; cUL Listed
Product Compliance	FCC (USA); CE (Europe)

1000 Eaton Boulevard
Cleveland, OH 44122
United States
<https://tripplite.eaton.com>

© 2025 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.