



Powering Business Worldwide

Eaton 9PX 180V Extended Battery Module (EBM) for 9PX6KUS UPS, 3U Rack/Tower, TAA

MODEL NUMBER: 9PXEBM180RTUS



Sealed lead-acid extended battery module (EBM) provides extended runtime for compatible UPS system in small business, education, retail, financial or healthcare applications.

Features

Backup Battery Module Gives Your Compatible Eaton UPS System Extended Runtime

The 9PXEBM180RTUS offers extended battery runtime when used in conjunction with Eaton's TAA-compliant 9PX6KUS 9PX UPS system. It can also be daisy-chained for a maximum of four matching battery packs to deliver even longer extended-run operation. Heavy-gauge cabling with high-current DC connectors is included for safe, simple installation.

Supports 3U Rack or Tower Installation

This backup battery pack's multi-use form factor supports mounting in 3U of space in an EIA-standard 19-inch rack using the included 4-post rail kit. You can also adapt it for tower installation using the included support stands.

TAA-Compliant for GSA Schedule Purchases

The 9PXEBM180RTUS is compliant with the Federal Trade Agreements Act (TAA), which makes it eligible for GSA (General Services Administration) Schedule and other federal procurement contracts.

Versatile Installation Options

For installation in 2-post rackmounts, one RK2PC mounting kit is required for each UPS, EBM, PPDM, or transformer.

Highlights

- Connects to expandable TAA-compliant Eaton 9PX UPS system for extended runtime
- Daisy-chain connector supports additional battery packs for even longer runtime
- Includes heavy-gauge cabling with high-current 180V DC connectors
- Supports 3U rack mounting or upright tower installation using included kit accessories
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

System Requirements

Compatible only with Eaton's TAA-compliant 9PX6KUS UPS system

Package Includes

- 9PXEBM180RTUS 180V Extended Battery Module
- External battery cable, 1 ft. (0.3 m)
- Tower support stands
- Rack-mounting hardware
- Quick start guide

Specifications

| OVERVIEW | |
|-----------------------------|--------------|
| UPC Code | 743172082558 |
| INPUT | |
| Input Phase | Single-Phase |
| UPS Input Cord Length (ft.) | 1 |
| UPS Input Cord Length (m) | 0.3 |



Powering Business Worldwide

| OUTPUT | |
|---|--|
| Individually Controllable Load Banks | No |
| BATTERY | |
| Battery Type | Valve Regulated Lead Acid (VRLA) |
| Expandable Runtime | No |
| DC System Voltage (VDC) | 180 |
| Replacement Battery Cartridge | 744-A1974 |
| Battery Management | ABM technology (3-stage charging extends battery service life by 50% and provides advance warning for battery replacement) |
| PHYSICAL | |
| Primary Form Factor | Rackmount; Tower |
| Rack Height | 3U |
| External Battery Pack Form Factor | Rack/Tower |
| Installation Form Factors Supported with Included Accessories | 4 post 19 inch rackmount |
| Installation Form Factors Supported with Optional Accessories | 2 post rackmount (eaton-2-post-rack-mount-rail-kit-for-9px-ups-RK2PC) |
| Minimum Required Rack Depth (cm) | 73.66 |
| Minimum Required Rack Depth (inches) | 29 |
| Unit Dimensions (hwd / in.) | 5.100 x 17.300 x 25.400 |
| Unit Weight (lbs.) | 150.000 |
| Unit Weight (kg) | 68.04 |
| ENVIRONMENTAL | |
| Operating Temperature Range | 32° to 104°F (0° to 40°C) |
| Relative Humidity | 0-95% non-condensing |
| STANDARDS & COMPLIANCE | |
| Product Certifications | cUL Listed; NOM (Mexico) |
| Product Compliance | ENERGY STAR Qualified; RoHS; Trade Agreements Act (TAA) |
| WARRANTY & SUPPORT | |
| Product Warranty Period (U.S. & Canada) | 3-year limited warranty |
| Extended Service Plans | ADVANCED DEPOT EXCHANGE Service Part Number: 9SW5Y-3000BCExpedited parts coverage for 5 yearsParts, electronics and UPS batteries coverageNext business day shippingTechnical support 5-YEAR ON-SITE PLAN (US ONLY) Service Part Number: WEBN75XX-7000BCOn-site parts and labor coverage for years 5Parts, electronics and UPS batteries coverage24x7 on-site labor coverage, next-day responseNext-day shippingTechnical support |



Powering Business Worldwide

1000 Eaton Boulevard
Cleveland, OH 44122
United States
<https://tripplite.eaton.com>

© 2025 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.