



BP48VP2U02TAA EXTENDED BATTERY MODULE

The Extended Battery Module offers extended run-times during power outages.



The CyberPower BP48VP2U02TAA is a rack/tower convertible Extended Battery Module (EBM) that extends battery runtimes during power outages and is designed for the following Smart App Sinewave UPS systems: PR1500RTXL2UTAA, PR2000RTXL2UTAA, PR3000RTXL2UTAA.

This EBM takes 2U of rack space and can be installed in either a rack or tower configuration to match the UPS form factor. Battery equalization technology improves battery life, and toolless battery panel access makes battery replacement fast and simple.

With a three-year lifetime limited warranty, you can trust CyberPower's commitment to the quality of the BP48VP2U02TAA.

COMPATIBLE APPLICATIONS

- PR1500RTXL2UTAA UPS Systems
- PR2000RTXL2UTAA UPS Systems
- PR3000RTXL2UTAA UPS Systems

FEATURES

- 48 V/70 A Output
- Fast Charge Technology
- 2U Rack/Tower Form Factor
- Three-Years Limited Warranty

SPECIFICATIONS

GENERAL

Voltage 48 V

Amperage 70 A

BATTERY

Battery Type Sealed Lead-Acid

Battery Size 12 V/9 Ah

Hot-Swappable Yes

Replacement Battery RB1290X4J

Battery Quantity 8

User Replaceable Yes

BATTERY - CONT.

Typical Recharge Time 6 Hours

Built-in Charger Yes

Replacement Battery Cartridge Quantity 2

PHYSICAL

Rack Size 2U

Dimensions (WxHxD) (in.) 17.1 x 3.4 x 19.7

Weight (lbs.) 66.2

Shipping Dimensions (WxHxD) (in.) 22.1 x 10.8 x 24.4

Shipping Weight (lbs.) 80.7

BP48VP2U02TAA EXTENDED BATTERY MODULE



SPECIFICATIONS CONT.

ENVIRONMENTAL

Operating Temperature	32°F - 104°F (0 - 40°C)
Operating Relative Humidity	0% - 95% (non-condensing)
Maximum Operating Elevation	10,000 ft (3,000 m)
Storage Temperature	5°F - 113°F (-15°C - 45°C)
Storage Relative Humidity	0 - 95% (non-condensing)
Maximum Storage Elevation	50,000 ft (15,000 m)

CERTIFICATIONS

Safety	CE, RCM, UL1778, cUL, FCC Class B, VCCI
Environmental	RoHS Compliant

WARRANTY

Product Warranty	Three-Years Limited
------------------	---------------------