



# CPS1220RM RACKMOUNT SURGE PROTECTOR



Industrial rack mount surge protectors designed to safeguard computer systems and networking equipment.

The CyberPower CPS1220RM, a 12-outlet (six front, six rear) rackmount power distribution unit (PDU), provides 100 – 125 V 20A output. It distributes power to 10 NEMA 5-20R receptacles from a single NEMA 5-20P input with unfiltered electrical pass-through. Designed for datacenters and other electrically demanding applications, the CPS1220RM has durable metal housing and a 15-foot AC power cord. It can be mounted either horizontally or vertically, includes a cord retention tray, and is ETL/RoHS certified. A three-year warranty covers the CPS1220RM for three years for as long as you own the product.

### TYPICAL APPLICATIONS

- VoIP Phone Systems
- Network Closets
- Data Centers
- Industrial Environments

### FEATURES

- Phase: Single
- Volts: 100 – 125 V
- Frequency: 60Hz
- Plug type: NEMA 5-20P
- Outlets: 12 NEMA 5-20R
- Outlet location: 6 Front / 6 Rear
- Size: 1U Rackmount
- Dimensions W x H x D: 17.25 x 1.75 x 4.75 in.
- Cord length (ft.): 15 ft.
- Warranty: 3-Year

### SPECIFICATIONS

INPUT	
Circuit Breaker	20A
Cord Length	15 ft. (4.6 m)
Input Plug Type	NEMA 5-20P
Maximum Input Current	20A
Nominal Input Voltage	120 VAC
Plug Style	Straight
Switch	Lighted On / Off

OUTPUT	
Nominal Output Voltage	120 VAC
Outlet Type	12 - NEMA 5-20R
Outlets - Front	6
Outlets - Rear	6
Outlets - Total	12
Overload Protection	20A
SURGE PROTECTION & FILTERING	
Clamping Voltage	800V (H-N)

# CPS1220RM

## RACKMOUNT SURGE PROTECTOR



### SPECIFICATIONS CONT.

PHYSICAL	
Color	Black
Form Factor Supported	1U Rackmount 0U Rackmount Undercounter Installation
Material of Construction	Metal
Rack Height	1U
PHYSICAL DIMENSIONS	
Physical Dimensions - Width/Height/Depth (cm)	43.82 x 4.45 x 12.07 cm
Physical Dimensions - Width/Height/Depth (mm)	438 x 44 x 121 mm
Physical Dimensions - Width/Height/Depth (in.)	17.25 x 1.75 x 4.75 in.
Weight (kg)	2.63 kg
Weight (lbs.)	5.80 lbs.
Country of Origin	China
SHIPPING DIMENSIONS	
Shipping Dimensions - Width/Height/Depth (cm)	20.32 x 5.72 x 55.25 cm
Shipping Dimensions - Width/Height/Depth (mm)	203.2 x 57.15 x 552.45 mm
Shipping Dimensions - Width/Height/Depth (in.)	8.0 x 2.25 x 21.75 in.
Shipping Weight (kg)	2.81 kg
Shipping Weight (lbs.)	6.20 lbs.

ENVIRONMENTAL	
Operating Elevation	0 to 10,000 ft / 3,048 m
Operating Relative Humidity	0% to 95% non-condensing
Operating Temperature	32°F to 104°F / 0°C to 40°C
Storage Elevation	0 to 50,000 ft / 15,239 m
Storage Temperature	5°F to 113°F / -15°C to 45°C
CERTIFICATIONS	
Environmental	RoHS Compliant
Safety	UL Recognized UL 498A UL1449 4th Edition cUL
WARRANTY	
Product Warranty	3-Year Limited