



CSHT706TC | HOME THEATER SURGE PROTECTION

Protect home and office computers, electronics, and home theater equipment

The CyberPower Home Theater Surge Protector CSHT706TC provides 1,950 joules of surge protection and 7 outlets to safeguard your home theater equipment from damage caused by electrical surges. Data line protection occurs with RJ11 ports for telecommunication devices such as phones, faxes, modems, and DSL lines. Gold-plated RG6 coaxial connectors protect cable/satellite TV receivers and broadband modems.

Features of the CSHT706TC include automatic shutdown, 7 outlets (1 widely-spaced for transformer plugs), a power cord (6 ft.), a right-angle plug with 45° offset, LED status indicators, impact-resistant casing, metal oxide varistor (MOV) technology, and an EMI/RFI noise filter. This surge suppressor comes with a Limited Lifetime Warranty and a Connected Equipment Guarantee.

TYPICAL APPLICATIONS

- Home Theater Equipment
- Cable DSL/Modems
- Personal Computers
- Phone/Fax/Modem
- Cable and Satellite
- Consumer Electronics

FEATURES

- Surge suppression: 1,950 J
- Volts: 125 V
- Circuit breaker: 15 A
- Plug type: NEMA 5-15P (45° offset)
- Outlet type: 7 x NEMA 5-15R (surge-protected)
- Transformer outlets: 1
- Power cord: 6 ft
- Data line protection: Telephone, Coaxial
- Cable/Satellite protection: Yes
- EMI/RFI Noise Filter: Yes
- Warranty: Limited Lifetime
- Connected Equipment Guarantee: \$150,000



SPECIFICATIONS

INPUT	
Circuit Breaker	15 A
Cord Length	6 ft (1.8 m)
Input Plug Type	NEMA 5-15P
Maximum Input Current	15 A
Plug Style	Right Angle - 45° Offset

OUTPUT	
Outlet Type	7 NEMA 5-15R
Outlets - Total	7
Outlets - Widely-Spaced	1
USB Charge Port	No

CSHT706TC

HOME THEATER SURGE PROTECTION

SPECIFICATIONS CONT.

SURGE PROTECTION & FILTERING

Attenuation	43 dB
Clamping Voltage	400V (H-N, H-G, N-G)
Coax Protection RG6	1 In 1 Out
EMI/RFI Filtration	150 KHz - 100 MHz
Maximum Surge Current	90,000 A
Maximum Surge Current H-G	30,000 A
Maximum Surge Current H-N	30,000 A
Maximum Surge Current N-G	30,000 A
Maximum Surge Voltage	6,000 V
Phone Protection RJ11	1-In / 2-Out
Response Time	<1 Nanosecond
Surge Suppression (Joules)	1,950 J

PHYSICAL

Color	Black
Cord Management	Yes
Material of Construction	Plastic
Safety Covers	Yes

DIMENSIONS

Physical Dimensions - WxHxD (cm)	7.9 x 3.99 x 30.96 cm
Physical Dimensions - WxHxD (mm)	79 x 40 x 310 mm
Physical Dimensions - WxHxD (in.)	3.11 x 1.57 x 12.19 in.
Weight (kg)	0.50 kg
Weight (lb)	1.10 lbs.

SHIPPING DIMENSIONS

Shipping Dimensions - WxHxD (cm)	5.64 x 37.47 x 11.43 cm
Shipping Dimensions - WxHxD (mm)	56.39 x 374.65 x 114.3 mm
Shipping Dimensions - WxHxD (in)	2.22 x 14.75 x 4.5 in.
Shipping Weight (kg)	0.68 kg
Shipping Weight (lbs.)	1.50 lbs.

CERTIFICATIONS

Environmental	RoHS Compliant
Safety	UL1363

WARRANTY

CEG Amount	\$150,000
Connected Equipment Guarantee	Lifetime
Product Warranty	Limited Lifetime