

Eaton 24V DC DIN Rail Extended Battery Module (EBM) for Select DC Industrial UPS Systems

MODEL NUMBER: BPDIN24XL











Provides extended runtime for compatible UPS systems in industrial, process, automation and machine control enclosure applications.

Features

Backup Battery Module Gives Your Compatible UPS System Extended Runtime

The BPDIN24XL offers extended battery runtime when used in conjunction with Eaton's DIN24240DC and DIN24480DC UPS systems. It can also be daisy-chained for a maximum of four matching EBMs to deliver even longer extended-run operation.

Supports Easy DIN Rail Installation

This extended battery module supports mounting in industrial, process, automation and machine control enclosure applications using the integrated 35 mm DIN rail mounting clamp.

Specifications

OVERVIEW		
UPC Code	037332275301	
INPUT		
Input Phase	Single-Phase	
BATTERY		
Battery Type	Valve Regulated Lead Acid (VRLA)	
DC System Voltage (VDC)	24	
PHYSICAL		
Primary Form Factor	DIN-Rail	
Material of Construction	Steel	

Highlights

- Compatible with expandable DIN24240DC and DIN24480DC UPS systems
- Daisy-chain connector allows addition of up to 4 total EBMs to extend backup runtime
- Built-in clamp mounts easily to a "top hat" 35mm DIN rail with no mounting screws or brackets required

System Requirements

Eaton DIN24240DC or DIN24480DC UPS system

Package Includes

- BPDIN24XL 24V DC DIN Rail Extended Battery Module
- · Safety card
- Owner's manual



Rack Height	OU	
External Battery Pack Form Factor	DIN Rail 35mm	
Shipping Dimensions (hwd / in.)	7.59 x 9.17 x 7.32	
Shipping Weight (kg)	4.50	
Unit Dimensions (hwd / in.)	4.880 x 8.310 x 4.550	
Unit Dimensions (hwd / cm)	12.395 x 21.107 x 11.557	
Unit Weight (lbs.)	9.48	
Unit Weight (kg)	4.30	
ENVIRONMENTAL		
Operating Temperature Range	+5°F to +122°F / -15°C to +50°C	
Storage Temperature Range	+5°F to +104°F / -15°C to +40°C	
Relative Humidity	0-95%, non-condensing	
STANDARDS & COMPLIANCE		
Product Certifications	UL Listed; cUL Listed	
Product Compliance	CE (Europe); REACH; RoHS; UKCA	
WARRANTY & SUPPORT		
Product Warranty Period (Worldwide)	3-year limited warranty	

1000 Eaton Boulevard Cleveland, OH 44122 United States https://tripplite.eaton.com © 2025 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.