



Powering Business Worldwide

## Waber-by-Tripp Lite Surge Suppressor with heavy-duty metal housing

MODEL NUMBER: **DG115-SR**



### Highlights

- 6 outlets/6 ft. cord
- 600 joule rating
- Audible surge indication
- Remote switch included

### Package Includes

- DG115-SR Power Strip
- Warranty information
- Instruction manual

### Description

The Waber-by-Tripp Lite DG115-SR Power Strip offers a convenient method of power distribution and surge suppression in workbench, wallmount or floor mount applications. Unique design includes remote power switch at the end of a 6 foot cord allows remote power control of connected equipment. Includes 6 NEMA 5-15R output receptacles, 6 foot AC line cord and keyhole mounting tabs for installation in a wide variety of applications. Protects connected equipment from transient surges and line noise with built in surge suppression rated at 600 joules. Corded, multi-outlet strip reduces cabling clutter and enables the connection of multiple electrical devices to a single AC wall socket. Features metal housing, lighted power switch with integrated 15 amp resettable circuit breaker and attractive gray color scheme. Lifetime warranty.

PLUG/OUTLETS - Input: NEMA 5-15P/Output: 6 NEMA 5-15R

ELECTRICAL - 120VAC, 50/60Hz, 15A (Requires standard NEMA 5-15R wall receptacle)

FORMAT - Corded power distribution strip with remote power switch on a 6 ft. cord

SUPPRESSION - 600 joules AC suppression

### Features

- Multi-outlet power strip offers convenient power distribution in workbench, wallmount or floor mount applications
- Mountable remote power switch at the end of a 6 foot cord allows remote power control of connected equipment.
- Includes 6 NEMA 5-15R output receptacles
- Lighted combination power switch with integrated circuit breaker
- Keyhole mounting tabs support permanent installation on a wide variety of surfaces
- UL1449 (USA/400V rating), UL1363 (USA), cUL (Canada)
- 15 amp power handling capacity
- 6 foot AC line cord
- Lifetime warranty

## Specifications

### OVERVIEW



Powering Business Worldwide

|                                              |                                                                                                                       |
|----------------------------------------------|-----------------------------------------------------------------------------------------------------------------------|
| UPC Code                                     | 037332115621                                                                                                          |
| <b>INPUT</b>                                 |                                                                                                                       |
| Recommended Electrical Service               | 120V (110-125V)                                                                                                       |
| Input Cord Gauge Type                        | 14 gauge; SJT                                                                                                         |
| Voltage Compatibility (VAC)                  | 120                                                                                                                   |
| Input Plug Type                              | NEMA 5-15P                                                                                                            |
| Input Cord Length (ft.)                      | 6                                                                                                                     |
| Right-Angle Plug                             | No                                                                                                                    |
| Input Cord Length (m)                        | 1.83                                                                                                                  |
| Integrated Cord Clip                         | No                                                                                                                    |
| <b>OUTPUT</b>                                |                                                                                                                       |
| Frequency Compatibility                      | 50 / 60 Hz                                                                                                            |
| Output (Watts)                               | 1800                                                                                                                  |
| Circuit Breaker (amps)                       | 15                                                                                                                    |
| <b>USER INTERFACE, ALERTS &amp; CONTROLS</b> |                                                                                                                       |
| Diagnostic LED(s)                            | Yes                                                                                                                   |
| Switches                                     | Lighted two position mountable remote power switch at the end of a dedicated 6 ft. cord controls power to all outlets |
| Diagnostic LED Details                       | Protection present (green)                                                                                            |
| <b>SURGE / NOISE SUPPRESSION</b>             |                                                                                                                       |
| AC Suppression Joule Rating                  | 600                                                                                                                   |
| AC Suppression Response Time                 | < 1 ns                                                                                                                |
| Protection Modes                             | Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression                                    |
| UL1449 Let Through Rating                    | 400V - UL Verified                                                                                                    |
| EMI / RFI Filtering                          | Up to 20 dB                                                                                                           |
| Immunity                                     | Conforms to IEE 587 / ANSI C62.41                                                                                     |
| Automatic Shut-Off                           | No                                                                                                                    |
| <b>DATALINE SURGE SUPPRESSION</b>            |                                                                                                                       |
| Cable (Coax) Protection                      | No                                                                                                                    |
| Network (Ethernet) Protection                | No                                                                                                                    |
| Telephone/DSL Protection                     | No                                                                                                                    |
| <b>PHYSICAL</b>                              |                                                                                                                       |
| Color                                        | Light Gray                                                                                                            |



Powering Business Worldwide

|                                      |                           |
|--------------------------------------|---------------------------|
| Material of Construction             | Metal                     |
| Power Cord Color                     | Light Gray                |
| Housing Color                        | Light Gray                |
| Mounting Holes or Slots              | Yes                       |
| Receptacle Color                     | Light gray                |
| Shipping Dimensions (hwd / in.)      | 2.16 x 15.00 x 6.00       |
| Shipping Dimensions (hwd / cm)       | 5.50 x 38.10 x 15.24      |
| Shipping Weight (lbs.)               | 2.12                      |
| Shipping Weight (kg)                 | 0.96                      |
| Unit Dimensions (hwd / in.)          | 1.500 x 12.594 x 2.500    |
| Unit Dimensions (hwd / cm)           | 31.75 x 6.35 x 3.8        |
| <b>FEATURES &amp; SPECIFICATIONS</b> |                           |
| Rotatable Outlets                    | No                        |
| Antimicrobial                        | No                        |
| <b>WARRANTY &amp; SUPPORT</b>        |                           |
| Product Warranty Period (Worldwide)  | Lifetime limited warranty |

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2025 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.