



Powering Business Worldwide

Eaton 9PX Maintenance Bypass for Select 8kVA to 11kVA 9PX UPS Systems, Hardwired Input/Output, 3 L6-30R Outlets, 3U Rack/Tower

MODEL NUMBER: **MBP11K208**



Reroutes utility power to keep essential equipment operational while you're servicing or replacing a UPS system.

Features

Compatible with Select Eaton 8kVA to 11kVA 9PX UPS Systems

The MBP11K208 works with Eaton's 9PX8K, 9PX8KHW, 9PX8KTF5, 9PX11K, 9PX11KHW, 9PX11KTF11 and 9PX11KTF5 UPS systems. The bypass switch lets you service or replace the UPS system without powering down any equipment and risking costly downtime. Power passes directly from the PDU to equipment.

Versatile Connection and Installation Options

The MBP11K208 features hardwired input and output connections. Three NEMA L6-30R outlets also allow load connection. You can mount the maintenance bypass switch in 3U of space in an EIA-standard 19-inch rack using the included 4-post rail kit. You can also adapt it for tower or wall installation using the included hardware.

Specifications

OVERVIEW	
UPC Code	743172043610
Accessory Type	Bypass Panel (Rack-Mount)
Accessory Class	UPS Accessories
INPUT	
UPS Input Connection Type	Hardwire
OUTPUT	
Individually Controllable Load Banks	No

Highlights

- Isolates UPS from connected loads for maintenance without powering down equipment
- Designed for 3U rack, tower or wall mounting using the included installation hardware
- Compatible with Eaton's 8kVA to 11kVA 9PX UPS systems

System Requirements

Compatible with Eaton's 9PX8K, 9PX8KHW, 9PX8KTF5, 9PX11K, 9PX11KHW, 9PX11KTF11 and 9PX11KTF5 UPS systems

Package Includes

- MBP11K208 Maintenance Bypass
- (2) Input/output covers
- Input/output cover fixation kit
- (2) Conduits for UPS input/output connection
- (4) Conduit fittings
- Mounting hardware
- Installation and user manual



Powering Business Worldwide

BATTERY	
Expandable Runtime	No
PHYSICAL	
Unit Dimensions (hwd / in.)	5.100 x 13.200 x 8.700
ENVIRONMENTAL	
Operating Temperature Range	32° to 104°F (0° to 40°C)
Relative Humidity	0-95% non-condensing
STANDARDS & COMPLIANCE	
Product Certifications	ICC-ES AC156 OSHPD Seismic Certified
Product Compliance	RoHS
WARRANTY & SUPPORT	
Product Warranty Period (U.S. & Canada)	3-year limited warranty

1000 Eaton Boulevard
Cleveland, OH 44122
United States
<https://tripplite.eaton.com>

© 2025 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.