



# 12-Outlet (10-15A & 2-20A) Vertical Power Strip, 120V, 20A, 15 ft. (4.57 m)Cord, 5-20P, 36 in.

MODEL NUMBER: PS361220









Add extra power outlets in rack-mount, workbench, office, retail displays and telecom applications, or any area that needs to power many electrical devices in close proximity to one another from a single AC wall outlet.

#### **Description**

Need to power many pieces of equipment in close proximity to one another, but don't have enough outlets to power them all? This PS361220 12-outlet vertical power strip will give you the outlets where you need them, when you need them. The PS361220 contains a 15-foot (4.6-meter) (14/3 SJT) cord, 10 standard NEMA 5-15R outlets and two commercial-use NEMA 5-20R outlets. Each outlet is spaced 2.64 inches apart (center-to-center), wide enough for many types of transformers or AC adapters without blocking adjacent outlets. Encased in a rugged all-metal housing, it comes with mounting clips for either vertical and horizontal mounting, making the PS361220 ideal for a variety of uses in rack-mount, workbench, industrial, office and telecom environments. An illuminated rocker-style power switch with a transparent guard prevents accidental turn-offs, while a 20-amp circuit breaker guards against dangerous circuit overloads. To match the decor of most professional settings, it has an extruded aluminum housing with black receptacles.

#### **Features**

#### Multi-Outlet 120V Power Distribution for Rack-Mount, Raceway and Workbench Applications

- 1800W, 120V, 20A, corded, multi-outlet power strip that safely connects multiple electrical devices to a single AC wall socket
- Saves the time and cost of installing new power outlets in un-powered areas
- Ideal for branch circuit power distribution to telecommunications, computers or internetworking
  equipment in rack enclosures, workbenches, table tops, work stations, offices, factories, repair shops,
  hobby shops, test stands and engineering labs

# 12 Convenient Outlets Power All Standard Electrical Equipment

- Features 12 outlets (10 NEMA 5-15R and 2 NEMA 5-20R) that are compatible with all standard electrical and electronic equipment
- Each outlet is 2.64 inches apart (center to center) wide enough to fit transformers or AC adapters without blocking adjacent outlets, so you can fully utilize the power strip all the time
- An extra-long, 15-ft. (4.57 m), 14 AWG, 3-wire, SJT cord can reach wall outlets mounted in a different area or room from where it draws AC power, putting you in control of getting reliable power where you need it most

# **Highlights**

- 12-outlet (ten 5-15R and two 5-20R) power strip with a 15-ft. (4.57 m) Cord and an industrialgrade 5-20P plug
- Rated at 1800W, 120V, featuring a 20A resettable circuit breaker to prevent circuit overloads
- Easy-to-install, vertical or horizontal mounting with included mounting clips
- Rocker-style, illuminated power switch with safety cover to prevent accidental turn offs
- RoHS-compliant and certified to meet UL 1363 standards

# **Package Includes**

- PS361220
- Mounting hardware
- Instruction manual





#### Easy-to-Install, Vertical and Horizontal Mounting Options

- Offers a convenient method of optional horizontal or vertical power distribution. Mounting clips are included.
- Its 36-in. length and strip-style, bench/cabinet, form factor fits in the most confined spaces unobtrusively
- Weighing less than 4 lbs (1.8 kgs), the PS361220 is both easy to handle and effortless to install

# **Built-In, Automatic Safety Features**

- An illuminated, rocker-style, power switch with a transparent guard prevents accidental turn offs, while still allowing you to see whether the PS361220 is operational at a glance
- An integral, 20-amp resettable circuit breaker prevents dangerous circuit overloads that can irreversibly damage connected equipment
- The breaker automatically disconnects AC input power to the PS361220 when it detects that the
  equipment load is drawing too much current

### Rugged, Durable Housing

- A rugged, all-metal housing is durably constructed to stand up to demanding network, laboratory or factory environments
- An attractive, extruded aluminum housing with stylish black receptacles matches the decor of most professional settings

# **Specifications**

| OVERVIEW                           |                       |
|------------------------------------|-----------------------|
| UPC Code                           | 037332186638          |
| INPUT                              |                       |
| Nominal Input Voltage(s) Supported | 120V AC               |
| Recommended Electrical Service     | 20A 120V              |
| Input Cord Gauge Type              | 12 gauge; SJT         |
| Voltage Compatibility (VAC)        | 120                   |
| Input Plug Type                    | NEMA 5-20P            |
| Input Cord Length (ft.)            | 15                    |
| Right-Angle Plug                   | No                    |
| Input Cord Length (m)              | 4.57                  |
| Integrated Cord Clip               | No                    |
| OUTPUT                             |                       |
| Frequency Compatibility            | 60 Hz                 |
| Output (Watts)                     | 1800                  |
| Output Receptacles                 | (10) 5-15R; (2) 5-20R |
| Circuit Breaker (amps)             | 20                    |
| Transformer Accommodation          | (6) Yes               |





| Right-Angle Outlets                    | No  |  |
|--|---|--|
| Outlet Spacing                         | 2.64 in.  |  |
|  |   |  |
| USER INTERFACE, ALERTS & CON           |   |  |
| Switches                               | Lighted 2 position switch controls power to all outlets   |  |
| Locking Switch Cover                   | Transparent on/off switch cover prevents accidental turn-off  |  |
| PHYSICAL                               |   |  |
| Color                                  | Silver  |  |
| Material of Construction               | Aluminum  |  |
| Power Cord Color                       | Black   |  |
| Form Factors Supported                 | Supports vertical or horizontal mounting in rack enclosures, raceways and a variety of other applications |  |
| Housing Color                          | Silver  |  |
| Mounting Holes or Slots                | No  |  |
| Outlets Measurement (Center to Center) | 2.64 in.  |  |
| Receptacle Color                       | Black   |  |
| Shipping Dimensions (hwd / in.)        | 2.40 x 4.40 x 40.00   |  |
| Shipping Dimensions (hwd / cm)         | 6.10 x 11.18 x 101.60   |  |
| Shipping Weight (lbs.)                 | 4.50  |  |
| Shipping Weight (kg)                   | 2.04  |  |
| Unit Dimensions (hwd / in.)            | 1.250 x 1.500 x 36.000  |  |
| Unit Dimensions (hwd / cm)             | 3.18 x 3.81 x 91.4  |  |
| Unit Weight (lbs.)                     | 3.79  |  |
| Unit Weight (kg)                       | 1.72  |  |
| Outlet Spacing                         | 2.64 in.  |  |
| Mounting Details                       | Includes mounting clips   |  |
| FEATURES & SPECIFICATIONS              |   |  |
| Antimicrobial                          | No  |  |
| Built-In Circuit Breaker               | Yes   |  |
| STANDARDS & COMPLIANCE                 |   |  |
| Product Certifications                 | cUL Listed; UL 1363; UL Listed  |  |
| Product Compliance                     | RoHS  |  |
| WARRANTY & SUPPORT                     |   |  |
| Product Warranty Period (Worldwide)    | Lifetime limited warranty   |  |





1000 Eaton Boulevard Cleveland, OH 44122 United States https://tripplite.eaton.com © 2025 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.