



Safe-IT UL 1363 Medical-Grade Power Strip, 6 Hospital-Grade Outlets, USB Charging, Safety Covers, Antimicrobial, 2 ft. Cord

MODEL NUMBER: PS-602-HGUSB











Highlights

- Medical-grade power strip approved for use outside patient care vicinities
- 6 NEMA 5-15R-HG outlets come with optional locking covers for protection
- Dual USB ports provide charging power to 2 mobile devices at the same time
- Antimicrobial protection helps resist the growth of bacteria, viruses, fungi, mold and mildew

Package Includes

- PS-602-HGUSB UL 1363
 Medical-Grade Power Strip, 6
 Outlets, 2 ft. Cord
- (6) Outlet safety covers
- · Owner's manual

Delivers power to medical equipment in areas outside patient care vicinities, including nursing stations, labs, offices and pharmacies.

Features

Medical-Grade Power Strip Approved for Hospitals, Clinics and Other Medical Facilities

The PS-602-HGUSB features six NEMA 5-15R-HG hospital-grade outlets that supply power to equipment used in areas outside patient care vicinities, including nursing stations, pharmacies, office and administration areas, and labs. This power strip has a NEMA 5-15P-HG "green dot" plug and meets UL 1363 standards.

Dual USB Ports Provide Charging Power

One USB-A port and one USB-C Power Delivery (PD) port let you charge smartphones, tablets and other vital mobile devices. The USB-C PD port provides up to 30W.

Antimicrobial Protection Helps Provide a Safer, Cleaner and Healthier Work Environment

The Safe-IT™ power strip is protected by an antimicrobial coating that helps resist the growth of bacteria, viruses, fungi, mold and mildew.

Premium Safety Features Help Ensure Proper Power Connections

With no central power switch, this power strip presents no danger of accidental shutoff and cutting off power to essential devices. Locking plastic safety covers are included to block access to unused outlets.

Ready for Installation in Demanding Medical Environments

The two-foot cord connects the power strip to a standard NEMA 5-15R wall outlet. Built-in mounting flanges let you mount the all-metal housing to a stable, flat surface. Scan the Easy Asset QR code on the side of the power strip to access product resources and other critical information.

Specifications

OVERVIEW	
UPC Code	037332287748





INPUT		
Nominal Input Voltage(s) Supported	120V AC	
Recommended Electrical Service	15A 120V	
Input Connection Type	NEMA 5-15P-HG	
Input Plug Features	Hospital Grade Plug	
Input Cord Gauge Type	14 gauge; SJT	
Voltage Compatibility (VAC)	120	
Input Plug Type	NEMA 5-15P-HG	
Input Cord Length (ft.)	1.5	
Right-Angle Plug	No	
Input Cord Length (m)	0.46	
Integrated Cord Clip	No	
ОИТРИТ		
Frequency Compatibility	50 / 60 Hz	
Output Receptacles	(6) 5-15R-HG	
Circuit Breaker (amps)	15	
Overload Protection	15 amp circuit breaker	
Transformer Accommodation	(2) Yes	
Outlet Orientation	Single row of 6	
Right-Angle Outlets	No	
USER INTERFACE, ALERTS & CON	TROLS	
Diagnostic LED(s)	No	
Switches	No power switch	
CHARGING		
Number of Charging Ports	2	
Total Charging Watts	30	
Charging Method	USB	
Charging Port Type	USB A (FEMALE); USB C (FEMALE)	
Charging Ports Details	USB C Power Delivery	
Charging Ports / Amps	(1) 2A; (1) 3A / 2A / 1.5A	
PHYSICAL		
Color	White	
Material of Construction	Metal	





Power Cord Color	White	
Housing Color	White	
Mounting Holes or Slots	Yes	
Slot or Hole Mount Measurement (Center to Center)	Distance between keyhole slots = 261.92mm; Distance between end tabs = 330.17mm	
Outlets Measurement (Center to Center)	1.52 in.	
Receptacle Color	White	
Shipping Dimensions (hwd / in.)	14.30 x 5.80 x 2.00	
Shipping Dimensions (hwd / cm)	36.32 x 14.73 x 5.08	
Shipping Weight (lbs.)	2.20	
Shipping Weight (kg)	1.00	
Unit Dimensions (hwd / in.)	13.630 x 2.500 x 1.650	
Unit Weight (lbs.)	2	
Unit Weight (kg)	0.91	
Mounting Details	Includes flanges	
FEATURES & SPECIFICATIONS		
Rotatable Outlets	No	
Antimicrobial	Yes	
Built-In Circuit Breaker	Yes	
Antibacterial	No	
Built-in Cable Management	No	
STANDARDS & COMPLIANCE		
Product Certifications	cUL Listed; UL 1363; UL Listed	
Product Compliance	RoHS; FCC Part 15 Class B (USA)	
WARRANTY & SUPPORT		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

1000 Eaton Boulevard Cleveland, OH 44122 United States https://tripplite.eaton.com © 2025 Eaton. All Rights Reserved.

Eaton is a registered trademark. All other trademarks are the property of their respective owners.