

Power Strip - Agency-Approved Hospital/Medical Outlet Strip

MODEL NUMBER: PS-615-HGULTRA



Highlights

- Versatile power distribution strip
- 6 hospital-grade receptacles and hospital-grade plug
- 15-ft. cord
- 15A resettable circuit breaker
- Double-fault safety protection

Package Includes

- PS-615-HGULTRA Power Strip
- User manual with warranty information

Description

Providing 15A capacity AC power distribution in a rugged all-metal outlet strip for 120V applications, Tripp Lite's PS-615-HGULTRA Power Strip is agency approved for use in physicians' offices, imaging centers, laboratories and medical facilities. Features include 6 hospital-grade receptacles with GFCI protection, 15-foot AC power cord and built-in resettable circuit breaker. Switchless design prevents accidental shutoff. Optional-use keyhole mounting tabs and flanges.

PLUG/OUTLETS: Incorporates NEMA 5-15P-HG hospital-grade plug and 6 NEMA 5-15R-HG hospital-grade receptacles

ELECTRICAL: 120V AC, 50/60Hz, 15A

FORMAT: All-metal corded multi-outlet strip

Features

- Rugged all-metal housing withstands years of use without breakage
- 6 x NEMA 5-15R-HG hospital-grade output receptacles (2 with GFCI protection)
- 15-ft. AC cord with integrated, molded NEMA5-15P-HG hospital-grade plug
- Optional-use keyhole mounting tabs and flanges.
- Switchless design prevents accidental shutoff
- 15A electrical capacity with built-in resettable circuit breaker
- 120V, 50/60Hz electrical compatibility
- Tested to UL (USA) and cUL (Canada)
- Agency approved for use in medical facilities

Specifications

| OVERVIEW | |
|----------|--------------|
| UPC Code | 037332123268 |
| INPUT | |



Powering Business Worldwide

TRIPP-LITE
by **EAT•N**

| | |
|--|------------------------|
| Recommended Electrical Service | 15A 120V |
| Voltage Compatibility (VAC) | 120 |
| Input Plug Type | NEMA 5-15P-HG |
| Input Cord Length (ft.) | 15 |
| Input Cord Length (m) | 4.57 |
| Integrated Cord Clip | No |
| OUTPUT | |
| Frequency Compatibility | 50 / 60 Hz |
| Output (Watts) | 1800 |
| Circuit Breaker (amps) | 15 |
| Overload Protection | 15A circuit breaker |
| Transformer Accommodation | (3) Yes |
| Outlet Orientation | Single row of 6 |
| Right-Angle Outlets | No |
| USER INTERFACE, ALERTS & CONTROLS | |
| Switches | No power switch |
| PHYSICAL | |
| Color | White |
| Material of Construction | Metal |
| Power Cord Color | White |
| Housing Color | White |
| Mounting Holes or Slots | Yes |
| Receptacle Color | White |
| Shipping Dimensions (hwd / in.) | 2.25 x 15.00 x 6.00 |
| Shipping Dimensions (hwd / cm) | 5.72 x 38.10 x 15.24 |
| Shipping Weight (lbs.) | 3.55 |
| Shipping Weight (kg) | 1.61 |
| Unit Dimensions (hwd / in.) | 1.500 x 13.750 x 2.500 |
| Unit Dimensions (hwd / cm) | 3.8 x 34.9 x 6.4 |
| Unit Weight (lbs.) | 2.4 |
| Unit Weight (kg) | 1.09 |
| Mounting Details | Includes flanges |
| FEATURES & SPECIFICATIONS | |

| | |
|-------------------------------------|---------------------------|
| Antimicrobial | No |
| Built-In Circuit Breaker | Yes |
| WARRANTY & SUPPORT | |
| Product Warranty Period (Worldwide) | Lifetime limited warranty |

1000 Eaton Boulevard
Cleveland, OH 44122
United States
<https://tripplite.eaton.com>

© 2025 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.