


# Programmable Relay I/O Card for Tripp Lite SVTX, SVX, S3MX and SV UPS Systems

MODEL NUMBER: RELAYCARDSV



Provides contact closures for remote monitoring of Tripp Lite SVTX, SVX, S3MX and SV Series UPS systems. Recommended for IBM server, PC and workstation equipment, auto-controlled industrial equipment and communication applications.

## Description

The RELAYCARDSV Programmable Relay I/O Card is a contact-closure management accessory card compatible only with Tripp Lite SVTX, SVX, S3MX and SV Series 3-phase UPS systems. It is ideal for providing contact closure output communications for IBM server, PC and workstation equipment and auto-controlled industrial equipment and communications applications. It lets you communicate UPS system status and events via six contact closure outputs. Each output relay can be configured as either Normally Close or Normally Open. You can also configure the input signal to perform remote UPS system shutdowns or battery tests. Relay contacts report UPS alarm, utility failure, UPS on-line mode, low battery, bypass mode and UPS failure. The RELAYCARDSV is simple to install in Tripp Lite SmartOnline® SVTX 400V non-modular, SVX 400V modular, S3MX 400V non-modular or SV 208V modular UPS system. A six-foot DB9 cable is included for connecting the UPS system to equipment for remote monitoring and control.

## Features

**Provides Contact Closures for Remote UPS System Monitoring** Recommended for IBM server, PC and workstation equipment and auto-controlled industrial equipment and communications applications  
 6 output relays configurable to Normally Close or Normally Open  
 Input signal performs remote UPS shutdown or battery test  
 Relay contacts report UPS alarm, utility failure, UPS on-line mode, low battery, bypass mode and UPS failure  
 Compatible with Tripp Lite SmartOnline SVTX 400V non-modular, SVX 400V modular, S3MX 400V non-modular and SV 208V modular UPS systems  
 6 ft. DB9 cable included

## Highlights

- Allows UPS to provide contact closure output communications
- 6 output relays configurable to Normally Close or Normally Open
- Input signal performs remote UPS shutdown or battery test
- For Tripp Lite SVTX, SVX, S3MX and SV 3-phase UPS systems only

## System Requirements

- Tripp Lite SmartOnline SVTX 400V non-modular, SVX 400V modular, S3MX 400V non-modular or SV 208V modular UPS system

## Package Includes

- RELAYCARDSV Programmable Relay I/O Card
- DB9 communication cable, 6 ft.
- Owner's manual

## Specifications

OVERVIEW	
UPC Code	037332199775
Accessory Type	Relay I/O Card
OUTPUT	



Powering Business Worldwide



Output Connector Type	DB9 port
<b>PHYSICAL</b>	
Shipping Dimensions (hwd / in.)	1.89 x 6.54 x 4.89
Shipping Dimensions (hwd / cm)	4.80 x 16.61 x 12.42
Shipping Weight (lbs.)	0.44
Shipping Weight (kg)	0.20
Unit Dimensions (hwd / in.)	1.300 x 2.640 x 5.080
Unit Dimensions (hwd / cm)	3.3 x 6.71 x 12.9
Unit Weight (lbs.)	0.18
Unit Weight (kg)	0.08
<b>COMMUNICATIONS</b>	
Communications Interface	Contact closure
<b>WARRANTY &amp; SUPPORT</b>	
Product Warranty Period (Worldwide)	2-year limited warranty

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2025 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.