

Rackmount PDU with 8 Outlets and Surge Protection - 1U

Product ID: RKPW081915



This 8-outlet (120V 15A)(12A UL) Rack PDU delivers a cost-effective power distribution solution for your server rack/cabinet. The 1U PDU can be mounted horizontally in any server rack 4in in depth or greater, to provide eight 120V 15A power ports/outlets, and features a rugged steel casing to ensure maximum durability.

The front of the PDU features two LEDs to indicate proper ground and surge detection while enabling you to control the power state with an illuminated power/reset switch.

To prevent costly breakdowns of connected devices, the rackmount PDU features a built-in circuit breaker and reset switch, ensuring dependable performance of vital equipment.

Certifications, Reports and Compatibility









Applications

- 8 easily accessible power outlets in a compact 1U of rack space
- Localize the power control for all of your connected system

Features

• POWER AND CHARGE: This rack mount power strip provides an additional 8 NEMA 5-15 outlets (120V/15A) and features a 6ft (1,8m) long cord so you can plug your devices in while leaving the rack mobile



- 1U RACK DESIGN: Compatible with all 19" server racks 4 inches or deeper, this horizontal-mount power distribution unit fits many network racks and has an integrated power cord; ANSI/EIA RS-310-D standard
- EASY INSTALLATION: This IT-grade rackmount PDU features a rugged steel chassis, LED indicators for ground and surge protection, and lets you control the power state with power and reset switches
- PROTECTS YOUR EQUIPMENT: This rack mountable 8-outlet (120V) power strip features a built-in circuit breaker and reset switch, ensuring a dependable performance of your networking equipment
- THE IT PRO'S CHOICE: Designed and built for IT Professionals, this rack PDU is backed for 2-Years, including free lifetime 24/5 multi-lingual technical assistance

Hardware		
	Warranty	2 Years
	Form Factor	Horizontal
	Number of Power Outlets	8
	Rack-Mountable	Yes
Performance		
	General Specifications	Surge Protection: 1800 Joules
	Maximum Total Current	15A
	Maximum Total Current Draw per Phase	15A
	Regulatory Derated Input Current (North America)	12A
	Nominal Input Voltage	120V
	Nominal Output Voltage	120V
	Maximum Output Voltage	125V
	Load Capacity	1800 VA
Connector(s)		
	Input Connector(s)	1 - NEMA 5-15 Power (North America)
	Output Connectors	8 - NEMA 5-15 Power (North America)
Indicators		
	LED Indicators	1 - Ground
		1 - Surge





Power Input Voltage 120 AC **Environmental Operating Temperature** -5C to 45C (23F to 113F) Storage Temperature -25C to 65C (-13F to 149F) Humidity 5% to 95% RH non-condencing **Physical** Characteristics Color Black Material Steel Cable Length 6.0 ft [1.8 m] **Product Length** 19.0 in [48.3 cm] **Product Width** 3.8 in [9.6 cm] **Product Height** 1.7 in [4.3 cm] Weight of Product 4.2 lb [1.9 kg] **Packaging** Information Package Quantity 1 Package Length 9.2 in [23.3 cm] Package Width 20.5 in [52.1 cm] Package Height 2.4 in [6.2 cm] Shipping (Package) 4.9 lb [2.2 kg] Weight What's in the Box 1 - 8 Port Power Distribution Unit Included in Package 4 - M5 Screws 4 - M5 Cage Nuts

1 - Installation Document



*Product appearance and specifications are subject to change without notice.