



Protect It! 6-Outlet Surge Protector - 5-15R Outlets, 2 USB Ports, 5-15P Direct Plug-In, 490 Joules, Black

MODEL NUMBER: SK62USBC











Protects your computer and other home/office electronics against dangerous power surges, spikes and line noise.

Features

6-Outlet Surge Protector with USB Charging Safeguards Your Sensitive Electronics

Ideal for your home, office, retail or industrial workstation, this Protect It!® surge protector features a surge protection rating of 490 joules to defend your valuable electronic components against power surges and spikes. The unit plugs directly into a wall outlet, avoiding annoying cord clutter.

NEMA 5-15R Outlets Accept a Wide Range of Electronic Devices

Plug your computer, printer, wireless router, desk lamp and other home/office electronics into six NEMA 5-15R outlets to protect them against dangerous surges, spikes and line noise.

Premium Protection from EMI/RFI Line Noise Helps Your Equipment Perform Better

This surge protector filters out disruptive EMI (electromagnetic interference) and RFI (radio frequency interference) line noise that can disturb your electronics and inflict hardware damage or data loss. This EMI/RFI filtering also helps your connected components perform better and last longer.

USB Charger Keeps Mobile Devices Ready for Use

One USB-C port and one USB-A port are available for charging your smartphone, tablet or other USB mobile devices. They share 4A for charging multiple devices at the same time.

Includes the Latest Safety Features to Maintain Your Equipment's Well-Being

An integrated 15A circuit breaker provides overload protection for connected devices. A green LED confirms at a glance that your equipment is protected.

Specifications

OVERVIEW	
UPC Code	037332283450
Product Type	Surge Protector

Highlights

- 6 NEMA 5-15R outlets distribute AC power to connected home/office/work equipment
- 490 joules protect your valuable electronics against dangerous surges and spikes
- Plugs directly into the wall (no cord required) for easy installation and no cable clutter
- USB ports share 4A for fast charging of phones and other mobile devices
- Easy-to-see green LED lets you know at a glance that your equipment is protected

Package Includes

- SK62USBC 6-Outlet Surge Protector, Black
- Owner's manual





Charging Form Factor	Direct Plug-In	
Device Compatibility	Phone; Tablet; Amazon Kindle	
INPUT		
Nominal Input Voltage(s) Supported	120V AC	
Recommended Electrical Service	120V	
Input Cord Length Details	Direct Plug-In	
Voltage Compatibility (VAC)	120	
Input Plug Type	NEMA 5-15P	
Input Cord Length (ft.)	0	
Right-Angle Plug	No	
Input Cord Length (m)	0.00	
Integrated Cord Clip	No	
OUTPUT		
Frequency Compatibility	60 Hz	
Output (Watts)	1875	
Output Receptacles	(6) 5-15R	
Circuit Breaker (amps)	15	
Transformer Accommodation	(4) Yes	
Right-Angle Outlets	No	
USER INTERFACE, ALERTS & CON	TROLS	
Diagnostic LED(s)	Yes	
Diagnostic LED Details	Green - Protected	
CHARGING		
Number of Charging Ports	2	
Total Charging Amps	4	
Total Charging Watts	1875	
Charging Method	USB	
Charging Port Type	USB A (FEMALE); USB C (FEMALE)	
Charging Ports / Amps	(2) 2A	
Overcharge Protection	No	
Charging Amps per Port	2A	
SURGE / NOISE SUPPRESSION		
AC Suppression Joule Rating	490	





AC Suppression Response Time	< 1 ns	
Protection Modes	L-N line suppression	
UL1449 Let Through Rating	600	
EMI / RFI Filtering	150KHz-100MHz	
Isolated Filter Banks	no	
Immunity	Conforms to IEE 587/ANSI C62.41	
Automatic Shut-Off	No	
DATALINE SURGE SUPPRESSION		
Cable (Coax) Protection	No	
Network (Ethernet) Protection	No	
Telephone/DSL Protection	No	
PHYSICAL		
Material of Construction	Plastic	
Housing Color	Black	
Mounting Holes or Slots	No	
Receptacle Color	Black	
Shipping Dimensions (hwd / in.)	7.30 x 3.80 x 2.90	
Shipping Dimensions (hwd / cm)	18.54 x 9.65 x 7.37	
Shipping Weight (lbs.)	0.73	
Shipping Weight (kg)	0.33	
Unit Dimensions (hwd / in.)	5.600 x 3.600 x 2.800	
Unit Dimensions (hwd / cm)	14.2 x 9.1 x 7.1	
Unit Weight (lbs.)	0.57	
Unit Weight (kg)	0.26	
FEATURES & SPECIFICATIONS		
Rotatable Outlets	No	
Antimicrobial	No	
GaN Technology	No	
STANDARDS & COMPLIANCE		
Product Certifications	CAN/CSA-C22.2 No. 269.3 (Canada); CAN/CSA-C22.2 No. 42 (Canada); UL 1449	
Product Compliance	FCC Part 15 Class B (USA); RoHS	
WARRANTY & SUPPORT		





Product Warranty Period (Worldwide)	Lifetime limited warranty
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$20,000 Ultimate Lifetime Insurance

1000 Eaton Boulevard Cleveland, OH 44122 United States https://tripplite.eaton.com © 2025 Eaton. All Rights Reserved.

Eaton is a registered trademark. All other trademarks are the property of their respective owners.