



4-Outlet Surge Protector with 4 USB Ports (4.2A Shared) - 6 ft. (1.83 m) Cord, 450 Joules, Metal Housing

MODEL NUMBER: TLM446USBB









4-outlet surge protector safeguards your home/office electronics against dangerous surges, spikes and line noise.

Features

4-Outlet Surge Protector with USB Safeguards Your Sensitive ElectronicsIdeal for your home, office, retail or industrial workstation, this Protect It!® 4-outlet surge protector features a surge protection rating of 450 joules to defend your sensitive electronic components against power surges and spikes.

NEMA 5-15R Outlets Accept a Wide Range of Electronic DevicesPlug your computer, printer, wireless router, desk lamp and other home/office electronics into four NEMA 5-15R outlets to protect them against dangerous surges, spikes and line noise.

4 USB Ports Share 4.2 Amps of Charging PowerThis surge protector with 4 USB ports is ideal for keeping your devices at full capacity. Four USB-A ports are available for charging your smartphone, tablet and other USB mobile devices.

Premium Protection from EMI/RFI Line Noise Helps Your Equipment Perform Better Various electromagnetic and radio sources found in virtually every home and business can cause disruptive interference on the AC line. Known as EMI (electromagnetic interference) and RFI (radio frequency interference), this line noise is a common cause of performance problems. This surge protector filters out disruptive line noise that can disturb your electronics and inflict hardware damage or data loss. This EMI/RFI filtering also helps your connected components perform better and last longer.

Includes the Latest Safety FeaturesThe lighted on/off switch provides one-touch control over connected equipment.

Versatile Surge Protector Provides Multiple Installation OptionsThis surge protector with 6-ft. (1.83 m) cord and NEMA 5-15P plug gives you flexibility in placing the unit away from the nearest wall outlet.

Specifications

OVERVIEW

Highlights

- 4 NEMA 5-15R outlets distribute AC power to connected home/office equipment
- 450 joules protect your valuable electronics against dangerous surges and spikes
- 4 USB ports share 4.2A for fast charging of phones, tablets and other mobile devices
- 6-ft. (1.83 m) cord with NEMA 5-15P plug allows flexibility in placing devices away from AC outlet
- Durable metal housing designed to stand up in harsh environments, such as warehouses

Applications

- Protect computers, peripherals, home theater equipment and other valuable electronics against AC power surges and spikes
- Filter potentially damaging line noise to improve connected equipment's performance and lifespan
- Safeguard valuable data against corruption stemming from unexpected surges
- Charge smartphones, tablets or other USB devices via USB ports

Package Includes

- TLM446USBB Protect It! 4-Outlet Surge Protector, Black Metal Housing
- · Owner's manual





UPC Code	037332223463	
Product Type	Surge Protector	
Charging Form Factor	Strip	
Device Compatibility	Phone; Tablet; Amazon Kindle	
INDUT.		
INPUT		
Nominal Input Voltage(s) Supported	120V AC	
Recommended Electrical Service	120V (110-125V)	
Input Cord Gauge Type	14 gauge; SJT	
Input Cord Gauge (AWG)	14	
Voltage Compatibility (VAC)	120	
Maximum Surge Amps	35500	
Input Plug Type	NEMA 5-15P	
Input Cord Details	SJT	
Input Cord Length (ft.)	6	
Right-Angle Plug	No	
Input Cord Length (m)	1.83	
Integrated Cord Clip	No	
ОИТРИТ		
Frequency Compatibility	50 / 60 Hz	
Output (Watts)	1800	
Output Receptacles	(4) 5-15R	
Circuit Breaker (amps)	15	
Overload Protection	15A resettable illuminated combo switch / circuit breaker	
Transformer Accommodation	(4) Yes	
Outlet Orientation	Single row of 4 outlets	
Right-Angle Outlets	Yes	
USER INTERFACE, ALERTS & CONTROLS		
Diagnostic LED(s)	Yes	
Switches	Combination AC circuit breaker and 2 position red illuminated on/off power switch	
CHARGING		
Number of Charging Ports	4	
Total Charging Watts	21	
Charging Method	USB	





Charging Port Type USB A (FEMALE) Charging Ports / Amps (4) 4.2A Overcharge Protection No SURGE / NOISE SUPPRESSION AC Suppression Joule Rating 450 AC Suppression Joule Rating 800 EMI / RF Filtering Yes Automatic Shut-Olf No DATALINE SURGE SUPPRESSION Cable (Coasy) Protection No Telephone/DSL Protection Metal Protection Selection Metal	Changing Dort Tun	LICE A (FEMALE)		
Overcharge Protection No SURGE / NOISE SUPPRESSION AC Suppression Joule Rating 450 AC Suppression Response Time < 1 ns				
SURGE / NOISE SUPPRESSION AC Suppression Joule Rating AC Suppression Joule Rating AC Suppression Response Time <1 ns UL:1449 Let Through Rating 800 EMI / RFI Filtering Yes Automatic Shur-Off No DATALINE SURGE SUPPRESSION Cable (Coax) Protection No Network (Ethernet) Protection No Telephone/DSL Protection No PHYSICAL Material of Construction Metal Power Cord Color Black Housing Color Black Mounting Holes or Stots No Receptacle Color Shipping Dimensions (twd / in.) 12.99 x 4.72 x 1.97 Shipping Weight (kg) 0.68 Unit Dimensions (hwd / in.) 11.380 x 1.870 x 1.750 Unit Weight (Ibs.) 1.29 Unit Weight (kg) 0.59 FEATURES & SPECIFICATIONS Rotable Outlets No Rotable Outlets No Rotal Outlets Rotal Rotal Outlets No Rotal Outlets Rotal Rotal Outlets No Rotal Rotal Outlets Rotal Rotal Outlets Rotal		(4) 4.2A		
AC Suppression Joule Rating 450 AC Suppression Response Time <1 ns	Overcharge Protection	No		
AC Suppression Response Time < 1 ns	SURGE / NOISE SUPPRESSION	SURGE / NOISE SUPPRESSION		
UL1449 Let Through Rating 800 EMI / RFI Filtering Yes Automatic Shut-Off No DATALINE SURGE SUPPRESSION Cable (Coax) Protection No Network (Ethernet) Protection No PHYSICAL Material of Construction Metal Power Cord Color Black Housing Color Black Mounting Holes or Slots No Receptacle Color Black Shipping Dimensions (theyd / in.) 12.99 x 4.72 x 1.97 Shipping Weight (kg) 0.68 Unit Dimensions (hwd / in.) 11.380 x 1.870 x 1.750 Unit Weight (kg) 0.59 FEATURES & SPECIFICATIONS* Rotatable Outlets No Antimicrobial No Gan Technology No STANDARDS & COMPLIANCE Product Certifications CANCSA-C22.2 No. 308 (Canada); CANCSA-C22.2 No. 8 (Canada); CUL Listed; NOM (Mexico); UL 1449; UL	AC Suppression Joule Rating	450		
EMI / RFI Filtering Yes Automatic Shut-Off No PATALINE SURGE SUPPRESSION Cable (Coax) Protection No Network (Ethernet) Protection No Telephone/DSL Protection No PHYSICAL Material of Construction Metal Power Cord Color Black Mounting Holes or Slots No Receptacle Color Black Shipping Dimensions (hwd / in.) 12.99 x.4.72 x.1.97 Shipping Weight (kg) 0.68 Unit Dimensions (hwd / in.) 11.380 x.1.870 x.1.750 Unit Weight (lbs.) 1.29 Unit Weight (kg) 0.59 FEATURES & SPECIFICATIONS Roan Technology No CANCSA-C22.2 No. 308 (Canada); CAN/CSA-C22.2 No. 8 (Canada); cUL Listed; NOM (Mexico); UL 1449; UL	AC Suppression Response Time	< 1 ns		
Automatic Shut-Off No DATALINE SURGE SUPPRESSION Cable (Coax) Protection No Network (Ethernet) Protection No PHYSICAL Material of Construction Metal Power Cord Color Black Housing Color Black Mounting Holes or Slots No Receptacle Color Black Shipping Dimensions (hwd / in.) 12.99 x 4.72 x 1.97 Shipping Weight (kg) 0.68 Unit Dimensions (hwd / in.) 11.380 x 1.870 x 1.750 Unit Weight (lbs.) 1.29 Unit Weight (kg) 0.59 FEATURES & SPECIFICATIONS Rotable Outlets No Antimicrobial No Antimicrobial No STANDARDS & COMPLIANCE Product Certifications CANICSA-C22.2 No. 308 (Canada); CANICSA-C22.2 No. 8 (Canada); cUL Listed; NOM (Mexico); UL 1449; UL	UL1449 Let Through Rating	800		
DATALINE SURGE SUPPRESSION Cable (Coax) Protection No Network (Ethernet) Protection No Telephone/DSL Protection No PHYSICAL Material of Construction Metal Power Cord Color Black Housing Color Black Mounting Holes or Slots No Receptacle Color Black Shipping Dimensions (hwd / in.) 12.99 x 4.72 x 1.97 Shipping Weight (kg) 0.68 Unit Dimensions (hwd / in.) 11.380 x 1.870 x 1.750 Unit Weight (lbs.) 1.29 Unit Weight (kg) 0.59 FEATURES & SPECIFICATIONS Rotatable Outlets No Antimicrobial No GaN Technology No STANDARDS & COMPLIANCE Product Certifications CAN/CSA-C22.2 No. 308 (Canada); CAN/CSA-C22.2 No. 8 (Canada); cUL Listed; NOM (Mexico); UL 1448; UL	EMI / RFI Filtering	Yes		
Cable (Coax) Protection No Network (Ethernet) Protection No PHYSICAL Material of Construction Metal Power Cord Color Black Housing Color Black Mounting Holes or Slots No Receptacle Color Black Shipping Dimensions (hwd / in.) 12.99 x 4.72 x 1.97 Shipping Weight (kg) 0.68 Unit Dimensions (hwd / in.) 11.380 x 1.870 x 1.750 Unit Dimensions (hwd / cm) 28.91 x 4.75 x 4.44 Unit Weight (kg) 0.59 FEATURES & SPECIFICATIONS Rotatable Outlets No Antimicrobial No GaN Technology No STANDARDS & COMPLIANCE Product Certifications CAN/CSA-C22.2 No. 308 (Canada); CAN/CSA-C22.2 No. 8 (Canada); cUL Listed; NOM (Mexico); UL 1449; UL	Automatic Shut-Off	No		
Nework (Ethernet) Protection No Telephone/DSL Protection No PHYSICAL Material of Construction Metal Power Cord Color Black Housing Color Black Mounting Holes or Slots No Receptacle Color Black Shipping Dimensions (hwd / in.) 12.99 x 4.72 x 1.97 Shipping Weight (kg) 0.68 Unit Dimensions (hwd / in.) 11.380 x 1.870 x 1.750 Unit Dimensions (hwd / orn) 28.91 x 4.75 x 4.44 Unit Weight (kg) 0.59 FEATURES & SPECIFICATIONS Rotatable Outlets No Antimicrobial No GaN Technology No STANDARDS & COMPLIANCE Product Certifications CAN/CSA-C22.2 No. 308 (Canada); CAN/CSA-C22.2 No. 8 (Canada); cUL Listed; NOM (Mexico); UL 1449; UL	DATALINE SURGE SUPPRESSION			
PHYSICAL Material of Construction Metal Power Cord Color Black Housing Color Black Mounting Holes or Slots No Receptacle Color Black Shipping Dimensions (hwd / in.) 12.99 x 4.72 x 1.97 Shipping Weight (kg) 0.68 Unit Dimensions (hwd / in.) 11.380 x 1.870 x 1.750 Unit Dimensions (hwd / or.) 28.91 x 4.75 x 4.44 Unit Weight (lbs.) 1.29 Unit Weight (kg) 0.59 FEATURES & SPECIFICATIONS Rotatable Outlets No Antimicrobial No GaN Technology No STANDARDS & COMPLIANCE Product Certifications CAN/CSA-C22.2 No. 308 (Canada); CAN/CSA-C22.2 No. 8 (Canada); cUL Listed; NOM (Mexico); UL 1449; UL	Cable (Coax) Protection	No		
Material of Construction Metal Power Cord Color Black Housing Color Black Mounting Holes or Slots No Receptacle Color Black Shipping Dimensions (hwd / in.) 12.99 x 4.72 x 1.97 Shipping Weight (kg) 0.68 Unit Dimensions (hwd / in.) 11.380 x 1.870 x 1.750 Unit Dimensions (hwd / cm) 28.91 x 4.75 x 4.44 Unit Weight (lbs.) 1.29 Unit Weight (kg) 0.59 FEATURES & SPECIFICATIONS Rotatable Outlets No Antimicrobial No GaN Technology No STANDARDS & COMPLIANCE Product Certifications CAN/CSA-C22.2 No. 308 (Canada); CAN/CSA-C22.2 No. 8 (Canada); cUL Listed; NOM (Mexico); UL 1449; UL	Network (Ethernet) Protection	No		
Material of Construction Metal Power Cord Color Black Housing Color Black Mounting Holes or Slots No Receptacle Color Black Shipping Dimensions (hwd / in.) 12.99 x 4.72 x 1.97 Shipping Weight (kg) 0.68 Unit Dimensions (hwd / in.) 11.380 x 1.870 x 1.750 Unit Dimensions (hwd / cm) 28.91 x 4.75 x 4.44 Unit Weight (lbs.) 1.29 Unit Weight (kg) 0.59 FEATURES & SPECIFICATIONS Rotatable Outlets No Antimicrobial No GaN Technology No STANDARDS & COMPLIANCE Product Certifications CAN/CSA-C22.2 No. 308 (Canada); CAN/CSA-C22.2 No. 8 (Canada); cUL Listed; NOM (Mexico); UL 1449; UL 1363; UL Listed	Telephone/DSL Protection	No		
Power Cord Color Black Housing Color Black Mounting Holes or Slots No Receptacle Color Black Shipping Dimensions (hwd / in.) 12.99 x 4.72 x 1.97 Shipping Weight (kg) 0.68 Unit Dimensions (hwd / in.) 11.380 x 1.870 x 1.750 Unit Dimensions (hwd / cm) 28.91 x 4.75 x 4.44 Unit Weight (lbs.) 1.29 Unit Weight (kg) 0.59 FEATURES & SPECIFICATIONS Rotatable Outlets No Antimicrobial No GaN Technology No STANDARDS & COMPLIANCE Product Certifications CAN/CSA-C22.2 No. 308 (Canada); CAN/CSA-C22.2 No. 8 (Canada); cUL Listed; NOM (Mexico); UL 1449; UL 1363; UL Listed	PHYSICAL			
Housing Color Black Mounting Holes or Slots No Receptacle Color Black Shipping Dimensions (hwd / in.) 12.99 x 4.72 x 1.97 Shipping Weight (kg) 0.68 Unit Dimensions (hwd / in.) 11.380 x 1.870 x 1.750 Unit Dimensions (hwd / cm) 28.91 x 4.75 x 4.44 Unit Weight (lbs.) 1.29 Unit Weight (kg) 0.59 FEATURES & SPECIFICATIONS Rotable Outlets No Antimicrobial No GaN Technology No STANDARDS & COMPLIANCE Product Certifications CAN/CSA-C22.2 No. 308 (Canada); CAN/CSA-C22.2 No. 8 (Canada); cUL Listed; NOM (Mexico); UL 1449; UL 1363; UL Listed	Material of Construction	Metal		
Mounting Holes or Slots Receptacle Color Black Shipping Dimensions (hwd / in.) 12.99 x 4.72 x 1.97 Shipping Weight (kg) 0.68 Unit Dimensions (hwd / in.) 11.380 x 1.870 x 1.750 Unit Dimensions (hwd / cm) 28.91 x 4.75 x 4.44 Unit Weight (lbs.) 1.29 Unit Weight (kg) 0.59 FEATURES & SPECIFICATIONS Rotatable Outlets No Antimicrobial No GaN Technology No STANDARDS & COMPLIANCE Product Certifications CAN/CSA-C22.2 No. 308 (Canada); CAN/CSA-C22.2 No. 8 (Canada); cUL Listed; NOM (Mexico); UL 1449; UL 1363; UL Listed	Power Cord Color	Black		
Receptacle Color Shipping Dimensions (hwd / in.) 12.99 x 4.72 x 1.97 Shipping Weight (kg) 0.68 Unit Dimensions (hwd / in.) 11.380 x 1.870 x 1.750 Unit Dimensions (hwd / cm) 28.91 x 4.75 x 4.44 Unit Weight (lbs.) 1.29 Unit Weight (kg) 0.59 FEATURES & SPECIFICATIONS Rotatable Outlets No Antimicrobial No GaN Technology No STANDARDS & COMPLIANCE Product Certifications CAN/CSA-C22.2 No. 308 (Canada); CAN/CSA-C22.2 No. 8 (Canada); cUL Listed; NOM (Mexico); UL 1449; UL 1363; UL Listed	Housing Color	Black		
Shipping Dimensions (hwd / in.) Shipping Weight (kg) 0.68 Unit Dimensions (hwd / in.) 11.380 x 1.870 x 1.750 Unit Dimensions (hwd / cm) 28.91 x 4.75 x 4.44 Unit Weight (lbs.) 1.29 Unit Weight (kg) 0.59 FEATURES & SPECIFICATIONS Rotatable Outlets No Antimicrobial No GaN Technology No STANDARDS & COMPLIANCE Product Certifications 12.99 x 4.72 x 1.97 Product Certifications 11.380 x 1.870 x 1.750 28.91 x 4.75 x 4.44 1.29	Mounting Holes or Slots	No		
Shipping Weight (kg) Unit Dimensions (hwd / in.) 11.380 x 1.870 x 1.750 Unit Dimensions (hwd / cm) 28.91 x 4.75 x 4.44 Unit Weight (lbs.) 1.29 Unit Weight (kg) 5.59 FEATURES & SPECIFICATIONS Rotatable Outlets No Antimicrobial No GaN Technology No STANDARDS & COMPLIANCE Product Certifications CAN/CSA-C22.2 No. 308 (Canada); CAN/CSA-C22.2 No. 8 (Canada); cUL Listed; NOM (Mexico); UL 1449; UL 1363; UL Listed	Receptacle Color	Black		
Unit Dimensions (hwd / in.) 11.380 x 1.870 x 1.750 Unit Dimensions (hwd / cm) 28.91 x 4.75 x 4.44 Unit Weight (lbs.) 1.29 Unit Weight (kg) 0.59 FEATURES & SPECIFICATIONS Rotatable Outlets No Antimicrobial No GaN Technology No STANDARDS & COMPLIANCE Product Certifications CAN/CSA-C22.2 No. 308 (Canada); CAN/CSA-C22.2 No. 8 (Canada); cUL Listed; NOM (Mexico); UL 1449; UL 1363; UL Listed	Shipping Dimensions (hwd / in.)	12.99 x 4.72 x 1.97		
Unit Dimensions (hwd / cm) 28.91 x 4.75 x 4.44 Unit Weight (lbs.) 1.29 Unit Weight (kg) 5.59 FEATURES & SPECIFICATIONS Rotatable Outlets No Antimicrobial No GaN Technology No STANDARDS & COMPLIANCE Product Certifications CAN/CSA-C22.2 No. 308 (Canada); CAN/CSA-C22.2 No. 8 (Canada); cUL Listed; NOM (Mexico); UL 1449; UL 1363; UL Listed	Shipping Weight (kg)	0.68		
Unit Weight (kg) 1.29 Unit Weight (kg) 0.59 FEATURES & SPECIFICATIONS Rotatable Outlets No Antimicrobial No GaN Technology No STANDARDS & COMPLIANCE Product Certifications 1.29 1	Unit Dimensions (hwd / in.)	11.380 x 1.870 x 1.750		
Unit Weight (kg) FEATURES & SPECIFICATIONS Rotatable Outlets No Antimicrobial No GaN Technology No STANDARDS & COMPLIANCE Product Certifications CAN/CSA-C22.2 No. 308 (Canada); CAN/CSA-C22.2 No. 8 (Canada); cUL Listed; NOM (Mexico); UL 1449; UL	Unit Dimensions (hwd / cm)	28.91 x 4.75 x 4.44		
FEATURES & SPECIFICATIONS Rotatable Outlets No Antimicrobial No GaN Technology No STANDARDS & COMPLIANCE Product Certifications CAN/CSA-C22.2 No. 308 (Canada); CAN/CSA-C22.2 No. 8 (Canada); cUL Listed; NOM (Mexico); UL 1449; UL 1363; UL Listed	Unit Weight (lbs.)	1.29		
Rotatable Outlets No Antimicrobial No GaN Technology No STANDARDS & COMPLIANCE Product Certifications CAN/CSA-C22.2 No. 308 (Canada); CAN/CSA-C22.2 No. 8 (Canada); cUL Listed; NOM (Mexico); UL 1449; UL 1363; UL Listed	Unit Weight (kg)	0.59		
Antimicrobial No GaN Technology No STANDARDS & COMPLIANCE Product Certifications CAN/CSA-C22.2 No. 308 (Canada); CAN/CSA-C22.2 No. 8 (Canada); cUL Listed; NOM (Mexico); UL 1449; UL 1363; UL Listed	FEATURES & SPECIFICATIONS			
GaN Technology No STANDARDS & COMPLIANCE Product Certifications CAN/CSA-C22.2 No. 308 (Canada); CAN/CSA-C22.2 No. 8 (Canada); cUL Listed; NOM (Mexico); UL 1449; UL 1363; UL Listed	Rotatable Outlets	No		
STANDARDS & COMPLIANCE Product Certifications CAN/CSA-C22.2 No. 308 (Canada); CAN/CSA-C22.2 No. 8 (Canada); cUL Listed; NOM (Mexico); UL 1449; UL 1363; UL Listed	Antimicrobial	No		
Product Certifications CAN/CSA-C22.2 No. 308 (Canada); CAN/CSA-C22.2 No. 8 (Canada); cUL Listed; NOM (Mexico); UL 1449; UL 1363; UL Listed	GaN Technology	No		
1363; UL Listed	STANDARDS & COMPLIANCE			
Product Compliance FCC Part 68; RoHS	Product Certifications	CAN/CSA-C22.2 No. 308 (Canada); CAN/CSA-C22.2 No. 8 (Canada); cUL Listed; NOM (Mexico); UL 1449; UL 1363; UL Listed		
	Product Compliance	FCC Part 68; RoHS		





WARRANTY & SUPPORT		
Product Warranty Period (Worldwide)	Lifetime limited warranty	
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$10,000 Ultimate Lifetime Insurance	

1000 Eaton Boulevard Cleveland, OH 44122 United States https://tripplite.eaton.com © 2025 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.