



5-Outlet Surge Protector with 1 USB-A and 1 USB-C (3.9A Shared) - 6 ft. Cord, 2100 Joules, Metal Housing

MODEL NUMBER: TLM506USBC











5-outlet surge protector safeguards your home/office electronics against dangerous surges, spikes and line noise.

Features

5-Outlet Surge Protector with USB Safeguards Your Sensitive Electronics

Ideal for your home, office, retail or industrial workstation, this Protect It!® 5-outlet surge protector features a surge protection rating of 2100 joules to defend your sensitive electronic components against power surges and spikes. Because residential power outlets have three wires—hot line (H), neutral (N) and ground (G)—the TLM506USBC protects all three, covering the two protection modes: full normal mode (H-N) and common mode (N-G/H-G).

NEMA 5-15R Outlets Accept a Wide Range of Electronic Devices

Plug your computer, printer, wireless router, desk lamp and other home/office electronics into five NEMA 5-15R outlets to protect them against dangerous surges, spikes and line noise. One outlet is separated from the others to allow connection of bulky transformers without blocking adjacent outlets.

2 USB Ports Share 3.9 Amps of Charging Power

This surge protector with one USB-A port and one USB-C port is ideal for keeping your devices at full capacity. The USB ports are available for charging your smartphone, tablet and other mobile devices.

Premium Protection from EMI/RFI Line Noise Helps Your Equipment Perform Better

Various electromagnetic and radio sources found in virtually every home and business can cause disruptive interference on the AC line. Known as EMI (electromagnetic interference) and RFI (radio frequency interference), this line noise is a common cause of performance problems. This surge protector filters out disruptive line noise that can disturb your electronics and inflict hardware damage or data loss. This EMI/RFI filtering also helps your connected components perform better and last longer.

Includes the Latest Safety Features

The lighted on/off switch with integrated circuit breaker provides one-touch control over connected equipment. LEDs let you know when your connected devices are properly protected. Each outlet features a built-in safety cover to protect it from dust and other debris when not in use.

Versatile Surge Protector Provides Multiple Installation Options

This surge protector with 6-foot braided AC input cord and NEMA 5-15P plug gives you flexibility in placing the unit away from the nearest wall outlet. Keyhole slots incorporated into the bottom panel provide convenient wall or desk mounting options for the black metal housing.

Highlights

- 5 NEMA 5-15R outlets distribute AC power to connected home/office equipment
- 2100 joules protect your valuable electronics against dangerous surges and spikes
- USB-A and USB-C ports share 3.9A for fast charging of phones and other mobile devices
- 6 ft. braided input cord allows flexibility in placing devices away from wall outlet
- Durable metal housing designed to stand up in harsh environments, such as warehouses

Applications

- Protect computers, peripherals, home theater equipment and other valuable electronics against AC power surges and spikes
- Filter potentially damaging line noise to improve connected equipment's performance and lifespan
- Safeguard valuable data against damage stemming from unexpected surges
- Charge smartphones, tablets or other USB devices via USB ports

Package Includes

- TLM506USBC Protect It! 5-Outlet Surge Protector, Black Metal Housing
- Owner's manual





Specifications

OVERVIEW		
UPC Code	037332260062	
Product Type	Surge Protector	
Charging Form Factor	Strip	
Device Compatibility	Phone; Tablet; Amazon Kindle	
INPUT		
Nominal Input Voltage(s) Supported	120V AC	
Recommended Electrical Service	120V (110-125V)	
Input Cord Gauge Type	14 gauge; SJT	
Input Cord Gauge (AWG)	14	
Voltage Compatibility (VAC)	120	
Maximum Surge Amps	35500	
Input Plug Type	NEMA 5-15P	
Input Cord Details	SJT	
Input Cord Length (ft.)	6	
Right-Angle Plug	No	
Input Cord Length (m)	1.83	
Integrated Cord Clip	No	
ОИТРИТ		
Frequency Compatibility	50 / 60 Hz	
Output (Watts)	1800	
Output Receptacles	(5) 5-15R	
Circuit Breaker (amps)	15	
Overload Protection	15A resettable illuminated combo switch / circuit breaker	
Transformer Accommodation	(1) Yes	
Outlet Orientation	Single row of 5 outlets	
Right-Angle Outlets	Yes	
USER INTERFACE, ALERTS & CONTROLS		
Diagnostic LED(s)	Yes	
Switches	Combination AC circuit breaker and 2 position red illuminated on/off power switch	
Diagnostic LED Details	1x Green Protected and 1x Red Grounded	





Charging Ports / Amps (2) 3 Overcharge Protection No SURGE / NOISE SUPPRESSION AC Suppression Joule Rating 2100 AC Suppression Response Time < 1 r Protection Modes Inclu	USB A (FEMALE); (1) USB C (FEMALE)		
Total Charging Watts Charging Method Charging Port Type (1) U Charging Ports / Amps Overcharge Protection No SURGE / NOISE SUPPRESSION AC Suppression Joule Rating AC Suppression Response Time Protection Modes UL1449 Let Through Rating EMI / RFI Filtering Automatic Shut-Off Yes DATALINE SURGE SUPPRESSION Cable (Coax) Protection No	USB A (FEMALE); (1) USB C (FEMALE)		
Charging Method USB Charging Port Type (1) U Charging Ports / Amps (2) 3 Overcharge Protection No SURGE / NOISE SUPPRESSION AC Suppression Joule Rating 2100 AC Suppression Response Time < 1 r Protection Modes Inclu UL1449 Let Through Rating L-N, EMI / RFI Filtering Yes Automatic Shut-Off Yes DATALINE SURGE SUPPRESSION Cable (Coax) Protection No	USB A (FEMALE); (1) USB C (FEMALE)		
Charging Port Type (1) U Charging Ports / Amps (2) 3 Overcharge Protection No SURGE / NOISE SUPPRESSION AC Suppression Joule Rating 2100 AC Suppression Response Time < 1 r Protection Modes Inclu UL1449 Let Through Rating L-N, EMI / RFI Filtering Yes Automatic Shut-Off Yes DATALINE SURGE SUPPRESSION Cable (Coax) Protection No	USB A (FEMALE); (1) USB C (FEMALE)		
Charging Ports / Amps (2) 3 Overcharge Protection No SURGE / NOISE SUPPRESSION AC Suppression Joule Rating 2100 AC Suppression Response Time < 1 r Protection Modes Inclu UL1449 Let Through Rating L-N, EMI / RFI Filtering Yes Automatic Shut-Off Yes DATALINE SURGE SUPPRESSION Cable (Coax) Protection No			
Overcharge Protection No SURGE / NOISE SUPPRESSION AC Suppression Joule Rating 2100 AC Suppression Response Time < 1 r Protection Modes Inclu UL1449 Let Through Rating L-N, EMI / RFI Filtering Yes Automatic Shut-Off Yes DATALINE SURGE SUPPRESSION Cable (Coax) Protection No	3.04		
SURGE / NOISE SUPPRESSION AC Suppression Joule Rating 2100 AC Suppression Response Time < 1 r Protection Modes Inclu UL1449 Let Through Rating L-N, EMI / RFI Filtering Yes Automatic Shut-Off Yes DATALINE SURGE SUPPRESSION Cable (Coax) Protection No	5.07		
AC Suppression Joule Rating 2100 AC Suppression Response Time < 1 r Protection Modes Inclu UL1449 Let Through Rating L-N, EMI / RFI Filtering Yes Automatic Shut-Off Yes DATALINE SURGE SUPPRESSION Cable (Coax) Protection No			
AC Suppression Response Time < 1 r Protection Modes Inclu UL1449 Let Through Rating L-N, EMI / RFI Filtering Yes Automatic Shut-Off Yes DATALINE SURGE SUPPRESSION Cable (Coax) Protection No	SURGE / NOISE SUPPRESSION		
Protection Modes Inclu UL1449 Let Through Rating L-N, EMI / RFI Filtering Yes Automatic Shut-Off Yes DATALINE SURGE SUPPRESSION Cable (Coax) Protection No	0		
UL1449 Let Through Rating L-N, EMI / RFI Filtering Automatic Shut-Off PATALINE SURGE SUPPRESSION Cable (Coax) Protection No	ns		
EMI / RFI Filtering Yes Automatic Shut-Off Yes DATALINE SURGE SUPPRESSION Cable (Coax) Protection No	udes full normal mode (H-N) and common mode (N-G / H-G) line suppression		
Automatic Shut-Off Yes DATALINE SURGE SUPPRESSION Cable (Coax) Protection No	, L-G, N-G, 500, 500, 500		
DATALINE SURGE SUPPRESSION Cable (Coax) Protection No			
Cable (Coax) Protection No			
	DATALINE SURGE SUPPRESSION		
Network (Ethernet) Protection No			
Telephone/DSL Protection No			
PHYSICAL			
Material of Construction Meta	al		
Power Cord Color Black	ck; Gray Braided Cord		
Housing Color Black	ck; Silver		
Mounting Holes or Slots No			
Receptacle Color Black	ck		
Unit Dimensions (hwd / in.) 8.600	00 x 2.800 x 1.400		
Unit Dimensions (hwd / cm) 21.8-	34 x 7.11 x 3.56		
Unit Weight (lbs.) 1.03	3		
Unit Weight (kg) 0.47	,		
FEATURES & SPECIFICATIONS			
Rotatable Outlets No			
Antimicrobial No			
GaN Technology No			





STANDARDS & COMPLIANCE		
Product Certifications	CAN/CSA-C22.2 No. 269.3 (Canada); CAN/CSA-C22.2 No. 308 (Canada); UL 1449; UL 1363	
Product Compliance	RoHS	
WARRANTY & SUPPORT		
Product Warranty Period (Worldwide)	Lifetime limited warranty	
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$25,000 Ultimate Lifetime Insurance	

1000 Eaton Boulevard Cleveland, OH 44122 United States https://tripplite.eaton.com © 2025 Eaton. All Rights Reserved.

Eaton is a registered trademark. All other trademarks are the property of their respective owners.