



Power It! Power Strip with 6 Right-Angle Outlets, 15 ft. (4.57 m) Cord, Transparent Switch Cover

MODEL NUMBER: TLM615NCRA



Description

The Power It!® TLM615NCRA power strip offers reliable, convenient and cost-effective power distribution for appliances, power tools, lighting and other electrical equipment. Includes six right-angle NEMA 5-15R outlets, 15-foot (4.6-meter) AC power cord and keyhole mounting slots. Multi-outlet strip reduces cable clutter and enables the connection of multiple electrical devices to a single AC wall socket. Features rugged metal case to stand up to the most demanding environments, illuminated power switch with transparent cover to prevent accidental shutoff and 15A integrated circuit breaker to prevent dangerous overloads.

Features

- Multi-outlet power strip offers reliable, convenient and cost-effective power distribution for appliances, power tools, lighting and other electrical equipment
- Includes 6 right-angle NEMA 5-15R outlets
- Illuminated on/off switch provides one-touch power control for connected equipment
- · Transparent switch cover snaps tight to prevent accidental shutoff
- Convenient keyhole slots provide secure mounting options for a wide variety of surfaces and applications
- 15A power handling capacity with integrated circuit breaker
- 120V AC, 50/60Hz electrical compatibility
- 15-ft. (4.57 m) AC power cord
- Rugged metal case provides extra safety and durability
- UL certification

Specifications

OVERVIEW	
UPC Code	037332135681
INPUT	

Highlights

- 6 right-angle outlets
- Illuminated on/off switch with cover
- 15-amp circuit breaker
- 15-ft. (4.57 m) power cord
- Rugged metal case
- Keyhole mounting slots

Package Includes

- TLM615NCRA power strip
- Warranty information
- Instruction manual





Nominal Input Voltage(s) Supported 120V AC Recommended Electrical Sovice 15A 120V Input Cord Gauge Type 14 gauge: SJT Voltage Comparability (VAC) 120 Input Plug Type NEMA 5-15P Input Cord Length (ft.) 15 Right-Angle Rlug No Input Cord Length (ft.) 4.57 Integrated Cord Clip No OUTPUT Frequency Compatibility Frequency Compatibility 50 / 60 Hz Output (Wath) 1800 Output Wath) 1800 Output Receptacles (6) 5-15R Circuit Breaker (amps) 15 Output Overtion 15A clicuit breaker Transformer Accommodation Single row of 6 (fight-angle) Right-Angle Outlets Yes USER INTERFACE, ALERTS & CONTROLS Switches Light Q 2 position switch controls power to all outlets Locking Switch Cover Preserved Color Light Gray Material Or Construction Metal Power Cord Color Light Gray Mounting Holes or Slets Yes <th></th> <th></th>		
Input Cord Gauge Type 14 gauge: SJT Voltage Compatibility (VAC) 120 Input Plug Type NEMA 5-15P Input Cord Length (ft) 15 Right-Angle Plug No Input Cord Length (m) 4.57 Integrated Cord Cip No OUTPUT Frequency Compatibility For Quput (Watts) 1800 Output Research (amps) 15 Circuit Breaker (amps) 15 Overload 16A (and the second of th	Nominal Input Voltage(s) Supported	120V AC
Votage Compatibility (VAC) 120 Input Plug Type NEMA 5-15P Input Cord Length (ft.) 15 Right-Angle Plug No Input Cord Length (m) 4.57 Integrated Cord Clip No OUTPUT Frequency Compatibility 50 / 60 Hz Output (Marks) Output Warks) 1800 Output Resker (amps) 15 Circuit Breaker (amps) 15 Overload Protection 15A circuit breaker Transformer Accommodation (3) Yes Outel Streaker & Ves Yes USER INTERFACE, ALERTS & CONTEOLS Switches Lighted 2 position switch controls power to all outlets Locking Switch Cover Transparent switch cover snaps light to prevent accidental shutoff PHYSICAL Color Light Gray Maarial of Construction Metal Power Cord Color Light Gray Housing Color Light Gray Housing Color Light Gray Housing Color Light Gray	Recommended Electrical Service	15A 120V
Input Plug Type NEMA 5-15P Input Cord Length (ft.) 15 Right-Angle Plug No Input Cord Length (m) 4.57 Inregrated Cord Clip No OUTPUT Frequency Compatibility 50 / 60 Hz Output (Watts) 1800 Coulput (Watts) Output Reserve (amps) 15 Circuit Breaker (amps) 15 Overload Protection 15A circuit breaker Transformer Accommodation (3) Yes Outlet Orientation Single row of 6 (right-angle) Right-Angle Outlets Yes USER INTERFACE, ALERTS & CONTEOLS Switches Loding Switch Cover Transparent switch cover snaps tight to prevent accidental shutoff PHYSICAL Color Light Gray Material of Construction Metal Power Cord Color Light Gray Mounting Holes or Slots Yes Slot or Hole Mount Measurement (Center to Center I) Is2 in. Receptacle Color Light Gray Mounting Holes or Slots Yes Slot or Hole Mount Measurement (Center to Cent	Input Cord Gauge Type	14 gauge; SJT
Input Cord Length (tt.) 15 Right-Angle Plug No Input Cord Length (m) 4.57 Integrated Cord Clip No OUTPUT Frequency Compatibility 50 / 60 Hz Output (Watts) 1800 Output Receptacles (6) 5-15R Circuit Breaker (amps) 15 Overload Protection 15A circuit breaker Transformer Accommodation (3) Yes Outlet Orientation Single row of 6 (right-angle) Right-Angle Outlets Yes USER INTERFACE, ALERTS & CONTROLS Switches Switch Cover Transparent switch cover snaps tight to prevent accidental shutoff PHYSICAL Color Color Light Gray Material of Construction Metal Power Cord Color Light Gray Mounting Holes or Slots Yes Slot or Hole Mount Measurement (Center to Center) Distance between mounting tabs = 203.20mm; Distance between end tabs = 330.17mm Outlets Measurement (Center to enter) 1.62 in. Receptacle Color Light gray Shipping Dimensions (hwd / in.) 15.50 x 2.40 x 6.50	Voltage Compatibility (VAC)	120
Right-Angle Plug No Input Cord Length (m) 4.57 Integrated Cord Clip No OUTPUT Frequency Compatibility 50 / 60 Hz Output Receptacles (6) 5-15R Circuit Breaker (amps) 15 Overload Protection 15A circuit breaker Transformer Accommodation (3) Yes Outlet Orientation Single row of 6 (right-angle) Right-Angle Outlets Yes USER INTERFACE, ALERTS & CONTROLS Switches Lighted 2 position switch controls power to all outlets Locking Switch Cover Transparent switch cover snaps tight to prevent accidental shutoff PHYSICAL Color Light Gray Material of Construction Metal Power Cord Color Light Gray Mounting Holes or Stots Yes Distance between mounting tabs = 203.20mm: Distance between end tabs = 330.17mm Outlets Measurement (Center to Center to Center) 1.62 in. Receptacle Color Light gray Shipping Dimensions (hwd / in.) 15.50 x 2.40 x 6.50 Shipping Dimensions (hwd / cm) 39.37 x 6.10 x 16.51 <td>Input Plug Type</td> <td>NEMA 5-15P</td>	Input Plug Type	NEMA 5-15P
Input Cord Length (m) 4.57 Integrated Cord Clip No OUTPUT Frequency Compatibility 50 / 60 Hz Output (Wats) 1800 Output Receptacles (6) 5-15R Circuit Breaker (amps) 15 Overload Protection 15A circuit breaker Transformer Accommodation (3) Yes Outlet Orientation Single row of 6 (right-angle) Right-Angle Outlets Yes USER INTERFACE, ALERTS & CONTROLS Switches Lighted 2 position switch controls power to all outlets Locking Switch Cover PHYSICAL Color Light Gray Material of Construction Metal Pewer Cord Color Light Gray Mouning Holes or Stots Yes Sili or Hole Mount Neasurement (Center to Conter) Distance between mounting tabs = 203.20mm; Distance between end tabs = 330.17mm Outlets Measurement (Center to Conter) Light gray Shipping Dimensions (hwd / in.) 15.50 x 2.40 x 6.50 Shipping Dimensions (hwd / com) 39.37 x 6.10 x 16.51	Input Cord Length (ft.)	15
Integrated Cord Clip No OUTPUT Frequency Compatibility 50 / 60 Hz Output Receptacles (6) 5-15R Control (Watts) Circuit Breaker (amps) 15 Coverload Protection Overload Protection 15A circuit breaker Coverload Protection Transformer Accommodation (3) Yes Coulted Orientation Outlet Orientation Single row of 6 (right-angle) Right-Angle Outlets Yes VSER INTERFACE, ALERTS & CONTOLS Switches Lighted 2 position switch controls power to all outlets Locking Switch Cover Transparent switch cover snaps tight to prevent accidental shutoff PHYSICAL Color Light Gray Material of Construction Metal Power Cord Color Light Gray Mounting Holes or Slots Yes Slot or Hole Mount Measurement (Center to Center) Distance between mounting tabs = 203.20mm; Distance between end tabs = 330.17mm Outlets Measurement (Center to Center) 1.62 in. Receptacle Color Light gray Shipping Dimensions (hwd / in.) 15.50 x 2.40 x 6.50 Shipping Dimensions (hwd / in.) <t< td=""><td>Right-Angle Plug</td><td>No</td></t<>	Right-Angle Plug	No
OUTPUT Frequency Compatibility 50 / 60 Hz Output (Watts) 1800 Output (Receptacles (6) 5-15R Circuit Breaker (amps) 15 Overoad Protection 15A circuit breaker Transformer Accommodation (3) Yes Outlet Orientation Single row of 6 (right-angle) Right-Angle Outlets Yes USER INTERFACE, ALERTS & CONTROLS Switches Lighted 2 position switch controls power to all outlets Looking Switch Cover Transparent switch cover snaps tight to prevent accidental shutoff PHYSICAL Color Light Gray Material of Construction Metail Power Cord Color Light Gray Mounting Holes or Stors Yes Stor Hole Mount Measurement (Center to Center) Distance between mounting tabs = 203.20mm; Distance between end tabs = 330.17mm Outlets Measurement (Center to Center) 1.62 in. Receptacle Color Light gray Shipping Dimensions (hwd / in.) 15.50 x 2.40 x 6.50 Shipping Dimensions (hwd / orn) 39.37 x 6.10 x 16.51	Input Cord Length (m)	4.57
Frequency Compatibility 50 / 60 Hz Output (Wats) 1800 Output Receptacles (6) 5-15R Circuit Breaker (amps) 15 Overload Protection 15A circuit breaker Transformer Accommodation (3) Yes Outlet Orientation Single row of 6 (right-angle) Right-Angle Outlets Yes USER INTERFACE, ALERTS & CONTROLS Switches Lighted 2 position switch controls power to all outlets Locking Switch Cover Transparent switch cover snaps tight to prevent accidental shutoff PHYSICAL Color Light Gray Material of Construction Metal Power Cord Color Light Gray Housing Color Light Gray Mounting Holes or Slots Yes Slot or Hole Mount Measurement (Center to Center) Distance between mounting tabs = 203.20mm; Distance between end tabs = 330.17mm Outlets Measurement (Center to Center) 1.62 in. Receptacle Color Light gray Shipping Dimensions (hwd / in.) 15.50 x 2.40 x 6.50 Shipping Dimensions (hwd / rm) 39.37 x 6.10 x 16.51	Integrated Cord Clip	No
Output (Wats) 1800 Output Receptacles (6) 5-15R Circuit Breaker (amps) 15 Overload Protection 15A circuit breaker Transformer Accommodation (3) Yes Outlet Orientation Single row of 6 (right-angle) Right-Angle Outlets Yes USER INTERFACE, ALERTS & CONTROLS Switches Lighted 2 position switch controls power to all outlets Locking Switch Cover Transparent switch cover snaps tight to prevent accidental shutoff PHYSICAL Color Light Gray Material of Construction Metal Power Cord Color Light Gray Mounting Holes or Slots Yes Sist or Hole Mount Measurement (Center to Center) Distance between mounting tabs = 203.20mm; Distance between end tabs = 330.17mm Outlets Measurement (Center to Center) 1.62 in. Receptacle Color Light gray Shipping Dimensions (hwd / in.) 15.50 x 2.40 x 6.50 Shipping Dimensions (hwd / in.) 39.37 x 6.10 x 16.51	OUTPUT	
Output Receptacles (6) 5-15R Circuit Breaker (amps) 15 Overload Protection 15A circuit breaker Transformer Accommodation (3) Yes Outlet Orientation Single row of 6 (right-angle) Right-Angle Outlets Yes USER INTERFACE, ALERTS & CONTROLS Switches Lighted 2 position switch controls power to all outlets Locking Switch Cover Transparent switch cover snaps tight to prevent accidental shutoff PHYSICAL Color Light Gray Material of Construction Metal Power Cord Color Light Gray Mounting Holes or Slots Yes Slot or Hole Mount Measurement (Center to Center) Distance between mounting tabs = 203.20mm; Distance between end tabs = 330.17mm Outlets Measurement (Center to Center) 1.62 in. Receptacle Color Light gray Shipping Dimensions (hvd / in.) 15.50 x 2.40 x 6.50 Shipping Dimensions (hvd / in.) 39.37 x 6.10 x 16.51	Frequency Compatibility	50 / 60 Hz
Circuit Breaker (amps) 15 Overload Protection 15A circuit breaker Transformer Accommodation (3) Yes Outlet Orientation Single row of 6 (right-angle) Right-Angle Outlets Yes USER INTERFACE, ALERTS & CONTROLS Switches Lighted 2 position switch controls power to all outlets Locking Switch Cover Transparent switch cover snaps tight to prevent accidental shutoff PHYSICAL Color Color Light Gray Material of Construction Metal Power Cord Color Light Gray Mounting Holes or Slots Yes Slot or Hole Mount Measurement (Center to Center) Distance between mounting tabs = 203.20mm; Distance between end tabs = 330.17mm Outlets Measurement (Center to Center) 1.62 in. Receptacle Color Light gray Shipping Dimensions (hvd / in.) 15.50 x 2.40 x 6.50 Shipping Dimensions (hvd / rcm) 39.37 x 6.10 x 16.51	Output (Watts)	1800
Overload Protection 15A circuit breaker Transformer Accommodation (3) Yes Outlet Orientation Single row of 6 (right-angle) Right-Angle Outlets Yes USER INTERFACE, ALERTS & CONTROLS Switches Lighted 2 position switch controls power to all outlets Locking Switch Cover Transparent switch cover snaps tight to prevent accidental shutoff PHYSICAL Color Light Gray Material of Construction Metal Power Cord Color Light Gray Housing Color Light Gray Mounting Holes or Slots Yes Slot or Hole Mount Measurement (Center to Center) Distance between mounting tabs = 203.20mm; Distance between end tabs = 330.17mm Outlets Measurement (Center to Center) 1.62 in. Receptacle Color Light gray Shipping Dimensions (hwd / in.) 15.50 x 2.40 x 6.50 Shipping Dimensions (hwd / cm) 39.37 x 6.10 x 16.51	Output Receptacles	(6) 5-15R
Transformer Accommodation (3) Yes Outlet Orientation Single row of 6 (right-angle) Right-Angle Outlets Yes USER INTERFACE, ALERTS & CONTROLS Switches Lighted 2 position switch controls power to all outlets Locking Switch Cover Transparent switch cover snaps tight to prevent accidental shutoff PHYSICAL Color Light Gray Material of Construction Metal Power Cord Color Light Gray Housing Color Light Gray Mounting Holes or Slots Yes Slot or Hole Mount Measurement (Center to Center) Distance between mounting tabs = 203.20mm; Distance between end tabs = 330.17mm Outlets Measurement (Center to Center) 1.62 in. Receptacle Color Light gray Shipping Dimensions (hwd / in.) 15.50 x 2.40 x 6.50 Shipping Dimensions (hwd / cm) 39.37 x 6.10 x 16.51	Circuit Breaker (amps)	15
Outlet Orientation Single row of 6 (right-angle) Right-Angle Outlets Yes USER INTERFACE, ALERTS & CONTROLS Switches Lighted 2 position switch controls power to all outlets Locking Switch Cover Transparent switch cover snaps tight to prevent accidental shutoff PHYSICAL Color Color Light Gray Material of Construction Metal Power Cord Color Light Gray Housing Color Light Gray Mounting Holes or Slots Yes Slot or Hole Mount Measurement (Center to Center) Distance between mounting tabs = 203.20mm; Distance between end tabs = 330.17mm Outlets Measurement (Center to Center) 1.62 in. Receptacle Color Light gray Shipping Dimensions (hwd / in.) 15.50 x 2.40 x 6.50 Shipping Dimensions (hwd / cm) 39.37 x 6.10 x 16.51	Overload Protection	15A circuit breaker
Right-Angle Outlets Yes USER INTERFACE, ALERTS & CONTROLS Switches Lighted 2 position switch controls power to all outlets Locking Switch Cover Transparent switch cover snaps tight to prevent accidental shutoff PHYSICAL Color Light Gray Material of Construction Metal Power Cord Color Light Gray Housing Color Light Gray Mounting Holes or Slots Yes Slot or Hole Mount Measurement (Center to Center) Distance between mounting tabs = 203.20mm; Distance between end tabs = 330.17mm Outlets Measurement (Center to Center) 1.62 in. Receptacle Color Light gray Shipping Dimensions (hwd / in.) 15.50 x 2.40 x 6.50 Shipping Dimensions (hwd / cm) 39.37 x 6.10 x 16.51	Transformer Accommodation	(3) Yes
USER INTERFACE, ALERTS & CONTROLS Switches Lighted 2 position switch controls power to all outlets Locking Switch Cover Transparent switch cover snaps tight to prevent accidental shutoff PHYSICAL Color Light Gray Material of Construction Metal Power Cord Color Light Gray Housing Color Light Gray Mounting Holes or Slots Yes Slot or Hole Mount Measurement (Center) Distance between mounting tabs = 203.20mm; Distance between end tabs = 330.17mm Outlets Measurement (Center to Center) 1.62 in. Receptacle Color Light gray Shipping Dimensions (hwd / in.) 15.50 x 2.40 x 6.50 Shipping Dimensions (hwd / cm) 39.37 x 6.10 x 16.51	Outlet Orientation	Single row of 6 (right-angle)
Switches Lighted 2 position switch controls power to all outlets Locking Switch Cover Transparent switch cover snaps tight to prevent accidental shutoff PHYSICAL Light Gray Color Light Gray Material of Construction Metal Power Cord Color Light Gray Housing Color Light Gray Mounting Holes or Slots Yes Slot or Hole Mount Measurement (Center to Center) Distance between mounting tabs = 203.20mm; Distance between end tabs = 330.17mm Outlets Measurement (Center to Center) 1.62 in. Receptacle Color Light gray Shipping Dimensions (hwd / in.) 15.50 x 2.40 x 6.50 Shipping Dimensions (hwd / cm) 39.37 x 6.10 x 16.51	Right-Angle Outlets	Yes
Locking Switch Cover Transparent switch cover snaps tight to prevent accidental shutoff PHYSICAL Color Light Gray Material of Construction Metal Power Cord Color Light Gray Housing Color Light Gray Mounting Holes or Slots Yes Slot or Hole Mount Measurement (Center to Center) Distance between mounting tabs = 203.20mm; Distance between end tabs = 330.17mm Outlets Measurement (Center to Center) 1.62 in. Receptacle Color Light gray Shipping Dimensions (hwd / in.) 15.50 x 2.40 x 6.50 Shipping Dimensions (hwd / cm) 39.37 x 6.10 x 16.51	USER INTERFACE, ALERTS & CON	TROLS
PHYSICAL Color Light Gray Material of Construction Metal Power Cord Color Light Gray Housing Color Light Gray Mounting Holes or Slots Yes Slot or Hole Mount Measurement (Center to Center) Distance between mounting tabs = 203.20mm; Distance between end tabs = 330.17mm Outlets Measurement (Center to Center) 1.62 in. Receptacle Color Light gray Shipping Dimensions (hwd / in.) 15.50 x 2.40 x 6.50 Shipping Dimensions (hwd / cm) 39.37 x 6.10 x 16.51	Switches	Lighted 2 position switch controls power to all outlets
ColorLight GrayMaterial of ConstructionMetalPower Cord ColorLight GrayHousing ColorLight GrayMounting Holes or SlotsYesSlot or Hole Mount Measurement (Center to Center)Distance between mounting tabs = 203.20mm; Distance between end tabs = 330.17mmOutlets Measurement (Center to Center)1.62 in.Receptacle ColorLight grayShipping Dimensions (hwd / in.)15.50 x 2.40 x 6.50Shipping Dimensions (hwd / cm)39.37 x 6.10 x 16.51	Locking Switch Cover	Transparent switch cover snaps tight to prevent accidental shutoff
Material of Construction Metal Power Cord Color Light Gray Housing Color Light Gray Mounting Holes or Slots Yes Slot or Hole Mount Measurement (Center to Center) Distance between mounting tabs = 203.20mm; Distance between end tabs = 330.17mm Outlets Measurement (Center to Center) 1.62 in. Receptacle Color Light gray Shipping Dimensions (hwd / in.) 15.50 x 2.40 x 6.50 Shipping Dimensions (hwd / cm) 39.37 x 6.10 x 16.51	PHYSICAL	
Power Cord ColorLight GrayHousing ColorLight GrayMounting Holes or SlotsYesSlot or Hole Mount Measurement (Center to Center)Distance between mounting tabs = 203.20mm; Distance between end tabs = 330.17mmOutlets Measurement (Center to Center)1.62 in.Receptacle ColorLight grayShipping Dimensions (hwd / in.)15.50 x 2.40 x 6.50Shipping Dimensions (hwd / cm)39.37 x 6.10 x 16.51	Color	Light Gray
Housing Color Light Gray Mounting Holes or Slots Yes Slot or Hole Mount Measurement (Center to Center) Distance between mounting tabs = 203.20mm; Distance between end tabs = 330.17mm Outlets Measurement (Center to Center) 1.62 in. Receptacle Color Light gray Shipping Dimensions (hwd / in.) 15.50 x 2.40 x 6.50 Shipping Dimensions (hwd / cm) 39.37 x 6.10 x 16.51	Material of Construction	Metal
Mounting Holes or Slots Yes Slot or Hole Mount Measurement (Center to Center) Distance between mounting tabs = 203.20mm; Distance between end tabs = 330.17mm Outlets Measurement (Center to Center) 1.62 in. Receptacle Color Light gray Shipping Dimensions (hwd / in.) 15.50 x 2.40 x 6.50 Shipping Dimensions (hwd / cm) 39.37 x 6.10 x 16.51	Power Cord Color	Light Gray
Slot or Hole Mount Measurement (Center to Center) Distance between mounting tabs = 203.20mm; Distance between end tabs = 330.17mm Outlets Measurement (Center to Center) 1.62 in. Receptacle Color Light gray Shipping Dimensions (hwd / in.) 15.50 x 2.40 x 6.50 Shipping Dimensions (hwd / cm) 39.37 x 6.10 x 16.51	Housing Color	Light Gray
(Center to Center) Distance between mounting tabs = 203.20mm, Distance between end tabs = 330.17mm Outlets Measurement (Center to Center) 1.62 in. Receptacle Color Light gray Shipping Dimensions (hwd / in.) 15.50 x 2.40 x 6.50 Shipping Dimensions (hwd / cm) 39.37 x 6.10 x 16.51	Mounting Holes or Slots	Yes
Center) 1.02 m. Receptacle Color Light gray Shipping Dimensions (hwd / in.) 15.50 x 2.40 x 6.50 Shipping Dimensions (hwd / cm) 39.37 x 6.10 x 16.51		Distance between mounting tabs = 203.20mm; Distance between end tabs = 330.17mm
Shipping Dimensions (hwd / in.) 15.50 x 2.40 x 6.50 Shipping Dimensions (hwd / cm) 39.37 x 6.10 x 16.51	Outlets Measurement (Center to Center)	1.62 in.
Shipping Dimensions (hwd / cm) 39.37 x 6.10 x 16.51	Receptacle Color	Light gray
	Shipping Dimensions (hwd / in.)	15.50 x 2.40 x 6.50
	Shipping Dimensions (hwd / cm)	39.37 x 6.10 x 16.51
Shipping Weight (lbs.) 3.00	Shipping Weight (lbs.)	3.00





1.36		
2.000 x 13.750 x 2.500		
35 x 6.35 x 5.1		
2.8		
1.27		
Includes flanges		
FEATURES & SPECIFICATIONS		
No		
Yes		
cUL Listed; UL 1363; UL Listed		
RoHS		
WARRANTY & SUPPORT		
Lifetime limited warranty		

1000 Eaton Boulevard Cleveland, OH 44122 United States https://tripplite.eaton.com © 2025 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.