

# 3-Outlet Surge Protector with 2 USB Ports, 10 ft. (3.05 m) Cord - 510 Joules, Desk Clamp, White Housing

MODEL NUMBER: TLP310USBCW



Clamps safely to your workstation to protect your electronics against surges and charge your mobile devices.

## Features

**510-Joule Surge Protection for Home or Office Electronics** The 510-joule rating means your computer, printer, scanner, external hard drive and other sensitive electronic components are protected against strong surges and spikes.

This power surge protector with USB ports features full normal mode (H-N) and common mode (N-G/H-G) line surge suppression. It filters out disruptive EMI/RFI line noise that can cause equipment damage or data loss and exceeds IEEE 587 Category A and B surge suppression specifications.

**Charges a Wide Range of Electronic Devices** This 10-ft. (3.05 m) surge protector features two USB ports that produce 3.1A of combined power to charge your mobile devices, including smartphones, tablets and MP3 players. A top storage shelf holds smartphones and other small devices while they're charging.

**Fits Effortlessly Into Your Workstation** This 3-plug surge protector mounts to a clamp that attaches to most desks, tables and flat surfaces, bringing power and device charging to your desktop. Clamps adjusts from .59 to 1.77". The 10-ft. (3.05 m) power cord has a NEMA 5-15P plug and fits through the back of the clamp to reduce cable clutter.

**Lifetime Limited Warranty and Ultimate Lifetime Insurance** This three-outlet surge protector comes with a lifetime limited warranty and is backed by \$20,000 Ultimate Lifetime Insurance for any connected components damaged by a power surge (U.S., Canada and Puerto Rico only).

## Specifications

OVERVIEW	
UPC Code	037332224897
Product Type	Surge Protector

## Highlights

- Clamps firmly to most desks, tables and flat surfaces. Clamp adjusts from .59 to 1.77"
- 3 NEMA 5-15R outlets power most computers and peripherals
- 2 USB ports (3.1A total) for charging mobile devices
- 510 joules of surge suppression
- 10-ft. (3.05 m) power cord reaches distant AC outlets

## Applications

- Supplies power and charging in a limited amount of space, making it perfect for homes and offices, as well as college dorms and hotel rooms
- Safeguards your computer, printer and peripherals from dangerous surges
- Shields TVs, DVD players, video game consoles, streaming media players, sound systems and device chargers from surges
- Charges your equipment while keeping it safe

## Package Includes

- TLP310USBCW Protect It! 3-Outlet Surge Protector
- Desk clamp
- Mounting hardware
- Owner's manual



Powering Business Worldwide

TRIPP LITE  
SERIES

Charging Form Factor	Strip
Device Compatibility	Phone; Tablet; Amazon Kindle
<b>INPUT</b>	
Nominal Input Voltage(s) Supported	120V AC
Recommended Electrical Service	120V
Input Cord Length Details	Strip
Input Cord Gauge (AWG)	14
Voltage Compatibility (VAC)	120
Input Plug Type	NEMA 5-15P
Input Cord Details	SJT
Input Cord Length (ft.)	10
Right-Angle Plug	No
Input Cord Length (m)	3.05
Integrated Cord Clip	No
<b>OUTPUT</b>	
Frequency Compatibility	60 Hz
Output (Watts)	1800
Output Receptacles	(4) 5-15R
Circuit Breaker (amps)	15
Transformer Accommodation	(3) Yes
Right-Angle Outlets	No
<b>USER INTERFACE, ALERTS &amp; CONTROLS</b>	
Diagnostic LED(s)	Yes
Diagnostic LED Details	X1 Green LED - Protected
<b>CHARGING</b>	
Number of Charging Ports	2
Total Charging Watts	15.5
Charging Method	USB
Charging Port Type	USB A (FEMALE)
Charging Ports / Amps	(2) 3.1A
Overcharge Protection	No
<b>SURGE / NOISE SUPPRESSION</b>	
AC Suppression Joule Rating	510



Powering Business Worldwide

TRIPP LITE  
SERIES

AC Suppression Response Time	< 1 ns
Protection Modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression
UL1449 Let Through Rating	1000
EMI / RFI Filtering	Yes
Immunity	Conforms to IEE 587/ANSI C62.41
Automatic Shut-Off	No
<b>DATALINE SURGE SUPPRESSION</b>	
Cable (Coax) Protection	No
Network (Ethernet) Protection	No
Telephone/DSL Protection	No
<b>PHYSICAL</b>	
Material of Construction	Plastic
Power Cord Color	Gray
Mounting Holes or Slots	No
Receptacle Color	White
Shipping Dimensions (hwd / in.)	7.40 x 4.10 x 5.40
Shipping Weight (kg)	1.18
Unit Dimensions (hwd / in.)	1.940 x 1.760 x 5.510
Unit Dimensions (hwd / cm)	4.93 x 4.47 x 14.7
Unit Weight (lbs.)	2.34
Unit Weight (kg)	1.06
<b>FEATURES &amp; SPECIFICATIONS</b>	
Rotatable Outlets	No
Antimicrobial	No
GaN Technology	No
Mounting Accessory Included	Yes
<b>STANDARDS &amp; COMPLIANCE</b>	
Product Certifications	UL 1449; UL 962A
Product Compliance	RoHS
<b>WARRANTY &amp; SUPPORT</b>	
Product Warranty Period (Worldwide)	Lifetime limited warranty
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$20,000 <a class="insuranceLink" href="//triplite.eaton.com/support/insurance-policy">Ultimate Lifetime Insurance</a>



*Powering Business Worldwide*

**TRIPP LITE**  
SERIES

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2025 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.