# Protect It! 230V Surge Protector with 8-Schuko Type F Outlets, German Plug, 1140 Joules, Coax/Network Protection

MODEL NUMBER: **TLP82MASD**



## Highlights

- 8 safety outlets
- 2 m cord
- Network protection
- 1 Line coax protection
- Protected/Grounded LED's
- 1140 joule rating
- Energy saving master/subordinate outlet array

## Package Includes

- TLP82MASD surge suppressor
- 1.8 aerial cable and 2 aerial adapters
- 1.8 m gold coax cable
- 1.8 m network cable
- Instruction manual and warranty information

## Description

Tripp Lite's Protect It!™ TLP82MASD offers economical AC surge suppression for full protection of 220-250V home computers, pritners, scaners, and desk lamps. The TLP82MASD offers 8 Schuko type F outlets and a 2 meter AC line cord. Internal safety covers protect against accidental contact with unused outlets.

## Features

- Protect It!™ TLP82MASD offers economical AC surge suppression
- 1140 joules AC surge suppression shields equipment from surges and line noise
- 8 Shucko outlets protects computers and peripherals
- 2 m cord with German plug
- Lighted ON/OFF switch with circuit breaker
- Network Protection
- Coax Protection
- Aerial Adapters
- Energy saving master/subordinate outlet array
- Internal safety covers protect against accidental contact with unused outlets

# Specifications

| OVERVIEW | |
|---|---|
| UPC Code | 037332145390 |

| INPUT | |
|---|---|
| Nominal Input Voltage(s) Supported | 230V AC |

| | |
|---|---|
| Recommended Electrical Service | 230V (220-250V) |
| Maximum Input Amps | 10 |
| Voltage Compatibility (VAC) | 220-250 |
| Input Plug Type | German |
| Input Cord Length (ft.) | 6 |
| Right-Angle Plug | Yes |
| Input Cord Length (m) | 1.83 |
| Integrated Cord Clip | No |

**OUTPUT**

| | |
|---|---|
| Output (Watts) | 2500 |
| Output Receptacles | (8) Schuko Type F |
| Circuit Breaker (amps) | 10 |
| Transformer Accommodation | (5) Yes |

**USER INTERFACE, ALERTS & CONTROLS**

| | |
|---|---|
| Diagnostic LED(s) | Yes |
| Diagnostic LED Details | Protected/Grounded |

**SURGE / NOISE SUPPRESSION**

| | |
|---|---|
| AC Suppression Joule Rating | 1140 |
| Automatic Shut-Off | No |

**DATALINE SURGE SUPPRESSION**

| | |
|---|---|
| Cable (Coax) Protection | Yes |
| Cable (Coax) Protection Details | 1 line |
| Network (Ethernet) Protection | Yes |
| Telephone/DSL Protection | No |

**PHYSICAL**

| | |
|---|---|
| Color | Black |
| Power Cord Color | Black |
| Housing Color | Black |
| Mounting Holes or Slots | No |
| Receptacle Color | Black |
| Shipping Dimensions (hwd / in.) | 14.80 x 7.48 x 2.17 |
| Shipping Dimensions (hwd / cm) | 37.59 x 19.00 x 5.51 |
| Shipping Weight (lbs.) | 2.30 |

| Shipping Weight (kg) | 1.04 |
|---|---|
| Unit Dimensions (hwd / in.) | 12.440 x 4.610 x 1.933 |
| Unit Dimensions (hwd / cm) | 31.60 x 11.71 x 4.90 |
| Unit Weight (lbs.) | 2.1 |
| Unit Weight (kg) | 0.95 |

| **FEATURES & SPECIFICATIONS** | |
|---|---|
| Rotatable Outlets | No |
| Antimicrobial | No |

| **WARRANTY & SUPPORT** | |
|---|---|
| Product Warranty Period (Worldwide) | Lifetime limited warranty |