



Vividia CX-4010M Joystick Articulating Borescope



The **Vividia CX-4010M Flexible Joystick Articulating Inspection Camera Borescope** has a 4mm (0.16") diameter and 1 meter flexible probe length. The probe is covered by a metal-mesh tube for durability and IP67 waterproofing & dust resistance. It comes with a detachable 4.5" LCD monitor. The CX-4010M has bright LED lights, joystick pivoting and can be used to investigate dark places as a diagnostic inspection camera. The camera head can be steered with the joystick to all directions and all angles. The monitor has a removeable microSD card installed for saving media. One can seamlessly record picture and video directly to the card for transport to an external device. With a waterproof flexible insertion tube and probe camera, the Vividia CX-4010M borescope is suitable for many applications. These include but are not limited to looking into engine cylinders, inside airplane wings, behind instrumental panels and inside brake systems. It is also particularly useful for diesel applications due to its small diameter. The **Vividia CX-4010M** is a fantastic diagnostic inspection camera for auto mechanics and technicians. The CX-4010M is the LCD monitor version of CX-4010i, which does not have a standalone monitor and instead connects to iPhone, iPad & Android devices.



Tech Specs of CX-4010M borescope:

Model:	CX-4010M
Monitor size:	4.5 inch LCD
SD card:	Micro SD, max. 128G
Screen resolution:	800 x 600
Camera head diameter:	4mm / 0.16"
Camera head bending length:	~ 35mm / 1.38"
Camera sensor resolution:	CMOS, 1280x720
Focus range:	10mm / 0.4" to infinity
FOV:	120 degree
LED lights:	6 white LED lights; 4 levels brightness
Probe length:	1m / 3.3 ft.
Probe tube material:	Wear-resistant metal mesh
Articulation type and angles:	Joystick 360 all-around, >180 degree
Waterproof (probe only):	Waterproof IP67
Battery built-in:	Rechargeable lithium, 33500 mAh
Working time:	>3h after full charge
Power charging:	5V/2A, USB-C
Dimension:	195 x 57 x 10 mm
Weight:	0.6 kg / 1.3 lbs
Special features:	Auto off; articulation angle locking

