Free shipping in US mainland for order over \$70*

Tel: 1-864-469-0919

Email: info@oasisscientific.com

Vividia VS-2830PT Pan-Tilt Pipe Inspection Camera

Camera heads:

There are two camera heads included

in the package

Camera head #1, pan-tilt camera

head

Part #: C28PT

Camera diameter 28mm / 1.1"

Camera head length: 290mm / 11.4"

Material: Stainless steel housing Camera resolution: 1280 x 720 Sensor size: CMOS, 1/4 inch

View angle: 90 degree LEDs: Two LED lights

Rotate: Pan 360°; Tilt180°

Waterproof: IP68

Skids (included in package): one

40mm & one 90mm

Built-in 512Hz transmitter: Yes.

512Hz sonde Manual focus: No

Focus range: 20mm to 3000mm

Camera head #2, regular HD camera

head (not a PT camera)

Part #: C23HD

Camera size: ø23mm*135mm

Camera pixels: 1280*720

Sensor size: 1/2.9" SONY CMOS

View angle: 105°

LEDs: 12pcs

Waterproof: IP68



Monitor and control body:

LCD size: 10.1 inch

Screen pixels: 1280*800

Storage medium: 64GB SD card &

USB stick

Video format: AVI Photo format: JPEG Battery: 6000mAh 12V Work time: >4 hours

Digital zoom: 8 levels digital zoom Cable length counter: M/FT switch

and Count reset

Output: HDMI output (HD

interface)

Interface: RCA CVBS input; RCA

video output

Size of the main unit: 505*419*180mm

Weight: 2 kg



Push-rod cable:

Cable reel size: 332*59mm

Cable material: glass fiber cable

Cable length: 30m / 98ft

Cable diameter: 6.3mm, 5-core

coaxial

Cable length counter: Yes