

IP64 MINI & SUPER MINI CORN LAMPS



RETROFIT EXISTING FIXTURES



APPLICATIONS

- Post tops
- Bollards
- Commercial and residential recessed cans
- Institutional and educational facilities
- Tall and wall packs and floods

PRODUCT FEATURES

WATTAGES	15W, 25W
COLOR TEMPS	22K, 30K, 40K, 50K
INPUT VOLTAGE	100-277VAC
EFFICACY	15W: 120 lm/W; 25W: 190 lm/W
BASE TYPE	E26 medium, E39 mogul E39 supported with Adapter-8
AMBIENT TEMPS	-20 to 50C; -4 to 122F
RATED	IP64
LED LIFESPAN	50,000 hours
WARRANTY	5 years
CRI	>80

SPECIFICATIONS

PRODUCT #	WATTAGES	DIMENSIONS (WxL)	LUMENS (+/-10%)	SUGGESTED HID EQUIV.	LISTED
C-E26-15-IP64-50K-MINI	15W	2.52" x 5.91"	2,250	50-75W	ETL
C-E39-15-IP64-50K-MINI	15W	2.52" x 6.30"	2,250	50-75W	N/A
C-E26-25-IP64-50K-S-MINI-HL	25W	2.52" x 5.91"	4,750	100-175W	ETL
C-E39-25-IP64-50K-S-MINI-HL	25W	2.52" x 6.30"	4,750	100-175W	ETL

NOTE: Approved for suitable use in enclosed fixtures for all. Medium base (E26) can be converted to Mogul base (E39) without adding any length by using "Adapter-8". Replaces HID Mini 75-150W. Ballast bypass. Example: C-E26-15-50K-IP64-MINI

PRODUCT BUILDER

ex: C-E26-15-IP64-50K-MINI

TYPE	BASE	WATTAGE	RATED	COLOR TEMP.	PRODUCT
C	-	-	IP64	-	-
	E26 (medium) E39 (mogul)	15W 25W		50K (standard) 40K (standard) 30K (standard) 60K 22K	MINI S-MINI-HL