


Specification Sheet

Part Number: TAG14L-789



Laser printable white polyester has a smooth surface, allowing for the highest resolution and print contrast.

The acrylic-based adhesive bonds to a wide variety of substrates and can withstand high temperatures long term.

Lasertags are not affected by the high heat required in a laser printer.

Laser Tag Label, 1.0 x 0.38", 175 Per Sheet, Polyester, Clear, 5000/pkg

|                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|---------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Article Number      | 594-14789                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Type                | TAG14L                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Color               | White (WH)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Quantity Per        | pack                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Product Description | HellermannTyton white polyester labels are ideal for marking small electrical and electronic components, such as EPROMS', Integrated circuits, as well as the circuit board itself. Printed labels can withstand the soldering process and survive flux removal when the board is washed. HellermannTyton's 789 material is designed for use on flat surfaces and can also be used to identify connectors, buttons and just about anything requiring permanent, durable, high temperature and UV resistant marking. |
| Short Description   | Laser Tag Label, 1.0 x 0.38", 175 Per Sheet, Polyester, Clear, 5000/pkg                                                                                                                                                                                                                                                                                                                                                                                                                                             |

|                                |                                   |
|--------------------------------|-----------------------------------|
| Global Part Name               | TAG14L-789-WH                     |
| Width W (Imperial)             | 1.0                               |
| Width W (Metric)               | 25.4                              |
| Thickness T (Metric)           | 64.0                              |
| Height H (Imperial)            | 0.375                             |
| Height H (Metric)              | 9.52                              |
| Material                       | Type 789, Polyester (789)         |
| Material Shortcut              | 789                               |
| Adhesive                       | Acrylic                           |
| Halogen Free                   | Yes                               |
| UV Resistant (Yes/No)          | No                                |
| Use Conditions                 | For Indoor Use Only               |
| Adhesive Operating Temperature | -40°F to +302°F (-40°C to +150°C) |
| Operating Temperature          | -40°F to +300°F (-40°C to +149°C) |
| Reach Compliant (Article 33)   | Yes                               |

|                             |            |
|-----------------------------|------------|
| ROHS Compliant              | Yes        |
| Package Quantity (Imperial) | 5000       |
| Package Quantity (Metric)   | 5000       |
| Customs Number              | 3919905060 |
| Labels per Column           | 25         |
| Labels per Row              | 7          |

7930 N. Faulkner Road, Milwaukee, WI 53224  
Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2025 HellermannTyton. All Rights Reserved.  
[Contact Us](#)   [RoHS/WEEE Compliance](#)   [Disclaimer](#)   [Terms and Conditions](#)