

Specification Sheet

Part Number: 596-00748

Made with UV stable inks and materials for durability and weather resistance.

The labels are supplied with aggressive adhesive to ensure long life.

ENCLOSURE CONTAINS
CONDUCTORS FROM
MULTIPLE PV SOURCES

Solar Installation labels meet NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.

Solar Label, Enclosure Contains...PV Sources, 2020 Code, 4.0" x 2.0", VL, Red, 50/roll

Article Number	596-00748
Type	ECCMPV
Color	Red (RD)
Quantity Per	reel
Product Description	Many times common solar label designs are specified even though they might not be required by code. HellermannTyton offers a selection of some of the most commonly requested labels for use on solar installations.
Short Description	Solar Label, Enclosure Contains...PV Sources, 2020 Code, 4.0" x 2.0", VL, Red, 50/roll
Global Part Name	ECCMPV-V-RD

Width W (Imperial)	4.0
Width W (Metric)	101.6
Thickness T (Imperial)	0.0025
Thickness T (Metric)	64.0
Height H (Imperial)	2.0
Height H (Metric)	50.8
Width of Liner (Metric)	104.64
Width of Liner (Imperial)	4.12
Material	Vinyl (V)
Material Shortcut	V
Adhesive	Acrylic
Halogen Free	No
UV Resistant (Yes/No)	No
Use Conditions	For Indoor and Outdoor Use
Adhesive Operating Temperature	-40°F to +174°F (-40°C to +79°C)

Operating Temperature	-40°F to +174°F (-40°C to +79°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Certification/Specification	NEC2020 NEC2014 NEC2017 NEC2011
Warranty (US)	Yes
UL Recognized (US)	Yes
Package Quantity (Imperial)	50
Package Quantity (Metric)	50
Customs Number	3919102055
Labels per Column	1
Labels per Row	1

7930 N. Faulkner Road, Milwaukee, WI 53224
Phone: (800) 537-1512 | Email: corp@htamericas.com