

Specification Sheet

Part Number: 596-00757

Made with UV stable inks and materials for durability and weather resistance.

The labels are supplied with aggressive adhesive to ensure long life.

DC DISCONNECT

Solar Installation labels meet NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.

Solar Label, DC DISCONNECT, 4.0" x 1.0", VL, Red, 50/roll

Article Number 596-00757

Type DCD

Color Red (RD)

Quantity Per reel

Product Description Many times common solar label designs are specified even though they might not be required by code. HellermannTyton offers a selection of some of the most commonly requested labels for use on solar installations.

Short Description Solar Label, DC DISCONNECT, 4.0" x 1.0", VL, Red, 50/roll

Global Part Name DCD-V-RD

Width W (Imperial)	4.0
Width W (Metric)	101.6
Height H (Imperial)	1.0
Height H (Metric)	25.40
Material	Vinyl (V)
Material Shortcut	V
Adhesive	Acrylic
Halogen Free	No
UV Resistant (Yes/No)	No
Use Conditions	For Indoor and Outdoor Use
Adhesive Operating Temperature	-40°F to +174°F (-40°C to +79°C)
Operating Temperature	-40°F to +174°F (-40°C to +79°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Certification/Specification	NEC2011 NEC2014 NEC2017 NEC2020

Warranty (US) Yes

UL Recognized (US) Yes

Package Quantity (Imperial) 50

Package Quantity (Metric) 50

Customs Number 3919102055

Labels per Column 1

Labels per Row 1

7930 N. Faulkner Road, Milwaukee, WI 53224
Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2025 HellermannTyton. All Rights Reserved.
[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)