

Specification Sheet

Part Number: TAG11T4-822



White polyester is glossy, allowing for the highest resolution and print contrast.

The acrylic-based adhesive bonds to a wide variety of substrates and can withstand high temperatures long term.

Article Number	596-11822
Type	TAG11T4
Color	White (WH)
Quantity Per	reel
Product Description	HellermannTyton white polyester labels are ideal for marking small electrical and electronic components, such as EPROMS', Integrated circuits, as well as the circuit board itself. Printed labels can withstand the soldering process and survive flux removal when the board is washed. HellermannTyton's 822 material is designed for use on flat surfaces and can also be used to identify connectors, buttons and just about anything requiring permanent, durable, high temperature and UV resistant marking.
Short Description	Thermal Transfer Adhesive Labels, 0.65 x 0.2", 4 Across, Polyester, White, 5000/roll

Global Part Name	TAG11T4-822-WH
Width W (Imperial)	0.65
Width W (Metric)	16.5
Thickness T (Metric)	64.0
Height H (Imperial)	0.2
Height H (Metric)	5.08
Width of Liner (Metric)	66.04
Width of Liner (Imperial)	2.60
Material	Type 822, Polyester (822)
Material Shortcut	822
Adhesive	Acrylic
Halogen Free	Yes
UV Resistant (Yes/No)	No
Adhesive Operating Temperature	-40°F to +302°F (-40°C to +150°C)
Operating Temperature	-40°F to +302°F (-40°C to +150°C)

Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Certification/Specification	UL-Recognized
UL Recognized (US)	Yes
UL Recognized (US and Canada)	Yes

Package Quantity (Imperial)	5005
Package Quantity (Metric)	5000
Customs Number	3919102055
Labels per Column	1
Labels per Row	4

7930 N. Faulkner Road, Milwaukee, WI 53224
 Phone: (800) 537-1512 | Email: corp@htamericas.com