





ordering	

Order No. Part designation Version

EAN Qty.

Input Sensor

Temperature input range Number of inputs

Output

Output current Load resistance, current Influence of line resistance Function 8473020000 MCZ PT100/3 CLP 0...300C Signal converter/disconnector, 4...20 mA (current loop) , Tension clamp connection 4032248058297 10 pc(s).

PT100/2-/3-conductor (to IEC 751) 0...300 °C 1

4...20 mA (current loop) ≤ 600Ω Max. 0.006 K/Ω 3-conductor connection





Yes

1

10 ms

PT100

TS 35

Max. ± 250 ppm/K

Without isolation

0 °C...+50 °C -20 °C...+85 °C

Typical 0.2%, max. 0.5% of FSR

PT100/4...20 mA (current loop)

Max. 30 V/ min. 9 V + (20 mA x RL)

EN 50178, EN 60751, IEC751

SP c Wus

Tension clamp connection

пг		

Accuracy Linearization Step response time Temperature coefficient Number of outputs

General data

Function Input/Output Galvanic isolation Type of connection Mounting rail Voltage supply Ambient temperature (operational) Storage temperature

Insulation coordination

Standards EMC standards

Dimensions

Clamping range, max.1.5 mm²Clamping range, min.0.5 mm²Clamping range, nom.1.5 mm²Length91 mmHeight63.2 mmWidth6 mm

EMVG, EN 61000-6

Approvals

Approvals institutes

Classifications

eClass 4.1 eClass 5.0 eClass 5.1

Similar products

8425720000	MCZ PT100/3 CLP 0100C	Signal converter/disconnector, 420 mA (current loop) , Tension clamp connection
8483680000	MCZ PT100/3 CLP 0120C	Signal converter/disconnector, 420 mA (current loop) , Tension clamp connection
8604420000	MCZ PT100/3 CLP 0150C	Signal converter/disconnector, 420 mA (current loop), Tension clamp connection

27-20-02-06

27-20-02-06

27-20-02-06



8473010000	MCZ PT100/3 CLP 0200C	Signal converter/disconnector, 420 mA (current loop) , Tension clamp connection
8473000000	MCZ PT100/3 CLP -50C+150C	Signal converter/disconnector, 420 mA (current loop) , Tension clamp connection
8604430000	MCZ PT100/3 CLP -40C100C	Signal converter/disconnector, 420 mA (current loop) , Tension clamp connection

