

Product Search Data Sheet

NXFT15XH103FEAB030

In Production Recommended RoHS REACH

Appearance & Shape



Applications

Limited Usage	Consumer Grade
Other Usage	1. Temperature compensation for transistor, IC and crystal oscillator in mobile communications 2. Temperature sensor for rechargeable batteries 3. Temperature compensation of LCD 4. Temperature compensation in general use of electric circuits

Note: This datasheet may be out of date. Please download the latest datasheet of NXFT15XH103FEAB030 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=NXFT15XH103FEAB030

Packaging Information

Packaging	Specifications	Standard Packing Quantity
В	Bulk(Bag)	1000



 High accuracy and high sensibility temperature sensing is available by the small size and high accuracy NTC Thermistor.
Narrow space temperature sensing is available by the small sensing head and the thin lead wire.

3. You can choose the optimum length according to the design layout.

4. This product is compatible with our 0402 (EIA) size chip Thermistor.

5. Excellent long time aging stability

6. This is halogen free product (CI= max.900ppm、

Br=max.900ppm and CI+Br=max.1500ppm).

7. Lead is not contained in the product.

8. NXF series are recognized by UL/cUL (UL1434, File No.E137188).

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





NXFT15XH103FEAB030

Note: This datasheet may be out of date. Please download the latest datasheet of NXFT15XH103FEAB030 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=NXFT15XH103FEAB030

Specifications

Resistance (25°C)	10kΩ
Resistance Value Tolerance (at 25°C)	±1%
B-Constant (25/50°C)	3380K
B-Constant (25/50°C) Tolerance	±1%
B-Constant(25/80°C) (Reference Value)	3428K
B-Constant(25/85°C) (Reference Value)	3434K
B-Constant(25/100°C) (Reference Value)	3455K
Maximum Operating Current (25°C)	0.077mA
Rated Electric Power (25°C)	3.0mW
Typical Dissipation Constant (25°C)	0.6mW/°C
Thermal Time Constant	3s
Operating Temperature Range	-40°C to 125°C
Lead Shape	Lead Wire type
Size Code (in mm)	030 = 30mm
Size Code (in inch)	030 = 30mm
Shape	Lead
Mass	0.032g

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





Product Search Data Sheet

Note: This datasheet may be out of date. Please download the latest datasheet of NXFT15XH103FEAB030 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=NXFT15XH103FEAB030

NXFT15XH103FEAB030



Product Data



Resistance-Temperature Characteristics

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

