SIEMENS

Data sheet

6GK5721-1FC00-0AB0

product type designation



IWLAN client, SCALANCE W721-1, RJ45, 1 radio, 1 R-SMA antenna port, IEEE 802.11a/b/g/h/n, 2.4/5 GHz, gross data rate 150 Mbps, 1x RJ45 max. 100 Mbps, 24 V DC, joint block, IP20, 0... +55 °C, WPA2/802.11i/e, observe national approvals! CERT ID: ELN-W1-RJ-E1, FCC ID: LYHELN1V1, scope of delivery: manuals on CD-ROM, German/English, 1x joint block; only for operation in the USA.

transfer rate	
transfer rate	
with WLAN / maximum	150 Mbit/s
 for Industrial Ethernet 	10, 100 Mbit/s
transfer rate / for Industrial Ethernet	
• minimum	10 Mbit/s
● maximum	100 Mbit/s
interfaces	
number of electrical connections	
 for network components or terminal equipment 	1
 for power supply 	1
 for redundant voltage supply 	0
type of electrical connection	
 for network components or terminal equipment 	RJ45 socket
 for power supply 	3-pole screw terminal
design of the removable storage	
• C-PLUG	No
• KEY-PLUG	No
memory	
design of the removable storage	
• C-PLUG	No
• KEY-PLUG	No
interfaces / wireless	
number of radio cards / permanently installed	1
number of electrical connections / for external antenna(s)	1
type of electrical connection / for external antenna(s)	R-SMA (socket)
product feature / external antenna can be mounted directly on device	Yes
supply voltage, current consumption, power loss	
type of voltage / of the supply voltage	DC
consumed current	
• at DC / at 24 V / typical	0.15 A
power loss [W]	
• at DC / at 24 V / typical	3.6 W
supply voltage / 1	
from terminal block	19.2 V
supply voltage / 2	
from terminal block	28.8 V
ambient conditions	

W721-1 RJ45 (USA)

ambient temperature	
 during operation 	0 55 °C
 during storage 	-40 +85 °C
during transport	-40 +85 °C
relative humidity / at 25 °C / without condensation / during operation / maximum	95 %
ambient condition / for operation	When used under hazardous conditions (Zone 2), the SCALANCE W761-1 RJ45 or W72x-1 RJ45 product must be installed in an enclosure. To comply with EN 50021, this enclosure must meet the requirements of at least IP 54 in compliance with EN 60529.
protection class IP	IP20
design, dimensions and weights	
width	50 mm
height	114 mm
depth	74 mm
width / of the enclosure / without antenna	50 mm
height / of the enclosure / without antenna	114 mm
depth / of the enclosure / without antenna	74 mm
net weight	0.13 kg
fastening method	
S7-300 rail mounting	No
S7-1500 rail mounting	No
37-1500 rail mounting 35 mm top hat DIN rail mounting	Yes
· · ·	
wall mounting	No
radio frequencies	
operating frequency	
 for WLAN in 2.4 GHz frequency band 	2.41 2.48 GHz; depending on the country approvals
 for WLAN in 5 GHz frequency band 	4.9 5.8 GHz; depending on the country approvals
product features, product functions, product components / gen	eral
product function / Access Point Mode	No
product function / client Mode	Yes
product function	
iPCF client	No
iPCF-MC client	No
product function / iREF	No
product function / iPRP	No
product functions / management, configuration, engineering	
number of manageable IP addresses / in client	4
product function	
• CLI	Yes
 web-based management 	Yes
MIB support	Yes
TRAPs via email	Yes
 configuration with STEP 7 	Yes
 configuration with STEP 7 in the TIA Portal 	Yes
• WDS	No
protocol / is supported	
Address Resolution Protocol (ARP)	Yes
• ICMP	Yes
• Telnet	Yes
• HTTP	Yes
• HTTPS	Yes
• TFTP	Yes
• DCP	Yes
LLDP	No
identification & maintenance function	
I&M0 - device-specific information	Yes
	Yes
I&M1 - higher level designation/location designation product functions / diagnostics	
product functions / diagnostics	
product function	
PROFINET IO diagnosis	No
link check	No

connection monitoring IP-Alive	No
• SysLog	Yes
protocol / is supported	
• SNMP v1	Yes
• SNMP v2	Yes
• SNMP v3	Yes
product functions / VLAN	
product function	
function VLAN with IWLAN	No
product functions / DHCP	
product function	
DHCP client	Yes
DHCP server	Yes
DHCP Option 82	Yes
product functions / redundancy	
protocol / is supported	
STP/RSTP	Yes
• MSTP	Yes
• RSTP	Yes
product functions / security	
product function	
ACL - MAC-based	Yes
 management security, ACL-IP based 	Yes
 IEEE 802.1x (radius) 	Yes
• NAT/NAPT	Yes
 access protection according to IEEE802.11i 	Yes
• WPA/WPA2	Yes
• TKIP/AES	Yes
protocol / is supported	
• SSH	Yes
RADIUS	Yes
product functions / time	
protocol / is supported	
• NTP	Yes
• SNTP	Yes
 SIMATIC time synchronization (SIMATIC Time) 	Yes
standards, specifications, approvals	
standard	
• for FM	FM 3611: Class I, Division 2, Groups A,B,C,D, T4 / Class 1, Zone 2, Group IIC, T4, FM16US0205X
certificate of suitability	
EC Declaration of Conformity	Yes
CE marking	Yes
• C-Tick	Yes
• E1 approval	No
 railway application in accordance with EN 50155 	No
NEMA TS2	No
• IEC 61375	No
• IEC 61850-3	No
• NEMA4X	No
 Power-over-Ethernet according IEEE802.3at for type 1 and IEEE802.3af 	No
Power-over-Ethernet according to IEEE802.3at for type 2	No
standard for wireless communication	
• IEEE 802.11a	Yes
• IEEE 802.11b	Yes
• IEEE 802.11e	Yes
• IEEE 802.11g	Yes
• IEEE 802.11h	Yes
• IEEE 802.11i	Yes
• IEEE 802.11n	Yes

wireless approval	You will find the current list of countries at: www.siemens.de/funkzulassungen
standards, specifications, approvals / marine classification	
Marine classification association	
 American Bureau of Shipping Europe Ltd. (ABS) 	No
 French marine classification society (BV) 	No
DNV GL	No
 Korean Register of Shipping (KRS) 	No
 Lloyds Register of Shipping (LRS) 	No
 Nippon Kaiji Kyokai (NK) 	No
 Polski Rejestr Statkow (PRS) 	No
 Royal Institution of Naval Architects (RINA) 	No
tandards, specifications, approvals / hazardous environments	
standard / for hazardous zone	EN 60079-15:2005, EN 60079-0:2006, II 3 G Ex nA II T4 KEMA 07 ATEX 0145X
• from CSA and UL	ANSI/ISA 12.12.01-2013, CAN/CSA C22.2 No.213-M1987, Cl. 1, div. 2, GP. A, B, C, D, T4 / Cl. 1, Zone 2, GP IIC E240480
certificate of suitability / CCC / for hazardous zone according to GB standard	Yes
● as marking	Ex nA IIC T4 Gc
ccessories	
accessories	24 V DC screw terminal included in scope of delivery
urther information / internet links	
internet link	
 to website: TIA Selection Tool 	http://www.siemens.com/tia-selection-tool
 to web page: selection aid TIA Selection Tool 	http://www.siemens.com/tia-selection-tool
• to the website: IWLAN	http://www.siemens.com/iwlan
 to website: Industry Mall 	https://mall.industry.siemens.com
 to website: Information and Download Center 	http://www.siemens.com/industry/infocenter
 to website: Image database 	http://automation.siemens.com/bilddb
 to website: CAx-Download-Manager 	http://www.siemens.com/cax
 to website: Industry Online Support 	https://support.industry.siemens.com
ecurity information	
security information	Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)

last modified:

5/27/2023 🖸