


2.45 GHz / 5.5 GHz / 6.5 GHz PCB Antenna (ISM, IoT, Bluetooth, WLAN, Wi-Fi 5/6E)



#### General information

This small antenna is intended to be soldered to the main PCB of the mobile devices, routers or gateways. On request, the antenna geometry can be optimized for customer's housing design and material properties.

#### Typical applications

ISM, IoT, RFID, Bluetooth, WLAN, Wi-Fi 5/6E, ISM5800

#### Electrical data

Antenna type	Embedded / internal antenna soldered on the main PCB		
Frequency band	ISM2400, Wi-Fi 2.45 / 5.5 / 6.5 GHz, ISM5800		
Frequency range [MHz]	2400...2500	5150...5850	5925...7125 MHz
Return loss [dB] <sup>1)</sup>	-12	-8	-10
Peak gain [dBi]	2.3	3.6	2.1
Radiation efficiency [%]	74	67	56
Nominal input impedance [Ohm]	50		
Polarization	linear		
Radiation pattern	omnidirectional		
Maximum input power [W]	5		

#### Mechanical data

Antenna PCB dimensions [mm]	25 x 12.5 x 0.8
PCB material	FR4
Weight [g]	0.45

#### Environmental data

Operating temperature [°C]	-40...+85
Storage temperature [°C]	-40...+85
Ambient relative humidity [%]	0...95
RoHS / REACH compliant	yes / yes

#### Additional information

All electrical data have been obtained in free space on the reference board (not included) with the following dimensions: 50mm x 35mm x 0.8mm. Please note that the performance in the lower frequency bands is dependent on the ground plane length and may degrade in case of reducing the board size.


Other mechanical designs, materials or frequency bands are possible on request.

Further customization, electromagnetic simulations and measurements can be offered on request.


*All information (including technical data and pictures) presented in this document is typical and subject to change without notice. Sevskiy is a registered trade mark of Sevskiy GmbH. Copyright © 2009 - 2023 Sevskiy GmbH. All rights reserved. No warranties.*

2.45 GHz / 5.5 GHz / 6.5 GHz PCB Antenna (ISM, IoT, Bluetooth, WLAN, Wi-Fi 5/6E)

Measured input impedance matching



Coordinate system




Phi=0°, plane XZ, green curve  
Phi=90°, plane YZ, red curve  
Theta=90°, plane XY, blue curve


All information (including technical data and pictures) presented in this document is typical and subject to change without notice. Sevskiy is a registered trade mark of Sevskiy GmbH. Copyright © 2009 - 2023 Sevskiy GmbH. All rights reserved. No warranties.

2.45 GHz / 5.5 GHz / 6.5 GHz PCB Antenna (ISM, IoT, Bluetooth, WLAN, Wi-Fi 5/6E)


Radiation pattern (total realized gain, dBi)




2450 MHz



5500 MHz



5925 MHz




7125 MHz

All information (including technical data and pictures) presented in this document is typical and subject to change without notice. Sevskiy is a registered trade mark of Sevskiy GmbH. Copyright © 2009 - 2023 Sevskiy GmbH. All rights reserved. No warranties.


**2.45 GHz / 5.5 GHz / 6.5 GHz PCB Antenna (ISM, IoT, Bluetooth, WLAN, Wi-Fi 5/6E)**

**Product dimensions and recommended layout**



Top layer

Bottom layer



Copper




Free solder mask area

Unit: mm

All information (including technical data and pictures) presented in this document is typical and subject to change without notice. Sevskiy is a registered trade mark of Sevskiy GmbH. Copyright © 2009 - 2023 Sevskiy GmbH. All rights reserved. No warranties.

2.45 GHz / 5.5 GHz / 6.5 GHz PCB Antenna (ISM, IoT, Bluetooth, WLAN, Wi-Fi 5/6E)

Antenna placement



 Copper

 Copper keep-out area through the all PCB layers

Notes:

1. Mechanical mounting pads (without GND connection)
2. Reference board size: 50x35mm
3. Antenna must be mounted on the PCB board edge
4. The feedline should be placed as close as possible to the PCB corner

All information (including technical data and pictures) presented in this document is typical and subject to change without notice. Sevskiy is a registered trade mark of Sevskiy GmbH. Copyright © 2009 - 2023 Sevskiy GmbH. All rights reserved. No warranties.