May/2006 Ver.3.0 TDK Corporation Page 1 of 4

### LTCC CHIP ANTENNA FOR UWB

## SAMPLE P/N: **ANT1085-4R1-01A-ES4.5**

## [MECHANICAL DIMENSIONS]



# [ELECTRICAL CHARACTERISTICS]

PARAMETER	VALUE	UNIT
Operation Frequency	3.1 – 5.2	GHz
Polarization	Linear (Mixed)	NONE
Antenna Gain	2.0 (typ.)	dBi
Impedance	50	ohm
VSWR	3 (Max)	NONE

Operating temperature	-30	+85	°C
Storage temperature	-40	+85	°C

May/2006 Ver.3.0 TDK Corporation Page 2 of 4

#### [Recommended PCB Pattern] 7.25 3,25 3,25 2.10 t ø1.15 Antenna 1.30 **PCB** Outline placement guide -0.500.503.70 -1.001.00 0.71 1.25 Top Side Copper Ø0.60 Ø1.00 Via connects GND to GND Layer GND Layer 50 $\Omega$ Feed [Unit: mm]

Note 1: No ground should be placed on any layer under the antenna. Note 2: The antenna should be positioned close to the edge of the PCB.



Note: Tested antenna has been soldered on 24X43mm<sup>2</sup> PCB.

May/2006 Ver.3.0 TDK Corporation Page 3 of 4

# [RADIATION PATTERN]

- Item: ANT1085 4R1 01A
- Simulated results in advance of measurements



May/2006 Ver.3.0 TDK Corporation Page 4 of 4

