

OMNIDIRECTIONAL FIBERGLASS ANTENNAS

FG8246 FG8243 FG8240 FG9020



FIBERGLASS BASE STATION 8 DBI GAIN ANTENNAS PROVIDE SUPERIOR TELECOM CELLULAR PERFORMANCE

Laird's fiberglass base station antennas are collinear designs enclosed in a high-density fiberglass which is covered with a protective ultraviolet inhibiting coating.

The radiating elements are made from high-efficiency copper and are carefully phased to provide maximum gain in the horizontal plane. The mounting sleeves are tuned to eliminate RF currents from the transmission line, resulting in a cold sleeve allowing great freedom in mounting. This high quality and well-focused beam provides the highest gain and best efficiency.

FEATURES AND BENEFITS:

- Every fiberglass base antenna is tested on a network analyzer before shipping to assure the best performance
- Special UV treated to stand up to the sun
- Durable gold anodized sleeve and cap with N female connector
- Custom tuning available
- FedEx / UPS Shippable

APPLICATIONS:

- Omnidirectional outdoor antenna applications used by private organizations and government agencies around the globe
- Typical applications include land base and marine radio and data transmission for public safety agencies, commercial organizations, and the military

Part	FG8246	FG8243	FG8240	FG9020
Frequency Range	824-896 MHz	824-896 MHz	824-896 MHz	902-928 MHz
VSWR	2.0:1	2.0:1	2.0:1	2.0:1
Nominal Gain	6 dBd	4.5 dBi	0 dBi	0 dBi
Maximum Power	100 W	100 W	100 W	100 W
Nominal Impedance	50 Ω	50 Ω	50 Ω	50 Ω
Polarization	Vertical	Vertical	Vertical	Vertical
Pattern	Omnidirectional	Omnidirectional	Omnidirectional	Omnidirectional
Half-Power Beamwidth (Elevation° x Azimuth°)	30° x 360°	60° x 360°	110° x 360°	110° x 360°
Coaxial Cable Length and Type	None	None	None	None
Termination	N Female Connector	N Female Connector	N Female Connector	N Female Connector
Lightning Protection (Sold Separately)	Lightning Arrestor LABH350NN	Lightning Arrestor LABH350NN	Lightning Arrestor LABH350NN	Lightning Arrestor LABH350NN
Height	61″	23-1/8″	13-3/8″	13-3/8″
Diameter	1.310″	1.310″	1.310″	1.310″
Weight	0.5 lbs	1.5 lbs	0.65 lbs	0.65 lbs
Rated Wind Velocity	125 mph (210 kph)	125 mph (210 kph)	125 mph (210 kph)	125 mph (210 kph)
Rated Wind Velocity (with 0.5" radial ice)	85 mph (137 kph)	85 mph (137 kph)	85 mph (137 kph)	85 mph (137 kph)
Optional Mounting Kit (Sold Separately)	FM2	FM2	FM2SP	FM2SP
Wind Resistance	0.5549 sq ft	0.2161 sq ft	0.1217 sq ft	0.1217 sq ft

ANT-DS-FG8246 0114

Any information furnished by Laird Technologies, Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird Technologies materials rests with the end user, since Laird Technologies and its agents cannot be aware of all notential uses. Laird Technologies materials are subject to reliable for includental or consequential amages of any kind. All Laird Technologies shall not be laible for includental or consequential damages of any kind. All Laird Technologies reliable shall not be laible for includental or consequential damages of any kind. All Laird Technologies is hall not be laible for includental or consequential damages of any kind. All Laird Technologies is full not be laible for include material cancels. Laird, Laird Technologies Terms and Conditions of sale in effect from time to time, a covy of which will be furnished upon request. @ Coynight 2009 Laird Technologies, the Laird Technologies to Laird. Laird Technologies to Laird Technologies to Log, and other marks are trade marks of registred trade marks of Laird Technologies to cover or service names may be the property of third parties. Nothing herein provides a license under any Laird Technologies or any third party intellectual property rights.

Americas: +1.847 839.6907 IAS-AmericasEastSales@lairdtech.com

Europe: +1.32.80.7866.12 IAS-EUSales@lairdtech.com

Asia: +1.65.6.243.8022 IAS-AsiaSales@lairdtech.com

www.lairdtech.com



Elevation Pattern (Y, Z, or H-plane)







Elevation Pattern (Y, Z, or H-plane)



