

## FM51RD1032 DATA SHEET

## 2 dBi MultiBand Rubber Duck Portable Antenna 617-5850 MHz SMA Connector

The 5G Fairview Microwave FM51RD1032 Rubber Duck Antenna is a high performance omnidirectional "rubber-duck" antenna. Designed for 617 MHz to 5800 MHz bands, it is in stock and can ship same day. It features a tilt-and-swivel SMA-Plug (male) connector, allowing them to be used at a right angle, vertically or any angle in-between. It is a coaxial sleeve design with an omni-directional pattern. The FM51RD1032 is ideally suited 4G, 5G, LTE, CBRS, UNII bands.

The Fairview Microwave high performance rubber-duck FM51RD1032 is a flexible antenna providing broad coverage and 1-4 dBi gain. This SMA male rubber duck is suitable for commercial radios in public and private 5G and Cellular networks that are equipped with SMA female connectors. Fairview Microwave's FM51RD1032 from Fairview Microwave supports 600, 700, 800, 850, 900, 1800, 2100, 2400, 2600, 3500, 5800 MHz bands.

This 5G 617 MHz to 5850 MHz rubber duck antenna with a SMA male connector just like the other RF components from Fairview Microwave is in stock and ships the same day. Contact our knowledgeable and friendly technical support and sales staff for your answers on any Fairview Microwave products.

#### Configuration

Design Gain Polarization Connector Type Portable 1 to 2 dBi Vertical SMA Male

#### **Electrical Specifications**

Min	Тур	Max	Units
617		5,850	MHz
		3.5:1	
	50		Ohms
1	2		dBi
		617	617 5,850 3.5:1

### **Specifications by Frequency**

Description	Band 1	Band 2	Band 3	Band 4	Band 5	Units
Range	0.617-0.96	1.427-2.7	3.3-5.85			GHz
Gain	1	2	4			dBi
VSWR	3:1	3.5:1	3.5:1			

**ABS** 

#### **Mechanical Specifications**

Radome Material

 Size

 Length
 0.79 in [20.07 mm]

 Width
 0.79 in [20.07 mm]

 Height
 5.33 in [135.38 mm]

 Weight
 0.022 lbs [9.98 g]



#### **Features:**

- 0 to 4 dBi Gain
- Tilt and Swivel Design
- SMA Male Connector
- Blade Design

## **Applications:**

- Infotainment Systems, Routers, WiFi Hotspots, HD Video Transmission, Gateways, Dash Cameras, Public Transportation
- Connected Cars or Self-Driving Cars, Fleet Management, Logistics
- 4G & 5G Networks
- 600, 700, 800, 850, 900, 1800, 1900, 2100, 2600, 3500, 5800 MHz Bands
- IoT, Cellular, Zigbee, Z-Wave, Bluetooth, CBRS, WiFi, C-Band, UNII

Fairview Microwave 301 Leora Ln., Suite 100 Lewisville, TX 75056 Tel: 1-800-715-4396 / (972) 649-6678

Fax: (972) 649-6689 www.fairviewmicrowave.com sales@fairviewmicrowave.com





# **Environmental Specifications Temperature**

Operating Range -20 to +65 deg C Storage Range -20 to +65 deg C

**Compliance Certifications** (see product page for current document)

#### **Plotted and Other Data**

Notes:

2 dBi MultiBand Rubber Duck Portable Antenna 617-5850 MHz SMA Connector from Fairview Microwave is in-stock and available to ship same-day. All of our RF/microwave products are available off-the-shelf from our ISO 9001:2008 certified facilities in Lewisville, Texas. Fairview Microwave is RF on-demand.

For additional information on this product, please click the following link: 2 dBi MultiBand Rubber Duck Portable Antenna 617-5850 MHz SMA Connector FM51RD1032

URL: https://www.fairviewmicrowave.com/multi-antenna-617-mhz-5.85-ghz-2-dbi-gain-sma-fm51rd1032-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Fairview Microwave reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Fairview Microwave does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Fairview Microwave does not assume any liability arising out of the use of any part or documentation.

301 Leora Ln., Suite 100, Lewisville, TX 75056 | Tel: 1-800-715-4396 / (972) 649-6678 / Fax: (972) 649-6689

Copyright © 2020

REV 1.0 Page 2 of 3





