

FM51YA1019 DATA SHEET

880 MHz to 960 MHz, Heavy-Duty Yagi Antenna, 7dBi, N-female

The Fairview Microwave 880 MHzto 960 MHz FM51YA1019 Yagi Antenna ships the same day and is designed for the most rugged conditions. This 900 MHz antenna provides 7 dBi of gain and adjustable polarization. Equipped with an N-Female connector, coaxial connections to a radio are simple and easy. The FM51YA1019 is ideally suited for 900 MHz ISM bands. This 7 dBi antenna supports Land Mobile Radio for land transportation, utility, manufacturing, and petrochemical companies (oil and gas).

Measuring 13.4 inches long, the N-female FM51YA1019 from Fairview Microwave is manufactured using robust 5/16" aircraft quality aluminum elements. The FM51YA1019 elements are completely welded to a 1" boom and painted black. This ensures performance and survivability in the toughest environments.

880 MHz to 960 MHz Yagi antennas from Fairview Microwave are high-quality components backed by expert technical support and sales personnel. Like the other RF components at Fairview Microwave, the 7 dBi FM51YA1019 is in stock and ready to ship the same day.

Configuration

Design	Yagi
Gain	7 to 7 dBi
Polarization	Linear
Cable Type	LMR400
Cable Length	36 in [914.4 mm]
Connector Type	N Female
Number of Ports	1

Electrical Specifications

Description	Min	Тур	Max	Units
Frequency Range	880		960	MHz
Input VSWR		1.3:1	1.5:1	
Impedance		50		Ohms
Gain		7		dBi
Input Power			150	Watts

Specifications by Frequency

Description	Band 1	Band 2	Band 3	Band 4	Band 5	Units
Range	0.88-0.928	0.928-0.96				GHz
Gain	7	7.5				dBi
Horiz. Beam Width	100	95				Degrees
Vert. Beam Width	60	55				Degrees
VSWR	1.5:1	1.5:1				

Mechanical Specifications

Housing Material Housing Plating/Color

Size Length Aluminum Powder Coat

13.4 in [340.36 mm]



Features:

- Aircraft Quality 6061-T6 Aluminum with 5/16' Elements with 360° Fully Welded to a 1' Boom
- Powder-Coated Balck for Corrosion, Fade, and Ice-Build Up Resistance
- Can be Installed for Either Vertical or Horizontal Polarization
- Comes with 36' LMR400 Pigtails with N-Type Female Connectors

Applications:

- 900 MHz Cellular and GSM
- 900 MHz ISM Band & Wireless LAN Systems
- Point to Multipoint & Non Line of Sight
- NLOS Applications
- RFID & SCADA
- LPWAN, LoRA, IoT, M2M

Fairview Microwave 301 Leora Ln., Suite 100 Lewisville, TX 75056 Tel: 1-800-715-4396 / (972) 649-6678 Fax: (972) 649-6689 www.fairviewmicrowave.com sales@fairviewmicrowave.com Fairview Microwave





Width Height Mounting Mast Diameter Weight 7.1 in [180.34 mm] 2.4 in [60.96 mm] 0.75 to 2 in [19.05 to 50.80 mm] 0.05 lbs [22.68 g]

Environmental Specifications

Temperature Operating Range Storage Range

Wind Loading Ingress Protection -40 to +60 deg C -40 to +140 deg C 200 MPH [321.87 KPH] IP55

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

880 MHz to 960 MHz, Heavy-Duty Yagi Antenna, 7dBi, N-female from Fairview Microwave is in-stock and available to ship same-day. All of our RF/microwave products are available off-the-shelf from our ISO 9001:2008 certified facilities in Lewisville, Texas. Fairview Microwave is RF on-demand.

For additional information on this product, please click the following link: 880 MHz to 960 MHz, Heavy-Duty Yagi Antenna, 7dBi, N-female FM51YA1019

URL: https://www.fairviewmicrowave.com/single-antenna-880-960-mhz-7-dbi-gain-n-fm51ya1019-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Fairview Microwave reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Fairview Microwave does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Fairview Microwave does not assume any liability arising out of the use of any part or documentation.

Fairview Microwave







301 Leora Ln., Suite 100, Lewisville, TX 75056 | Tel: 1-800-715-4396 / (972) 649-6678 / Fax: (972) 649-6689