

SP6T Normally Open Electro-Mechanical Relay Switch From DC to 22 GHz, 20 Watts, SMA

The FMSW6131 is an SP6T Electromechanical Relay Switch that operates over a wide frequency band from DC to 22 GHz and has a rating of 20 Watts input power (CW). Rated for 1M life cycles for high reliability operation, this design uses a Normally Open Actuator with a break before make configuration. The switch exhibits exceptional electrical performance specified from 0.3 dB max for insertion loss and 75 dB min for isolation, and guaranteed over -55°C to +85°C. The assembly requires an operating voltage of +28Vdc and is certified as RoHS compliant. External connectors include solder terminals and SMA female connectors.

Electrical Specifications

Switch Type	SP6T, Reflective
Actuator Type	Normally Open
Switching Sequence	Break Before Make

Description	Min	Typ	Max	Units
Frequency Range	DC		22	GHz
Impedance		50		Ohms
Operating Voltage		28		Volts
Actuating Current @ 28 Volts		135		mA
VSWR			1.6:1	
Insertion Loss			0.6	dB
Isolation	60			dB
Input Power (CW) (at 22 GHz)			20	Watts

Performance by Frequency

Description	F1	F2	F3	F4	F5	Units
Frequency Range	DC - 4	4 - 8	8 - 12	12 - 18	18 - 22	GHz
VSWR, Max	1.2:1	1.3:1	1.4:1	1.5:1	1.6:1	
Insertion Loss, Max	0.3	0.35	0.4	0.5	0.6	dB
Isolation, Min	75	70	65	60	60	dB

Mechanical Specifications

Size	
Length	1.75 in [44.45 mm]
Width/Diameter	1.75 in [44.45 mm]
Height	1.75 in [44.45 mm]
Weight	0.348 lbs [157.85 g]
Body Material and Plating	Aluminum
Package Type	Connectorized Module
Operating Life	1,000,000 Cycles
Switching Time	15 ms Max



Features:

- Single Pole Six Throw Relay Switch
- DC to 22 GHz Frequency Range
- 1M Cycle Operating Life Min
- Normally Open Actuator
- Insertion Loss 0.6 dB max
- Isolation 60 dB min
- 20 Watts Avg Power Max
- Switching Sequence Break Before Make

Applications:

- Test & Measurement
- Communications System
- Instrumentation

Fairview Microwave
1130 Junction Dr. #100
Allen, TX 75013
Tel: 1-800-715-4396 / (972) 649-6678
Fax: (972) 649-6689
www.fairviewmicrowave.com
sales@fairviewmicrowave.com

Connectors

RF Connector Type	SMA Female
RF Connector Contact Material & Plating	Beryllium Copper, Gold
RF Connector Body Material & Plating	Passivated Stainless Steel
Control Connector	Solder Pin

Environmental Specifications

Temperature

Operating Range	-55 to +85 deg C
ESD Sensitivity	ESD Sensitive Material. Transport material in Approved ESD bags. Handle in approved ESD Workstation.



Environmental Specification Notes:
 Designed to meet MIL-DTL-3928



Compliance Certifications (visit www.FairviewMicrowave.com for current document)


RoHS Compliant

Plotted and Other Data

Notes:

Typical Performance Data






SP6T Normally Open Electro-Mechanical Relay Switch From DC to 22 GHz, 20 Watts, SMA from Fairview Microwave is in-stock and available to ship same-day. All of our RF/microwave products are available off-the-shelf from our ISO 9001:2008 certified facilities in Allen, Texas. Fairview Microwave is RF on-demand.

For additional information on this product, please click the following link: [SP6T Normally Open Electro-Mechanical Relay Switch From DC to 22 GHz, 20 Watts, SMA FMSW6131](http://www.fairviewmicrowave.com/sp6t-normally-open-electro-mechanical-relay-switch-fmsw6131-p.aspx)

URL: <http://www.fairviewmicrowave.com/sp6t-normally-open-electro-mechanical-relay-switch-fmsw6131-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Fairview Microwave reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Fairview Microwave does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Fairview Microwave does not assume any liability arising out of the use of any part or documentation.



UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES.
TOLERANCES ARE:

DECIMALS	ANGLES	FRACTIONS
.XX ± .03	± 1°	± 1/16
.XXX ± .010		

HOLE DIAMETER	TOLERANCE
.0135 TO .125	+.004/-0.001
.126 TO .250	+.005/-0.001
.251 TO .500	+.006/-0.001
.501 TO .750	+.008/-0.001
.751 TO 1.000	+.010/-0.001
1.001 TO 2.000	+.012/-0.001

* THESE DIMENSIONS AND TOLERANCES
SUPERSEDE NOTE #1 ON TITLE BLOCK.


FAIRVIEW MICROWAVE INC.
ALLEN, TX 75013 WWW.FAIRVIEWMICROWAVE.COM

NOTES:

1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES [mm].

TITLE
SP6T Normally Open Electro-Mechanical Relay Switch
From DC to 22 GHz, 20 Watts, SMA

DWG NO	FMSW6131	CAGE CODE	3FKR5
CAD FILE	031915	SHEET	SCALE N/A SIZE A 200



<div>FAIRVIEW MICROWAVE INC.</div> <div>ALLEN, TX 75013 WWW.FAIRVIEWMICROWAVE.COM</div>		<div>NOTES:</div> <div>1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.</div> <div>2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.</div> <div>3. DIMENSIONS ARE IN INCHES [mm].</div>			
<div>TITLE</div> <div>SP6T Normally Open Electro-Mechanical Relay Switch</div> <div>From DC to 22 GHz, 20 Watts, SMA</div>		<div>DWG NO</div> <div>FMSW6131</div>		<div>CAGE CODE</div> <div>3FKR5</div>	
<div>CAD FILE</div> <div>031215</div>		<div>SHEET</div>		<div>SCALE</div> <div>N/A</div>	<div>SIZE</div> <div>A</div>
				<div>200</div>	