

Smarteq™ MiniBlade Omnidirectional Wi-Fi 6E, CBRS 5G Antenna

Cellular Antennas (5G, LTE, CBRS, 3G, 2G) - Omnidirectional

710599, 710629, 710630, 710631



Description


Slim and compact cellular antenna that delivers reliable connectivity.

Technologies

- 2.4 / 3.5 / 5 / 6GHz
- Wi-Fi 6E/Wi-Fi 7
- Bluetooth®

Features

- 5G ready
- Easy installations with adhesive mount on glass or non-conductive surface
- Slim and flexible design made it suitable for curved surface mounting



Smarteq™ MiniBlade Omnidirectional Wi-Fi 6E, CBR5 5G Antenna

Cellular Antennas (5G, LTE, CBR5, 3G, 2G) - Omnidirectional

Smarteq™ MiniBlade is an adhesive mounted omnidirectional ultra-wideband antenna capable of supporting radio systems operating in the 2400 to 7200MHz spectrum. Wi-Fi 6E/Wi-Fi 7, Bluetooth®, V2X and 5G ready, which make the MiniBlade antenna the perfect choice for applications such as indoor Wi-Fi coverage, internet onboard buses, EV-chargers, Wi-Fi zones, and Wi-Fi supported devices. Its superior RF performance enables high connectivity and throughput.

Features

- Wi-Fi 6E/Wi-Fi 7, Bluetooth®, V2X and 5G ready
- 2400 - 7200MHz
- Easy installations with adhesive mount on glass or non-conductive surface
- Slim and flexible design made it suitable for curved surface mounting
- IP 65

Applications

- Off-Highway Vehicle (OHV)
- ECU/Gateway
- Smart Metering
- Smart City
- EV-chargers
- Industrial IoT

Certifications



SPECIFICATIONS



Smarteq™ MiniBlade Omnidirectional Wi-Fi 6E, CBRS 5G Antenna

Cellular Antennas (5G, LTE, CBRS, 3G, 2G) - Omnidirectional

Standard Configurations

Model	Cable	Cable Length	Connector	Housing Color
710599	RG316	1.5m	SMA-m	Black
710629	RG316	0.5m	SMA-m	Black
710630	RG316	0.2m	SMA-m	Black
710631	RG316	0.5m	RP SMA-m	Black

Electrical Specifications – RF Antennas (All Models)

Frequency Ranges	VSWR	Max. 3D Gain	Efficiency	Nominal Impedance	Polarization	Radiation Pattern
2400 - 2485 MHz	2:1	3.8dBi	79%	50Ω	Linear	Omnidirectional
3400 - 3800 MHz	2:1	5dBi	71%			
4900 - 5950 MHz	2:1	7dBi	64%			
5925 - 7125 MHz	3:1	5dBi	33%			

Mechanical and Environmental Specifications (All Models)

Physical

Dimensions (L x W x H)	55.6 x 23.6 x 6.6mm (incl. 1.1mm 3M adhesive)
Weight	~ 35g (incl. 1.5m cable with SMA connector)
Material	Dryflex, FR4
Operating / Storage Temperature	-40°C to +85°C
IP Class	IP 65

Extension Cables

Part Number	Cable Length	Connector	Gender	Color
LL58 Cable				
201417-1	3m	SMA	Female/Male	White
201417-2	5m	SMA	Female/Male	White
201417-3	10m	SMA	Female/Male	White
201417-7	5m	SMA	Female/Male	Black
Low Loss Cable				
707220	3m	SMA	Female/Male	Black
710298	5m	SMA	Female/Male	Black
201417-3	10m	SMA	Female/Male	Black

* RF data with the antenna mounted on plastic 5mm thick and 20cm long cable

CONTACT US

**For more information about
this product contact your
sales representative or visit
> pctel.com/antenna-products**

Solving Complex Wireless Challenges

PCTEL is a leading global provider of wireless technology solutions, including purpose-built Industrial IoT devices, antenna systems, and test and measurement products. Trusted by our customers for 29 years, we solve complex wireless challenges to help organizations stay connected, transform, and grow.



PCTEL, Inc.

T: +1 630 372 6800 | pctel.com

Specifications subject to change without notice. PCTEL® and Smarteq™ are trademarks or registered trademarks of PCTEL, Inc. ©2023 PCTEL, Inc. All rights reserved. (December 5, 2023)