



5 Watts WR-229 Waveguide Load 3.22 GHz to 4.9 GHz, Aluminum with CPR-229F Flange

Waveguide Terminations Technical Data Sheet

PE-W229TR1001

Features

- WR-229 Waveguide
- Operating Frequency Range from 3.22 GHz to 4.9 GHz
- CPR-229F Flange
- 1.03:1 Max VSWR
- 5 Watts Average Power Handling

Applications

- Radar Systems
- Military and Space
- Wireless Radio Systems
- Telecom Infrastructure
- Communication Systems
- R&D Labs
- Microwave Radio Systems

Description

The PE-W229TR1001 is a WR-229 waveguide termination/load that operates in the frequency range of 3.22 GHz to 4.9 GHz. This WR-229 waveguide termination has a Max VSWR of 1.03:1. This waveguide termination design is made of painted aluminum and incorporates a CPR-229F flange. Waveguide terminations are part of Pasternack's comprehensive waveguide product offerings which are available in stock and ready for same-day shipment.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	3.22		4.9	GHz
VSWR			1.03:1	
Input Power (CW)			5	Watts

Mechanical Specifications

Size	
Length	9.84 in [249.94 mm]
Width/Dia.	2.75 in [69.85 mm]
Height	3.87 in [98.3 mm]
Weight	0.5 lbs [226.8 g]

Description	Flange	Waveguide
Designation		WR-229
Type	CPR-229F	
Material	Aluminum	Aluminum
Plating		Chromate
Finish		Grey paint

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [5 Watts WR-229 Waveguide Load 3.22 GHz to 4.9 GHz, Aluminum with CPR-229F Flange PE-W229TR1001](#)



5 Watts WR-229 Waveguide Load 3.22 GHz to
4.9 GHz, Aluminum with CPR-229F Flange

Waveguide Terminations Technical Data Sheet

PE-W229TR1001

Environmental Specifications

Temperature

Operating Range

-40 to +70 deg C

Compliance Certifications (see [product page](#) for current document)

Notes:

5 Watts WR-229 Waveguide Load 3.22 GHz to 4.9 GHz, Aluminum with CPR-229F Flange from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [5 Watts WR-229 Waveguide Load 3.22 GHz to 4.9 GHz, Aluminum with CPR-229F Flange PE-W229TR1001](#)

URL: <https://www.pasternack.com/5-watts-wr-229-rf-load-3.22-4.9-ghz-instrumentation-grade-pe-w229tr1001-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

