



2 Watts WR-28 Waveguide Load 29.4 GHz to 31 GHz,
Aluminum with UG Square Cover Flange

Waveguide Terminations Technical Data Sheet

PE-W28TR1002

Features

- WR-28 Waveguide
- Operating Frequency Range from 29.4 GHz to 31 GHz
- UG Square Cover Flange
- 1.15:1 Max VSWR
- 2 Watts Average Power Handling

Applications

- Radar Systems
- Military and Space
- Wireless Radio Systems
- Telecom Infrastructure
- Communication Systems
- R&D Labs
- Microwave Radio Systems

Description

The PE-W28TR1002 is a WR-28 waveguide termination/load that operates in the frequency range of 29.4 GHz to 31 GHz. This WR-28 waveguide termination has a Max VSWR of 1.15:1. This waveguide termination design is made of painted aluminum and incorporates a standard UG Square Cover flange. Waveguide terminations are part of Pasternack's comprehensive waveguide product offerings which are available in stock and ready for same-day shipment.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	29.4		31	GHz
VSWR			1.15:1	
Input Power (CW)			2	Watts

Mechanical Specifications

Size	
Length	0.59 in [14.99 mm]
Width/Dia.	0.75 in [19.05 mm]
Height	0.75 in [19.05 mm]

Description	Flange	Waveguide
Designation	UG-599/U	WR-28
Type	Square Cover	
Material	Aluminum	Aluminum
Plating		Chromate
Finish		Grey paint

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [2 Watts WR-28 Waveguide Load 29.4 GHz to 31 GHz, Aluminum with UG Square Cover Flange PE-W28TR1002](#)



2 Watts WR-28 Waveguide Load 29.4 GHz to 31 GHz,
Aluminum with UG Square Cover Flange

Waveguide Terminations Technical Data Sheet

PE-W28TR1002

Compliance Certifications (see [product page](#) for current document)

Notes:

2 Watts WR-28 Waveguide Load 29.4 GHz to 31 GHz, Aluminum with UG Square Cover Flange from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [2 Watts WR-28 Waveguide Load 29.4 GHz to 31 GHz, Aluminum with UG Square Cover Flange PE-W28TR1002](#)


URL: <https://www.pasternack.com/2-watts-wr-28-rf-load-29.4-31-ghz-instrumentation-grade-pe-w28tr1002-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE-W28TR1002 CAD Drawing

2 Watts WR-28 Waveguide Load 29.4 GHz to 31 GHz,
Aluminum with UG Square Cover Flange

REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	3/31/2021	S.PONG



UNLESS OTHERWISE SPECIFIED
LEADING DIMENSIONS ARE INCHES
DIMENSIONS IN [] ARE MILLIMETERS

TOLERANCES:

X = ± .2	[5.08]	FRACTIONS
.XX = ± .02	[.51]	± 1/32
.XXX = ± .005	[.13]	ANGLES ± 1°

CABLE LENGTH (L) TOLERANCES:

L ≤ 12 [305]	± .1 [25]	/ -0
12 [305] < L ≤ 60 [1524]	± .2 [51]	/ -0
60 [1524] < L ≤ 120 [3048]	± .4 [102]	/ -0
120 [3048] < L ≤ 300 [7620]	± .6 [152]	/ -0
300 [7620] < L	± .5% L	/ -0

ALL DIMENSIONS SHOWN
ARE FOR REFERENCE ONLY.

PE PASTERNAK
an INFINITI® brand

Pasternack Enterprises, Inc.
P.O. Box 16759, Irvine, CA 92623.
Phone: 1.949.261.1920 | 1.866.727.8376
Fax: 1.949.261.7451
Website: www.pasternack.com
E-mail: sales@pasternack.com

THIRD-ANGLE PROJECTION

THE INFORMATION AND
DESIGN IN THIS DOCUMENT
IS THE PROPERTY OF
PASTERNAK CORPORATION
ALL RIGHTS RESERVED.

SHEET 1 OF 1
SCALE N/A

SIZE CAGE CODE DRAWN BY ITEM NO. REV

A 53919 K.DANG PE-W28TR1002 A

NOTES:

1. LABEL PER ILS-100-09. FOR INTERNAL USE ONLY.
LABEL LOCATION FOR REFERENCE ONLY.

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE
WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.